



**BARGE "FMT-6001"
FLORIDA MARINE
INNAGE TABLE**

**SLOP TANK
PORT**

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. TO-002

#	0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.	15 FT.
0	0.00	26.65	53.30	79.95	106.60											
1/4	0.56	27.20	53.85	80.50	107.15											
1/2	1.11	27.76	54.41	81.06	107.71											
3/4	1.67	28.32	54.96	81.61	108.26											
1	2.22	28.87	55.52	82.17	108.82											
1/4	2.78	29.43	56.08	82.72	109.37											
1/2	3.33	29.98	56.63	83.28	109.93											
3/4	3.89	30.54	57.19	83.84	110.48											
2	4.44	31.09	57.74	84.39	111.04											
1/4	5.00	31.65	58.30	84.95	111.60											
1/2	5.55	32.20	58.85	85.50	112.15											
3/4	6.11	32.76	59.41	86.06	112.71											
3	6.66	33.31	59.96	86.61	113.26											
1/4	7.22	33.87	60.52	87.17	113.82											
1/2	7.77	34.42	61.07	87.72	114.37											
3/4	8.33	34.98	61.63	88.28	114.93											
4	8.88	35.53	62.18	88.83	115.48											
1/4	9.44	36.09	62.74	89.39	116.04											
1/2	9.99	36.64	63.29	89.94	116.59											
3/4	10.55	37.20	63.85	90.50	117.15											
5	11.10	37.75	64.40	91.05	117.70											
1/4	11.66	38.31	64.96	91.61	118.26											
1/2	12.21	38.86	65.51	92.16	118.81											
3/4	12.77	39.42	66.07	92.72	119.37											
6	13.32	39.97	66.62	93.27	119.92											
1/4	13.88	40.53	67.18	93.83	120.48											
1/2	14.44	41.08	67.73	94.38	121.03											
3/4	14.99	41.64	68.29	94.94	121.59											
7	15.55	42.20	68.84	95.49	122.14											
1/4	16.10	42.75	69.40	96.05	122.70											
1/2	16.66	43.31	69.96	96.60	123.25											
3/4	17.21	43.86	70.51	97.16	123.81											
8	17.77	44.42	71.07	97.72	124.36											
1/4	18.32	44.97	71.62	98.27	124.92											
1/2	18.88	45.53	72.18	98.83	125.48											
3/4	19.43	46.08	72.73	99.38	126.03											
9	19.99	46.64	73.29	99.94	126.59											
1/4	20.54	47.19	73.84	100.49	127.14											
1/2	21.10	47.75	74.40	101.05	127.70											
3/4	21.65	48.30	74.95	101.60	128.25											
10	22.21	48.86	75.51	102.16	128.81											
1/4	22.76	49.41	76.06	102.71	129.36											
1/2	23.32	49.97	76.62	103.27	129.92											
3/4	23.87	50.52	77.17	103.82												
11	24.43	51.08	77.73	104.38												
1/4	24.99	51.63	78.28	104.93												
1/2	25.54	52.19	78.84	105.49												
3/4	26.09	52.74	79.39	106.04												

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 1/26/2015

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE



BARGE "FMT-6001"
FLORIDA MARINE
INNAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO TO-002

Table with columns for gauge height (0 FT to 14 FT) and corresponding capacity values for two ports (left and right). Includes a sub-header 'CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS'.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 01/26/2015

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT 15'-9 1/2" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT 15'-9 1/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE





BARGE "FMT-6001" FLORIDA MARINE

OUTAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. TO-002

Table with 18 columns representing gauge heights from 2 FT. to 17 FT. and multiple rows for different gauge locations (0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17).

CAPACITIES GIVEN IN BARRELS OR 42 U.S. GALLONS

STRAPPED: 1/2x2/015

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT 17'-3 1/2" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

Inspectorate America Corporation logo



BARGE "FMT-6001" FLORIDA MARINE

OUTAGE TABLE

2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. TO-002

Table with 17 columns (0 FT. to 15 FT.) and 17 rows (0 to 15). Each cell contains a numerical value representing gauge height and capacity. Includes a note: CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/26/015

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT 15'-9 1/4" (TO RIM OF 2" DIA BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

Inspectorate America Corporation logo



**BARGE "FMT-6001"
FLORIDA MARINE
OUTGAGE TABLE**

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.	15 FT.
0	5,466.08	5,119.90	4,779.82	4,439.74	4,099.66	3,759.58	3,419.50	3,079.42	2,739.34	2,399.26	2,059.18	1,719.10	1,379.02	1,038.94	698.86
1	5,459.27	5,113.09	4,773.01	4,432.93	4,092.85	3,752.77	3,412.69	3,072.61	2,732.53	2,392.45	2,052.37	1,712.29	1,372.21	1,032.13	692.05
2	5,452.46	5,109.28	4,769.20	4,429.12	4,089.04	3,748.96	3,408.88	3,068.80	2,728.72	2,388.64	2,048.56	1,708.48	1,368.40	1,028.32	685.87
3	5,445.65	5,105.51	4,764.52	4,424.44	4,084.36	3,744.28	3,404.20	3,064.12	2,724.04	2,383.96	2,043.88	1,703.80	1,363.72	1,023.64	681.68
4	5,438.84	5,101.74	4,759.84	4,419.76	4,079.68	3,739.60	3,399.52	3,059.44	2,719.36	2,379.28	2,039.20	1,699.12	1,359.04	1,019.46	677.49
5	5,432.03	5,097.97	4,755.16	4,415.08	4,075.00	3,734.92	3,394.84	3,054.76	2,714.68	2,374.60	2,034.52	1,694.44	1,354.36	1,015.27	673.30
6	5,425.22	5,094.20	4,750.48	4,410.40	4,070.32	3,730.24	3,390.16	3,050.08	2,710.00	2,369.92	2,029.84	1,689.76	1,349.68	1,011.08	669.11
7	5,418.41	5,090.43	4,745.80	4,405.72	4,065.64	3,725.56	3,385.48	3,045.40	2,705.32	2,365.24	2,025.16	1,685.08	1,345.00	1,006.90	664.92
8	5,411.60	5,086.66	4,741.12	4,401.04	4,061.28	3,720.88	3,380.80	3,040.72	2,700.64	2,360.56	2,020.48	1,680.40	1,340.32	1,002.72	660.73
9	5,404.79	5,082.89	4,736.44	4,396.36	4,056.92	3,716.20	3,376.12	3,036.04	2,696.00	2,355.88	2,015.80	1,675.72	1,335.64	998.54	656.54
10	5,397.98	5,079.12	4,731.76	4,391.68	4,052.56	3,711.52	3,371.44	3,031.36	2,691.36	2,351.20	2,011.12	1,671.04	1,330.96	994.35	652.35
11	5,391.17	5,075.35	4,727.08	4,387.00	4,048.20	3,706.84	3,366.76	3,026.68	2,686.72	2,346.52	2,006.44	1,666.36	1,326.28	990.16	648.16
12	5,384.36	5,071.58	4,722.40	4,382.32	4,043.84	3,702.16	3,362.08	3,022.00	2,682.08	2,341.84	2,001.76	1,661.68	1,321.60	985.97	643.97
13	5,377.55	5,067.81	4,717.72	4,377.64	4,039.48	3,697.48	3,357.40	3,017.32	2,677.44	2,337.16	1,997.08	1,657.00	1,316.92	981.78	639.78
14	5,370.74	5,064.04	4,713.04	4,372.96	4,035.12	3,692.80	3,352.72	3,012.64	2,672.80	2,332.48	1,992.40	1,652.32	1,312.24	977.59	635.59
15	5,363.93	5,060.27	4,708.36	4,368.30	4,030.76	3,688.12	3,348.04	3,007.96	2,668.16	2,327.84	1,987.72	1,647.64	1,307.56	973.40	631.40

* CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

REFERENCE GAUGE HEIGHT 15'-9 1/2" (TO RIM OF 2" DIA BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND INSPECTORATE WILL AFFIRM AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION
Signature

2 PORT

HULL NO. 002

STRAPPED: 1/26/2015



CGA/ALPHA BRG 2/88

INSPECTOR/BRG

**BARGE "FMT-6001"
FLORIDA MARINE
OUTAGE TABLE**

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 10-002

CAPACITY BELOW STRIKE POINT		REFERENCE GAUGE HEIGHT		17.3 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK)		GAUGE WITH HERMETIC GAUGE TAPE ONLY		WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE		INSPECTOR AMERICA CORPORATION	
0	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.	15 FT.
17 FT.	151.83	123.82	95.81	67.80	39.79	11.78					
16 FT.	142.83	114.82	86.81	58.80	30.79	2.78					
15 FT.	133.83	105.82	77.81	49.80	21.79	-1.22					
14 FT.	124.83	96.82	68.81	40.80	12.79	-7.22					
13 FT.	115.83	87.82	59.81	31.80	3.79	-12.22					
12 FT.	106.83	78.82	50.81	22.80	-5.22	-17.22					
11 FT.	97.83	69.82	41.81	13.80	-10.22	-22.22					
10 FT.	88.83	60.82	32.81	4.80	-15.22	-27.22					
9 FT.	79.83	51.82	23.81	-4.20	-20.22	-32.22					
8 FT.	70.83	42.82	14.81	-13.20	-25.22	-37.22					
7 FT.	61.83	33.82	5.81	-22.20	-30.22	-42.22					
6 FT.	52.83	24.82	-3.20	-31.20	-35.22	-47.22					
5 FT.	43.83	15.82	-12.20	-40.20	-40.22	-52.22					
4 FT.	34.83	6.82	-21.20	-49.20	-45.22	-57.22					
3 FT.	25.83	-2.20	-30.20	-58.20	-50.22	-62.22					
2 FT.	16.83	-11.20	-39.20	-67.20	-55.22	-67.22					
1 FT.	7.83	-20.20	-48.20	-76.20	-60.22	-72.22					
0	-1.20	-29.20	-57.20	-85.20	-65.22	-77.22					

STRAPPED: 1267015

Shaw

INSPECTOR AMERICA CORPORATION



**BARGE "FMT-6001"
FLORIDA MARINE
INNAGE TABLE**

**SLOP TANK
STAR**

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. TO-002

#	0 FT.	#	1 FT.	#	2 FT.	#	3 FT.	#	4 FT.	#	5 FT.	#	6 FT.	#	7 FT.	#	8 FT.	#	9 FT.	#	10 FT.	#	11 FT.	#	12 FT.	#	13 FT.	#	14 FT.	#	15 FT.	
0	0.00	0	25.97	0	51.95	0	77.92	0	103.89																							
1/4	0.54	1/4	26.51	1/4	52.49	1/4	78.46	1/4	104.43																							
1/2	1.08	1/2	27.06	1/2	53.03	1/2	79.00	1/2	104.97																							
3/4	1.62	3/4	27.60	3/4	53.57	3/4	79.54	3/4	105.51																							
1	2.16	1	28.14	1	54.11	1	80.08	1	106.06																							
1/4	2.71	1/4	28.68	1/4	54.65	1/4	80.62	1/4	106.60																							
1/2	3.25	1/2	29.22	1/2	55.19	1/2	81.17	1/2	107.14																							
3/4	3.79	3/4	29.76	3/4	55.73	3/4	81.71	3/4	107.68																							
1	4.33	2	30.30	2	56.27	2	82.26	2	108.22																							
1/4	4.87	1/4	30.84	1/4	56.82	1/4	82.79	1/4	108.78																							
1/2	5.41	1/2	31.38	1/2	57.36	1/2	83.33	1/2	109.30																							
3/4	5.95	3/4	31.92	3/4	57.90	3/4	83.87	3/4	109.84																							
1	6.49	3	32.47	3	58.44	3	84.41	3	110.38																							
1/4	7.03	1/4	33.01	1/4	58.98	1/4	84.95	1/4	110.93																							
1/2	7.58	1/2	33.55	1/2	59.52	1/2	85.49	1/2	111.47																							
3/4	8.12	3/4	34.09	3/4	60.06	3/4	86.03	3/4	112.01																							
1	8.66	4	34.63	4	60.60	4	86.58	4	112.55																							
1/4	9.20	1/4	35.17	1/4	61.14	1/4	87.12	1/4	113.09																							
1/2	9.74	1/2	35.71	1/2	61.68	1/2	87.66	1/2	113.63																							
3/4	10.28	3/4	36.25	3/4	62.23	3/4	88.20	3/4	114.17																							
1	10.82	5	36.79	5	62.77	5	88.74	5	114.71																							
1/4	11.36	1/4	37.34	1/4	63.31	1/4	89.28	1/4	115.25																							
1/2	11.90	1/2	37.88	1/2	63.85	1/2	89.82	1/2	115.80																							
3/4	12.45	3/4	38.42	3/4	64.39	3/4	90.36	3/4	116.34																							
1	12.99	6	38.96	6	64.93	6	90.90	6	116.88																							
1/4	13.53	1/4	39.50	1/4	65.47	1/4	91.45	1/4	117.42																							
1/2	14.07	1/2	40.04	1/2	66.01	1/2	91.99	1/2	117.96																							
3/4	14.61	3/4	40.58	3/4	66.56	3/4	92.53	3/4	118.50																							
1	15.15	7	41.12	7	67.10	7	93.07	7	119.04																							
1/4	15.69	1/4	41.66	1/4	67.64	1/4	93.61	1/4	119.68																							
1/2	16.23	1/2	42.21	1/2	68.18	1/2	94.15	1/2	120.12																							
3/4	16.77	3/4	42.75	3/4	68.72	3/4	94.69	3/4	120.67																							
1	17.32	8	43.29	8	69.26	8	95.23	8	121.21																							
1/4	17.86	1/4	43.83	1/4	69.80	1/4	95.77	1/4	121.75																							
1/2	18.40	1/2	44.37	1/2	70.34	1/2	96.32	1/2	122.29																							
3/4	18.94	3/4	44.91	3/4	70.88	3/4	96.86	3/4	122.83																							
1	19.48	9	45.45	9	71.43	9	97.40	9	123.37																							
1/4	20.02	1/4	45.99	1/4	71.97	1/4	97.94	1/4	123.91																							
1/2	20.56	1/2	46.53	1/2	72.51	1/2	98.48	1/2	124.45																							
3/4	21.10	3/4	47.08	3/4	73.05	3/4	99.02	3/4	124.99																							
1	21.64	10	47.62	10	73.59	10	99.56	10	125.54																							
1/4	22.18	1/4	48.16	1/4	74.13	1/4	100.10	1/4	126.08																							
1/2	22.73	1/2	48.70	1/2	74.67	1/2	100.64	1/2	126.62																							
3/4	23.27	3/4	49.24	3/4	75.21	3/4	101.19	3/4																								
1	23.81	11	49.78	11	75.75	11	101.73																									
1/4	24.35	1/4	50.32	1/4	76.30	1/4	102.27																									
1/2	24.89	1/2	50.86	1/2	76.84	1/2	102.81																									
3/4	25.43	3/4	51.40	3/4	77.38	3/4	103.35																									

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/20/2015

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

Inspectorate
INSPECTORATE AMERICA CORPORATION



FORM WATTS 904 29 1975

**BARGE "FMT-6001"
FLORIDA MARINE
OUTAGE TABLE**

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO TO 002		17 FT.		16 FT.		15 FT.		14 FT.		13 FT.		12 FT.		11 FT.		9 FT.		8 FT.		7 FT.		6 FT.		5 FT.		4 FT.		3 FT.		2 FT.	
0	0	4,818.83	4,855.91	4,898.99	4,940.44	4,980.55	5,020.44	5,060.11	5,100.55	5,140.77	5,180.77	5,220.55	5,260.11	5,300.55	5,340.77	5,380.55	5,420.11	5,460.55	5,500.77	5,540.55	5,580.11	5,620.55	5,660.77	5,700.55	5,740.11	5,780.55	5,820.77	5,860.55	5,900.11	5,940.55	5,980.77
1	1	4,797.17	4,834.25	4,871.33	4,907.41	4,942.49	4,977.57	5,012.65	5,047.73	5,082.81	5,117.89	5,152.97	5,188.05	5,223.13	5,258.21	5,293.29	5,328.37	5,363.45	5,398.53	5,433.61	5,468.69	5,503.77	5,538.85	5,573.93	5,609.01	5,644.09	5,679.17	5,714.25	5,749.33	5,784.41	5,819.49
2	2	4,775.51	4,812.59	4,849.67	4,886.75	4,923.83	4,960.91	4,998.00	5,035.08	5,072.16	5,109.24	5,146.32	5,183.40	5,220.48	5,257.56	5,294.64	5,331.72	5,368.80	5,405.88	5,442.96	5,480.04	5,517.12	5,554.20	5,591.28	5,628.36	5,665.44	5,702.52	5,739.60	5,776.68	5,813.76	5,850.84
3	3	4,753.85	4,790.93	4,828.01	4,865.09	4,902.17	4,939.25	4,976.33	5,013.41	5,050.49	5,087.57	5,124.65	5,161.73	5,198.81	5,235.89	5,272.97	5,310.05	5,347.13	5,384.21	5,421.29	5,458.37	5,495.45	5,532.53	5,569.61	5,606.69	5,643.77	5,680.85	5,717.93	5,755.01	5,792.09	5,829.17
4	4	4,732.19	4,769.27	4,806.35	4,843.43	4,880.51	4,917.59	4,954.67	4,991.75	5,028.83	5,065.91	5,103.00	5,140.08	5,177.16	5,214.24	5,251.32	5,288.40	5,325.48	5,362.56	5,399.64	5,436.72	5,473.80	5,510.88	5,547.96	5,585.04	5,622.12	5,659.20	5,696.28	5,733.36	5,770.44	5,807.52
5	5	4,710.53	4,747.61	4,784.69	4,821.77	4,858.85	4,895.93	4,933.01	4,970.09	5,007.17	5,044.25	5,081.33	5,118.41	5,155.49	5,192.57	5,229.65	5,266.73	5,303.81	5,340.89	5,377.97	5,415.05	5,452.13	5,489.21	5,526.29	5,563.37	5,600.45	5,637.53	5,674.61	5,711.69	5,748.77	5,785.85
6	6	4,688.87	4,725.95	4,763.03	4,800.11	4,837.19	4,874.27	4,911.35	4,948.43	4,985.51	5,022.59	5,059.67	5,096.75	5,133.83	5,170.91	5,208.00	5,245.08	5,282.16	5,319.24	5,356.32	5,393.40	5,430.48	5,467.56	5,504.64	5,541.72	5,578.80	5,615.88	5,652.96	5,690.04	5,727.12	5,764.20
7	7	4,667.21	4,704.29	4,741.37	4,778.45	4,815.53	4,852.61	4,889.69	4,926.77	4,963.85	5,000.93	5,038.01	5,075.09	5,112.17	5,149.25	5,186.33	5,223.41	5,260.49	5,297.57	5,334.65	5,371.73	5,408.81	5,445.89	5,482.97	5,520.05	5,557.13	5,594.21	5,631.29	5,668.37	5,705.45	5,742.53
8	8	4,645.55	4,682.63	4,719.71	4,756.79	4,793.87	4,830.95	4,868.03	4,905.11	4,942.19	4,979.27	5,016.35	5,053.43	5,090.51	5,127.59	5,164.67	5,201.75	5,238.83	5,275.91	5,313.00	5,350.08	5,387.16	5,424.24	5,461.32	5,498.40	5,535.48	5,572.56	5,609.64	5,646.72	5,683.80	5,720.88
9	9	4,623.89	4,660.97	4,698.05	4,735.13	4,772.21	4,809.29	4,846.37	4,883.45	4,920.53	4,957.61	4,994.69	5,031.77	5,068.85	5,105.93	5,143.01	5,180.09	5,217.17	5,254.25	5,291.33	5,328.41	5,365.49	5,402.57	5,439.65	5,476.73	5,513.81	5,550.89	5,587.97	5,625.05	5,662.13	5,699.21
10	10	4,602.23	4,639.31	4,676.39	4,713.47	4,750.55	4,787.63	4,824.71	4,861.79	4,898.87	4,935.95	4,973.03	5,010.11	5,047.19	5,084.27	5,121.35	5,158.43	5,195.51	5,232.59	5,269.67	5,306.75	5,343.83	5,380.91	5,418.00	5,455.08	5,492.16	5,529.24	5,566.32	5,603.40	5,640.48	5,677.56
11	11	4,580.57	4,617.65	4,654.73	4,691.81	4,728.89	4,765.97	4,803.05	4,840.13	4,877.21	4,914.29	4,951.37	4,988.45	5,025.53	5,062.61	5,099.69	5,136.77	5,173.85	5,210.93	5,248.01	5,285.09	5,322.17	5,359.25	5,396.33	5,433.41	5,470.49	5,507.57	5,544.65	5,581.73	5,618.81	5,655.89
12	12	4,558.91	4,596.00	4,633.08	4,670.16	4,707.24	4,744.32	4,781.40	4,818.48	4,855.56	4,892.64	4,929.72	4,966.80	5,003.88	5,040.96	5,078.04	5,115.12	5,152.20	5,189.28	5,226.36	5,263.44	5,300.52	5,337.60	5,374.68	5,411.76	5,448.84	5,485.92	5,523.00	5,560.08	5,597.16	5,634.24
13	13	4,537.25	4,574.33	4,611.41	4,648.49	4,685.57	4,722.65	4,759.73	4,796.81	4,833.89	4,870.97	4,908.05	4,945.13	4,982.21	5,019.29	5,056.37	5,093.45	5,130.53	5,167.61	5,204.69	5,241.77	5,278.85	5,315.93	5,353.01	5,390.09	5,427.17	5,464.25	5,501.33	5,538.41	5,575.49	5,612.57
14	14	4,515.59	4,552.67	4,589.75	4,626.83	4,663.91	4,701.00	4,738.08	4,775.16	4,812.24	4,849.32	4,886.40	4,923.48	4,960.56	4,997.64	5,034.72	5,071.80	5,108.88	5,145.96	5,183.04	5,220.12	5,257.20	5,294.28	5,331.36	5,368.44	5,405.52	5,442.60	5,479.68	5,516.76	5,553.84	5,590.92
15	15	4,493.93	4,531.01	4,568.09	4,605.17	4,642.25	4,679.33	4,716.41	4,753.49	4,790.57	4,827.65	4,864.73	4,901.81	4,938.89	4,975.97	5,013.05	5,050.13	5,087.21	5,124.29	5,161.37	5,198.45	5,235.53	5,272.61	5,309.69	5,346.77	5,383.85	5,420.93	5,458.01	5,495.09	5,532.17	5,569.25
16	16	4,472.27	4,509.35	4,546.43	4,583.51	4,620.59	4,657.67	4,694.75	4,731.83	4,768.91	4,806.00	4,843.08	4,880.16	4,917.24	4,954.32	4,991.40	5,028.48	5,065.56	5,102.64	5,139.72	5,176.80	5,213.88	5,250.96	5,288.04	5,325.12	5,362.20	5,399.28	5,436.36	5,473.44	5,510.52	5,547.60
17	17	4,450.61	4,487.69	4,524.77	4,561.85	4,598.93	4,636.01	4,673.09	4,710.17	4,747.25	4,784.33	4,821.41	4,858.49	4,895.57	4,932.65	4,969.73	5,006.81	5,043.89	5,080.97	5,118.05	5,155.13	5,192.21	5,229.29	5,266.37	5,303.45	5,340.53	5,377.61	5,414.69	5,451.77	5,488.85	5,525.93

REFERENCE GAUGE HEIGHT 17'-3 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK)

GAUGE WITH HERMETIC GAUGE TAPE ONLY.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

* CAPACITY BELOW STRIKE POINT

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS