2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

	vessel:F	mT /092	
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON			
		PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.	
		EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.	
		TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.	
	N/A	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.	
		CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.	
THE ABOVE	ITEMS CHECKED, TEST	ED AND VERIFIED BY	

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

OPERATION	IS SECTION 61.00-61.500		
	129094/		
DRTCO PERIN	MAXIMUM DADITO		
TANK(S) TESTED: ALL	PRESSURE INDICATOR: MANGETER		
VESSEL OWNER AND ADDRESS: FLORIDA MARINE REGORDE FIFTH ST. MANDEVILLE WA			
TES	T RESULTS		
TEST DATE: 11-24-24	1100		
D	BEGINNING TIME:		
ENDING PRESSURE: 28 OF HO			
TOTAL PRECSIBELOSS	ALLOW ABLET INSBURE		
TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"			
THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.3044, ALLD 13 CONSIDERED VAPOR TIGHT.			
	WITNESS: TARROD GOIN (PRINT) WITNESS: (SIGN) AFFILIATION OF WITNESS		
CALCULATION OF ALLOWABLE PRESSURE LOSS:			
0.861 x 15.7 x (4, 285 / 1/1)			
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI L = MAXIMUM LOADING RATE IN BARRELS PER V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF NOTES: 14.70psi = 406.8 inches of H2O 1 psi = 27.67 inches of H2O 1 inch = 25.40 mm 1 inch = 2.54 cm 1 oz. = 1.729 inches OF H2O			