

Florida Marine Transporters, Inc.

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL: FMT 1410
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46 CFR 35.35-70 AND 33 CFR 156.170 ON
PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY
WITHIN 10% OF ACCURACY. EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
TRANSFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
CHECKED AND IS CLEAR OF POLMERIZING CARGO.
THE ABOVE ITEMS CHECKED, TESTED, AND VERIFIED BY:

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

C10 1111 0	20041	
VESSEL: FMT 1410	OFFICIAL NUMBER: 1299465	
TESTING LOCATION: FMT Shipyard	MAXIMUM LOADING RATE (BPH) 4, 285	
TANK(S) TESTED: ALL	PRESSURE INDICATOR: MANAGETER	
VESSEL OWNER AND ADDRESS: American Inlay	Marine LLC 3838 N Carseway BLUBST 3335 metalice LA 7000Z	
TEST RESULTS		
TEST DATE 1-13-25		
BEGINNING PRESSURE: 28" # 42°	BEGINNING TIME: 0700	
ENDING PRESSURE 28" of H20	ENDING TIME 0800	
TOTAL PRESSURE LOSS:	ALLOWABLE PRESSURE LOSS: 5.2 OF HAD	
NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF TO	AL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"	
	CCORDANCE WITH SECTION 61.304F, AND IS ED VAPOR TIGHT. WITNESS: Adam Brand (PRINT WITNESS: (SIGN) FMT	
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AHILIATION OF WITNESS	
0.861 x 15.7. x (4,285 / 1/,	$\frac{\mathbf{O}(66)}{\mathbf{APL}} = \frac{5.2}{\mathbf{APL}}$	
IP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (I L = MAXIMUM LOADING RATE IN BARRELS PER HO V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF V NOTES: 14.70psi = 406.8 inches of H2O 1 psi = 27.67 inches of H2O 1 inch = 25.40 mm 1 inch = 2.54 cm 1 oz. = 1.729 inches OF H2O	DUR	