FMT

Florida Marine Transporters, Inc.

2360 Fifth Street Mandaville, LA 70471 (985) 629-2082 Phone (985) 629- 2110 Fax

HOSE AND PIPELINE TESTS

	PRESSURE CALLOTS
/	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRANSFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 126 P.S.I
NIA	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
	VAPOR PIPELINE HAS BEEN VISUALLY CHECKED AND IS CLEAR OF POLMERIZING CARGO.

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL EMT 1412	OFFICIAL NUMBER: 1299466		
TESTING LOCATION: FMT Skipped	MAXIMUM LOADING RATE (BPH) 4, 285		
TANKIS) TESTED: ALL	PRESSURE INDICATOR: MANOMETER		
VESSEL OWNER AND ADDRESS:	Marine LLC 3838 N Carseway DLVD SE 3335		
TEST RESULTS			
TEST DATE 1-16-25	W Ox		
BEGINNING PRESSURE: 28" # 442 °	BEGINNING TIME: 0800		
ENDING PRESSURE 28' of 420	ENDINGTIME 0900		
TOTAL PRESSURE LOSS:	ALLOWABLE PRESSURE LOSS: 5.2 of the		
NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF TOIL	IL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"		
THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT.			
TESTER: Carlos Dubon (PRINT)	WITNESS: Adam Brand (PRINT)		
TESTER: (SIGN)	WIINESS: (SIGN)		
Ψ "	FMT		
	AFFILIATION OF WITNESS		
CALCULATION OF ALLOWABLE PRESSURE LOSS:			
0.861 x 15.7. x(4,285 / 11.	066)= 5.2		
(IP) (L) (T	(APL)		
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (I L = MAXIMUM LOADING RATE IN BARRELS PER HE V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF V	DUR		
NOTES: 14.70psi = 406.8 inches of H2O			
1 psi = 27.67 inches of H2O			
1 inch = 25.46 mm			
1 inch = 2.54 cm			