2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

## HOSE AND PIPELINE TESTS

FMT 3005
CHECKED AND TESTED IN ACCORDANCE WITH 170 ON
w «
PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
ED AND VERIFIED BY:

Florida Marine Transporters Inc.

## MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FMT3005	OFFICIAL NUMBER: 1087895
TESTING LOCATION: STS FLT.	MAXIMUM LOADING RATE (BPH) 5,000
TANK(S) TESTED: ALL	PRESSURE INDICATOR: MANOMETER
VESSEL OWNER AND ADDRESS: FLORIDA MA	PINE 2360 FIFTH ST. WANTENLIE CH
TEST DATE: 11-22-24 TEST	RESULTS
BEGINNING PRESSURE: 28" OF 42°	BEGINNING TIME: 1300
24 440	ending time:
TOTAL PRESSURE LOSS:O	ALLOWABLE PRESSURE LOSS: 2.2" 1/20
CONSIDER	CORDANCE WITH SECTION 61.304F, AND IS ED VAPOR TIGHT.  WITNESS: LEC CHAMPAGAJE (PRINT)  WITNESS: (SIGN)
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AFFILIATION OF WITNESS
$0.861 \times 15.7 \times (5.000 / 30, (V))$	$\frac{706}{\text{(APL)}} = \frac{2.2}{\text{(APL)}}$
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1) L = MAXIMUM LOADING RATE IN BARRELS PER HOW = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WARD NOTES:  14.70psi = 406.8 inches of H2O 1 psi = 27.67 inches of H2O 1 inch = 25.40 mm 1 inch = 2.54 cm 1 oz. = 1.729 inches OF H2O	our de la company de la compan