A 11 A A

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

## HOSE AND PIPELINE TESTS

| vessel:   | FIMT 3026  |
|---|--|
| THE FOLLOWING ITEMS HAVE BEEN 46CFR 35.35-70 AND 33CFR 156. | CHECKED AND TESTED IN ACCORDANCE WITH 170 ON 9 -23-24  |
|   | PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.                                      |
|   | EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.  |
|   | TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.                           |
|   | ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I. |
| N/A   | CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.                                  |
|   |  |

THE ABOVE ITEMS CHECKED, TESTED AND VERIFIED BY:

Florida Marine Transporters Inc.

## MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 OFFICIAL NUMBER:\_\_\_ TESTING LOCATION: MOBILE AL. MAXIMUM LOADING RATE (BPH) 5,000

PRESSURE INDICATOR: MANOMETER TANK(S) TESTED.

| IANK(S) TESTED:        |               | A ALLOS GALLOS SERVICIONES |                       |
|------------------------|---------------|----------------------------|-----------------------|
| VESSEL OWNER AND ADDRI | ESS: KMT 2360 | FIFTH ST- MAN              | DEVILLE.              |
|                        |               | ST RESULTS                 | H.                    |
| TEST DATE: 9-23-2      | <u>.4</u>     |                            |                       |
| BEGINNING PRESSURE: 2  | 8" of HAO     | BEGINNING TIME:            | 1400                  |
| ENDING PRESSURE: 20    |               | ENDING TIME:               | 1430                  |
| TOTAL PRESSURE LOSS:   |               | ALLOWABLE PRESSU           | RE LOSS: 2.2" of 1/20 |

NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"

THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT.

(PRINT) (SIGN) AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS:  $0.861 \times \frac{15.7}{\text{(TP)}} \times (\frac{5,000}{\text{(L)}} \frac{30,706}{\text{(V)}}) = \frac{2.2}{\text{(APL)}}$ 

TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOURV = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER

NOTES: 14.70psi = 406.8 inches of H2O 1psi = 27.67 inches of H2O 1 inch = 25.40 mmlinch = 2.54 cm

loz. = 1.729 inches OF H2O