2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

## HOSE AND PIPELINE TESTS

vessel: F	MT 3036
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON	
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I,
	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
N/A	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
THE ABOVE ITEMS CHECKED, TESTED AND VERIFIED BY:	
William tonsitive	

V = VOLIIME OF TANK(5) IN BARRELS

NOTES:

APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER 14.70psi = 406.8 inches of H2O

 $l_{pSi} = 27.67$  inches of H2O

102- = 1.729 inches OF H2O

l inch = 25.40 mm linch = 2.54 cm

Florida Marine Transporters Inc.

## MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 OFFICIAL NUMBER: FMT 3036 TESTING LOCATION: TAYLORS BAYOU P.A. MAXIMUM LOADING RATE (BPH) PRESSURE INDICATOR: VESSELOWNER AND ADDRESS: FLORIDA TEST RESULTS 10-11-24 TEST DATE: 1300 BEGINNING TIME: BEGINNING PRESSURE: 1330 ENDING TIME: ENDING PRESSURE: ALLOWABLE PRESSURE LOSS: TOTAL PRESSURE LOSS: NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" . ... THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. (PRINT) WITNESS: (SIGN) AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR