















BARGE "FMT-3042" FLORIDA MARINE

OUTAGE TABLE

2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2090-1

Table with 21 columns representing gauges from 0 FT. to 15 FT. and 34 rows of depth measurements (0, 1/4, 1/2, 3/4) for each gauge, listing capacity values in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/11/00

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature and Inspectorate America Corporation text



BARGE "FMT-3042" FLORIDA MARINE

OUTAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2090-1

Table with columns for depth (0 to 15 FT.) and capacity in barrels (0 to 3/4). Includes a vertical line on the left side.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/1/00

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature

INSPECTORATE AMERICA CORPORATION





# BARGE "FMT-3042"

## FLORIDA MARINE

HULL NO. 2090-1

CORRECTION TABLE FOR TRIM AFT.

### FOR INNGAGE GAUGES ONLY

TRIM	TANKS NO. 1	TANKS NO. 2	TANKS NO. 3
	PORT OR STAR.	PORT OR STAR.	PORT OR STAR.
0'-6"	NIL	NIL	NIL
1'-0"	NIL	NIL	NIL
1'-6"	NIL	NIL	NIL
2'-0"	NIL	NIL	NIL
2'-6"	NIL	NIL	NIL
3'-0"	NIL	NIL	NIL
3'-6"	NIL	NIL	NIL
4'-0"	(-) 0'-0 1/8"	NIL	NIL
4'-6"	(-) 0'-0 1/8"	(+) 0'-0 1/8"	NIL
5'-0"	(-) 0'-0 1/8"	(+) 0'-0 1/8"	NIL

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED, TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 12/11/00 BY:   
INSPECTORATE AMERICA CORPORATION