



INSPECTORATE

BARGE "FMT-3051"

FLORIDA MARINE

HULL NO.2113-2

CORRECTION TABLE FOR TRIM AFT.


FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	(+) 0'-0 1/8"	(-) 0'-0 1/8"
1'-0"	(-) 0'-0 1/8"	(+) 0'-0 1/8"	(-) 0'-0 1/8"
1'-6"	(-) 0'-0 1/8"	(+) 0'-0 1/4"	(-) 0'-0 1/8"
2'-0"	(-) 0'-0 1/4"	(+) 0'-0 1/4"	(-) 0'-0 1/4"
2'-6"	(-) 0'-0 1/4"	(+) 0'-0 3/8"	(-) 0'-0 1/4"
3'-0"	(-) 0'-0 1/4"	(+) 0'-0 3/8"	(-) 0'-0 3/8"
3'-6"	(-) 0'-0 3/8"	(+) 0'-0 1/2"	(-) 0'-0 3/8"
4'-0"	(-) 0'-0 3/8"	(+) 0'-0 1/2"	(-) 0'-0 1/2"
4'-6"	(-) 0'-0 3/8"	(+) 0'-0 5/8"	(-) 0'-0 1/2"
5'-0"	(-) 0'-0 1/2"	(+) 0'-0 5/8"	(-) 0'-0 5/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 11/19/02 BY: 
INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3051"
FLORIDA MARINE
INNAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2113-2

Table with columns for height (0 FT. to 14 FT.) and corresponding capacity values for each measurement.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 11/19/02

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-5 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and name



BARGE "FMT-3051" FLORIDA MARINE

OUTGAUGE TABLE

2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2113-2

Table with 15 columns for gauge heights (0 FT. to 15 FT.) and rows for different gauge readings (0, 1/4, 1/2, 3/4) at each height. Values represent capacities in barrels of 42 U.S. gallons.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 11/19/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION logo



BARGE "FMT-3051" FLORIDA MARINE

OUTAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2113-2

Table with columns for gauge height (0 FT. to 15 FT.) and rows for measurement points (0, 1/4, 1/2, 3/4). Each cell contains a numerical value representing capacity.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 11/19/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and logo



BARGE "FMT-3051" FLORIDA MARINE

OUTAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2113-2

Table with 18 columns (2 FT. to 17 FT.) and multiple rows of capacity data. Includes a diagonal line through the first 5 columns.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 11/19/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 17'-0" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3051"
FLORIDA MARINE

OUTAGE TABLE

2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2113-2

Table with 17 columns (2 FT. to 16 FT.) and 4 rows per column (0, 1/4, 1/2, 3/4). Each cell contains numerical data representing measurements at different depths and locations.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 11/19/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-10 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3051" FLORIDA MARINE

OUTAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2113-2

Table with columns for gauge height (2 FT. to 16 FT.) and rows for measurement points (0, 1/4, 1/2, 3/4). Each cell contains a numerical value representing the measurement at that point.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 11/19/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 16'-11" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of an inspector

INSPECTORATE AMERICA CORPORATION