FIOTIDA Marine Transporters, Inc.

675 N. Causeway Blvd. Mandeville, LA 70448 (385) 629-2082 Phone (385) 629-2110 Fax

HOSE AND PIPELINE TESTS

	āŤ	2
	vessel:	MT 3053
	*	* × 26
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON		
		at B
¥ .		PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
ē.		EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
;		TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
		ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
	NA	CARGO HOSE VISUALL (AND HYDROSTATICALLY CHECKED TO 2015 P.S.I.
		er _{er} er
THE ABOVE	ITEMS CHECKED, TEST	ED AND VERIFIED BY:
	390	104

l inch = 25.40 mm l inch = 2.54 cm

10z. = 1.729 inches OF H2O

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306 VESSEL: FMT 3053 OFFICIAL NUMBER:_ TESTING LOCATION: MT. VERNON MAXIMUM LOADING RATE (BPH) 5,000 TANK(S) TESTED: ALL PRESSURE INDICATOR: MANOMETER VESSEL OWNER AND ADDRESS: FLORIDA MARINE 2360 FIFTH ST. MANDEVILLE 4A TEST RESULTS TEST DATE: 2-24-25 BEGINNING TIME: /300 BEGINNING PRESSURE: 28" OF 442 0 ENDING TIME: ____ ENDING PRESSURE: 28" OF 1420 ALLOWABLE PRESSURE LOSS: 2.2 LA 0 TOTAL PRESSURE LOSS: ______ NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. MOW VPRINT) WITNESS: _ (SIGN) TESTER: AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: 0.861 x (TP) x (S,000) (S,000)TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER 14.70psi = 406.8 inches of H2O NOTES: 1psi = 27.67 inches of H2O