

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL:	MT 3063	
	£*	
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON 12-8-24		
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.	
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.	
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.	
	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.	
N/A	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.	
THE ABOVE ITEMS CHECKED, TEST	ED AND VERIFIED BY:	

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FMT 3063	OFFICIAL NUMBER: 1205483
TESTING LOCATION: BUPFALO FLT.	MAXIMUM LOADING RATE (BPH) 5,000
	PRESSURE INDICATOR: MANGRER
VESSEL OWNER AND ADDRESS: DLOC DA MIN	PINE 2360 FIFTH ST. MANDENNE CA
TEST DATE: 12-8-24 TEST	T RESULTS
BEGINNING PRESSURE: 29" of Ha	BEGINNING TIME: 1300
ENDING PRESSURE: 38 64120	ENDING TIME:
TOTAL PRESSURE LOSS:	ALLOWABLE PRESSURE LOSS: 2.2" 1/20
CONSIDER	FMF
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AFFILIATION OF WITNESS
0.861 × 15.7 × 5.000 / 30,	$ \frac{706}{\text{(APL)}} = \frac{2.2}{\text{(APL)}} $
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (I L = MAXIMUM LOADING RATE IN BARRELS PER H V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF V NOTES: 14.70psi = 406.8 inches of H2O 1 psi = 27.67 inches of H2O 1 inch = 25.40 mm 1 inch = 2.54 cm 1 oz. = 1.729 inches OF H2O	OUR