2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

		li .	2 5	
	VESSEL:	FMT 3070		
		*	***	
		BEEN CHECKED AND TE 156.170 ON		NCE WITH
		PRESSURE GAU	GES HAVE BEEN F ACCURACY.	CHECKED
27		EMERGENCY SHO	UTDOWN HAS BEEN ERABLE.	CHECKED
8			M RELIEF VALVE E HECKED - 125,P.S	
		ASSOCIATED V	R PIPING SYSTE ALVES HAVE BEEN AT 187.5 P.S.I.	TESTED
	NA	CARGO HOS HYDROSTATICAL	SE VISUALLY LLY CHECKED TO 22!	AND 5 P.S.I.
THE ABOVE	ITEMS CHECKED,	TESTED AND VERIFIE	ED BY:	
	120		119	

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FMT 3070	OFFICIAL NUMBER: 1117765
TESTING LOCATION: ERGON FUT.	MAXIMUM LOADING RATE (BPH) 5,000
TANKER TECTED. A44	PRESSURE INDICATOR: MANOMETER ARINE 2360 FIFTH ST. MANDEVILLE
TEST	RESULTS
BEGINNING PRESSURE: 18" OF HE O ENDING PRESSURE: 28" OF HE O	BEGINNING TIME: 1400
ENDING PRESSURE: 28"0FH+0	ENDING TIME: 1430
TOTAL PRESSURE LOSS: 0	ALLOWABLE PRESSURE LOSS: 2.2" H20
THIS VESSEL HAS BEEN TESTED IN ACCONSIDER TESTER: D. J. C. D. D. (PRINT)	CCORDANCE WITH SECTION 61.304F, AND IS ED VAPOR TIGHT. WITNESS: JARROD C.9 IN (PRINT) WITNESS: (SIGN)
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AFFILIATION OF WITNESS
$0.861 \times 15.7 \times (5,000) / 30$	(APL) = (APL)
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (L = MAXIMUM LOADING RATE IN BARRELS PER H V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF Y NOTES: 14.70psi = 406.8 inches of H2O 1psi = 27.67 inches of H2O 1 inch = 25.40 mm 1inch = 25.40 mm 1oz. = 1.729 inches OF H2O	OUR