



BARGE "FMT-3078"

FLORIDA MARINE


HULL NO. 2100-2

CORRECTION TABLE FOR TRIM AFT.			
FOR INNAGE GAUGES ONLY			
TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	NIL	NIL
1'-0"	NIL	(-) 0'- 0 1/8"	NIL
1'-6"	NIL	(-) 0'- 0 1/8"	NIL
2'-0"	NIL	(-) 0'- 0 1/8"	NIL
2'-6"	NIL	(-) 0'- 0 1/8"	NIL
3'-0"	NIL	(-) 0'- 0 1/4"	NIL
3'-6"	NIL	(-) 0'- 0 1/4"	(-) 0'- 0 1/8"
4'-0"	NIL	(-) 0'- 0 1/4"	(-) 0'- 0 1/8"
4'-6"	NIL	(-) 0'- 0 1/4"	(-) 0'- 0 1/8"
5'-0"	NIL	(-) 0'- 0 1/4"	(-) 0'- 0 1/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 11/19/01 BY: 
INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3078"
FLORIDA MARINE

OUTAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2100-2

Table with columns for gauge heights (0 FT. to 15 FT.) and rows for barge measurements (1/4, 1/2, 3/4, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11). Includes capacity values in barrels at the bottom of each row.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 11/19/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION logo



BARGE "FMT-3078" FLORIDA MARINE

OUTAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2100-2

Table with columns for height (0 FT. to 15 FT.) and capacity (0 to 4,904.59). Rows represent different gauge heights and capacities.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 11/19/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name

BARGE "FMT-3078"
FLORIDA MARINE

OUTAGE TABLE

2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2100-2

IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.	IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.	IN	15 FT.	IN	16 FT.
0		0	4,780.14	0	4,438.63	0	4,095.58	0	3,752.52	0	3,409.47	0	3,066.41	0	2,723.35	0	2,380.30	0	2,037.24	0	1,694.19	0	1,351.13	0	1,008.07	0	665.02	0	321.96
1		1	4,751.70	1	4,410.05	1	4,066.99	1	3,723.93	1	3,380.88	1	3,037.82	1	2,694.77	1	2,351.71	1	2,008.65	1	1,665.60	1	1,322.54	1	979.49	1	636.43	1	293.37
11		11	4,467.22	11	4,124.17	11	3,781.11	11	3,438.05	11	3,095.00	11	2,751.94	11	2,408.89	11	2,065.83	11	1,722.77	11	1,379.72	11	1,036.66	11	693.61	11	350.55	11	16.63

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 11/19/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
 GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.


 INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3078"
FLORIDA MARINE

OUTAGE TABLE

3 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2100-2

Table with 18 columns (IN, 2 FT. to 16 FT.) and multiple rows showing capacity data in barrels of 42 U.S. gallons. Includes a diagonal line across the first few rows.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-10 1/2" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY

STRAPPED: 11/19/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and name.



BARGE "FMT-3078"
FLORIDA MARINE

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2100-2

Table with 18 columns (IN, 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT., 15 FT., 16 FT.) and 20 rows (0 to 16 FT. depth). Each cell contains numerical values representing measurements.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY

STRAPPED: 11/19/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION