



BARGE "FMT-3082"

FLORIDA MARINE

HULL NO. 2104-2

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	NIL	NIL
1'-0"	NIL	(-) 0'- 0 1/8"	NIL
1'-6"	NIL	(-) 0'- 0 1/8"	NIL
2'-0"	NIL	(-) 0'- 0 1/8"	NIL
2'-6"	NIL	(-) 0'- 0 1/8"	NIL
3'-0"	NIL	(-) 0' - 0 1/4"	NIL
3'-6"	NIL	(-) 0' - 0 1/4"	(-) 0'- 0 1/8"
4'-0"	NIL	(-) 0' - 0 1/4"	(-) 0'- 0 1/8"
4'-6"	NIL	(-) 0' - 0 1/4"	(-) 0'- 0 1/8"
5'-0"	NIL	(-) 0' - 0 1/4"	(-) 0'- 0 1/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 3/28/02

BY:


INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3082" FLORIDA MARINE INNAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2104-2

Large innage table with 20 columns (0 FT. to 14 FT.) and multiple rows of capacity data. Includes a note: CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS.

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-5 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 3/28/02

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of the inspector.

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3082" FLORIDA MARINE INNAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2104-2

Table with columns for height (0 FT. to 14 FT.) and corresponding capacity values for each foot, including fractional increments (1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 3/28/02

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3082"
FLORIDA MARINE

OUTAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2104-2

Table with 18 columns (2 FT. to 16 FT.) and 20 rows. Each cell contains a number and a fraction (e.g., 0, 1/4, 1/2, 3/4) representing capacity at different gauge heights.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 16'-11 1/2" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY

STRAPPED: 3/26/02

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION text.



BARGE "FMT-3082" FLORIDA MARINE

OUTAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2104-2

Table with columns for gauge height (2 FT. to 16 FT.) and rows for various measurement points (0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11). Each cell contains a numerical value representing capacity or measurement.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

STRAPPED: 3/28/02

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name



BARGE "FMT-3082"
FLORIDA MARINE
OUTAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2104-2

Table with 18 columns representing 2 FT. to 17 FT. gauge heights and multiple rows of capacity data for various draft levels (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 17'-0 1/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY

STRAPPED: 3/28/02

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION text



BARGE "FMT-3082" FLORIDA MARINE

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2104-2

Table with columns for gauge height (2 FT. to 16 FT.) and rows for tank levels (0, 1/4, 1/2, 3/4). Each cell contains a capacity value in barrels of 42 U.S. gallons.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 3/28/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11 1/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and name.



BARGE "FMT-3082" FLORIDA MARINE

OUTAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2104-2

Table with columns for gauge height (0 FT. to 15 FT.) and corresponding capacity values in barrels. Includes a diagonal line on the left side of the table.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 3/28/02

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature and text: INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3082" FLORIDA MARINE

OUTAGE TABLE

3 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2104-2

Table with columns for gauge height (0 FT. to 15 FT.) and rows for various measurements (0, 1/4, 1/2, 3/4, 1, 1 1/4, 1 1/2, 2, 2 1/4, 3, 3 1/4, 4, 4 1/4, 5, 5 1/4, 6, 6 1/4, 7, 7 1/4, 8, 8 1/4, 9, 9 1/4, 10, 10 1/4, 11, 11 1/4, 12, 12 1/4, 13, 13 1/4, 14, 14 1/4, 15). Each cell contains a numerical value representing capacity in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 3/28/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature and text: INSPECTORATE AMERICA CORPORATION

