

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

## HOSE AND PIPELINE TESTS

VESSEL:	MT 3092	
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON		
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.	
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.	
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.	
~ / / / n	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.	
N I Pt	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.	
THE ABOVE ITEMS CHECKED, TESTED AND VERIFIED BY:		
±	Les Des of	

Florida Marine Transporters Inc.

## MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FMT 3093	OFFICIAL NUMBER: 112 7056
TESTING LOCATION: 5 T 5 FLT	MAXIMUM LOADING RATE (BPH) 5,000
	PRESSURE INDICATOR: MANAMETER
VESSEL OWNER AND ADDRESS: PLACIDA MY	RINE 2360FIFTHST MANDEVICCE, LA
	RESULTS
	BEGINNING TIME: 1330
ending pressure: 28" of H20	ENDINGTIME 1400
	ALLOWABLE PRESSURE LOSS: 2-2" JH20
CONSIDER	CCORDANCE WITH SECTION 61.304F, AND IS ED VAPOR TIGHT.  WITNESS: MATT BRAZZEL (PRINT)  WITNESS: (SIGN)
rester: 72 (SIGN)	WITNESS: (SIGN)  FMT  AFFILIATION OF WITNESS
CALCULATION OF ALLOWABLE PRESSURE LOSS:	
0.861 x 15.7 x ( 5,000 / 30, (TP) (L)	$\frac{706}{V} = \frac{Z. Z}{(APL)}$
FP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (I L = MAXIMUM LOADING RATE IN BARRELS PER H V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF V	OUR
NOTES: 14.70psi = 406.8 inches of H2O 1psi = 27.67 inches of H2O 1 inch = 25.40 mm linch = 2.54 cm 1oz. = 1.729 inches OF H2O	,