



BARGE "FMT-3096"

FLORIDA MARINE

HULL NO. 2107-6

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	(-) 0' - 0 1/8"	NIL
1'-0"	NIL	(-) 0' - 0 1/8"	NIL
1'-6"	NIL	(-) 0' - 0 1/4"	NIL
2'-0"	NIL	(-) 0' - 0 3/8"	NIL
2'-6"	NIL	(-) 0' - 0 3/8"	NIL
3'-0"	NIL	(-) 0' - 0 1/2"	NIL
3'-6"	NIL	(-) 0' - 0 5/8"	NIL
4'-0"	NIL	(-) 0' - 0 3/4"	NIL
4'-6"	NIL	(-) 0' - 0 3/4"	NIL
5'-0"	NIL	(-) 0' - 0 7/8"	NIL

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 6/13/02

BY:

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3096"
FLORIDA MARINE
INNAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2107-6

Table with 18 columns (0 FT. to 14 FT.) and multiple rows (0 to 3/4) showing capacity data in barrels for various depths and fractions.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/13/02

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-5 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of an inspector

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3096" FLORIDA MARINE INNAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2107-6

Table with columns for height (0 FT. to 14 FT.) and corresponding capacity values in barrels. Includes sub-columns for 1/4, 1/2, and 3/4 increments.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/13/02

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION logo



BARGE "FMT-3096" FLORIDA MARINE INNAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2107-6

Table with columns for height (0 FT. to 14 FT.) and corresponding capacity values for various gauge heights (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/13/02

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-5 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3096" FLORIDA MARINE

OUTAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2107-6

Table with 17 columns representing gauge heights from 0 FT. to 15 FT. and multiple rows for each height, showing capacity values in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/13/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-5 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION logo



BARGE "FMT-3096" FLORIDA MARINE

OUTAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2107-6

Table with 15 columns representing gauge heights (0 FT. to 15 FT.) and multiple rows for each height, showing capacity values in barrels. Includes a diagonal line on the left side of the table.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/13/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION logo



BARGE "FMT-3096" FLORIDA MARINE

OUTAGE TABLE

2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2107-6

Main data table with columns for gauge height (0 FT. to 15 FT.) and corresponding capacity values. Includes rows for 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 14, 1/2, 3/4, and 15 FT. gauges.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/13/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature and INSPECTORATE AMERICA CORPORATION logo



ARGE "FMT-3096" FLORIDA MARINE OUTAGE TABLE

3 STAR

ARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2107-6

Main data table with 22 columns for height (0 FT to 15 FT) and multiple rows for liquid levels and capacities.


CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/13/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.





BARGE "FMT-3096" FLORIDA MARINE

OUTAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2107-6

Table with columns for gauge height (2 FT. to 16 FT.) and rows for various measurements (0 to 11). Includes capacity values in barrels of 42 U.S. gallons.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/13/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11 1/2" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION logo.



BARGE "FMT-3096" FLORIDA MARINE

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2107-6

Table with columns for height (2 FT. to 16 FT.) and capacity (N, 1/4, 1/2, 3/4). Each cell contains a capacity value corresponding to a specific height.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/13/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 16'-11 1/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name