2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

	VESSEL:	F-MT 3168	(72))
	9	d gay	
THE FOLLOW 46CFR 35.	WING ITEMS HAVE BEEN 35-70 AND 33CFR 156	CHECKED AND TESTED IN ACCORDANCE 170 ON 4-27-24.	E WITH
			1961
		PRESSURE GAUGES HAVE BEEN C WITHIN 10% OF ACCURACY.	HECKED
		EMERGENCY SHUTDOWN HAS BEEN C AND FOUND OPERABLE.	HECKED
		TRASFER SYSTEM RELIEF VALVE HATESTED AND CHECKED - 125, P.S.	
		ALL TRANSFER PIPING SYSTEM ASSOCIATED VALVES HAVE BEEN AND CHECKED AT 187.5 P.S.I.	S AND TESTED
	N/A	CARGO HOSE VISUALLY HYDROSTATICALLY CHECKED TO 225	AND P.S.I.
THE ABOVE	ITEMS CHECKED, TES	TED AND VERIFIED BY:	*
th	ω •.		

linch = 25.40 mm linch = 2.54 cm

loz. = 1.729 inches OF H2O

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER

OPERATIONS SECTION 61.00-61.306 VESSEL: FMT 3168 OFFICIAL NUMBER: 1174489 TESTING LOCATION: GATES FIPORT MAXIMUM LOADING RATE (BPH) 5,000 TANK(S) TESTED: ALL PRESSURE INDICATOR: MANOMETER VESSEL OWNER AND ADDRESS: DLORIDA MARINE 2360 FIFTH ST. MANDENUTE CA TEST RESULTS TEST DATE: 6-27-24 BEGINNING PRESSURE: 18 OF HAD BEGINNING TIME: 1330 ENDING PRESSURE: 27.8" 0= 1420

TOTAL PRESSURE LOSS: 2" 0=1420 ENDING TIME: ___ ALLOWABLE PRESSURE LOSS: 2.2" of H20 NOTE: VESSEL IS CONSIDERED YAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. MATT BRAZZEL (PRINT) WITNESS: LEE (PRINT) ____(SIGN) AFFILIATION OF WITNESS CALCULATION OF ALLOWABLE PRESSURE LOSS: TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR V = VOLUME OF TANK(S) IN BARRELSAPL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER 14.70psi = 406.8 inches of H2O 1 psi = 27.67 inches of H2O