2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

## HOSE AND PIPELINE TESTS

VESSEL:		
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON		
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.	
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.	
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.	
	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.	
N 177	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.	
THE ABOVE ITEMS CHECKED, TESTED AND VERIFIED BY:		

Florida Marine Transporters Inc.

## MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FMT 3194	OFFICIAL NUMBER: 1191579
TESTING LOCATION: 191 FLT	
TANK(S) TESTED: ALL	PRESSURE INDICATOR: MANOMETER
VESSEL OWNER AND ADDRESS: FMT 231	
TEST DATE: _ 5 - 19 - 24	RESULTS
BEGINNING PRESSURE: 28" of Har o  ENDING PRESSURE: 28" of Har o	BEGINNING TIME: 1730
ENDING PRESSURE: 28 10 - 1420	ENDING TIME: 1800
TOTAL PRESSURE LOSS:	ALLOWABLE PRESSURE LOSS: 2.2".x H20
NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL	AL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT.	
TESTER: ROY HUUAL (PRINT)	WITNESS: Chad Tolliver (PRINT)
TESTER (SIGN)	WITNESS: (SIGN)
	FMT
CAY CAN ATTON OF ALL OWARD TRESCRIPE LOSS.	AFFILIATION OF WITNESS
CALCULATION OF ALLOWABLE PRESSURE LOSS:	7.3
$0.861 \times 15.7 \times (5,000) / 30$	$\frac{708}{(APL)} = \frac{2.2}{(APL)}$
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces) L = MAXIMUM LOADING RATE IN BARRELS PER HOUR V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER	
NOTES: 14.70psi = 406.8 inches of H2O 1psi = 27.67 inches of H2O 1 inch = 25.40 mm 1inch = 2.54 cm 1oz. = 1.729 inches OF H2O	