

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

## HOSE AND PIPELINE TESTS

	VESSEL:	FMT 3204		
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON/-2-/S				
		PRESSURE GAUGES HAVE BEEN CHECK WITHIN 10% OF ACCURACY.	ED	
		EMERGENCY SHUTDOWN HAS BEEN CHECK AND FOUND OPERABLE.		
		TRASFER SYSTEM RELIEF VALVE HAS BE TESTED AND CHECKED - 125 P.S.I.	EN ND	
	NA	ALL TRANSFER PIPING SYSTEMS AN ASSOCIATED VALVES HAVE BEEN TEST. AND CHECKED AT 187.5 P.S.I.		
8		CARGO HOSE VISUALLY AN HYDROSTATICALLY CHECKED TO 225 P.S.	ND I.	
THE ABOVE	ITEMS CHECKED, TEST	en and verified by:	> *	
y	*			

Florida Marine Transporters Inc.

## MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL:	OFFICIAL NUMBER: 1203918
TESTING LOCATION: C-ATES FLT	
	PRESSURE INDICATOR: MANONETER
VESSEL OWNER AND ADDRESS: FLORIDA M	ARIJE 2360 FIFTHST. MANDEULIE CA
TEST DATE: 1-2-25	T RESULTS
BEGINNING PRESSURE: 28" WFH20	BEGINNING TIME: 1200
ending pressure: 28"0F 100	ENDING TIME: 1230
TOTAL PRESSURE LOSS:	ALLOWABLE PRESSURE LOSS: 2.2".x H20
NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TO	TAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
	CCORDANCE WITH SECTION 61.304F, AND IS RED VAPOR TIGHT.
TESTER: MATT BRAZZEL (PRINT)	WITNESS: LEE CHAMPAGNE (PRINT)
TESTER: (SIGN)	1 (1)
•	FMT
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AFFILIATION OF WITNESS
0.861 x /5.7 x ( 5,000 / 30	706 = 2.2
(TP) (L)	(V) (APL)
TP = 14.7 Plus the barge test pressure in PSI ( L = MAXIMUM loading rate in barrels PER F Y = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF	iour
NOTES: 14.70psi = 406.8 inches of H2O 1psi = 27.67 inches of H2O 1 inch = 25.40 mm linch = 2.54 cm	