

## United States of America Department of Homeland Security United States Coast Guard

Certification Date: 12 Nov 2024 Expiration Date: 12 Nov 2029

### Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

Vessel Name	Official Number	IMO Numbe	er .	Call Sign	Service	
FMT 6006	1254215				Tank Bar	ge
Hailing Port	Hull Material	Horsep	ower	Propulsion		
NEW ORLEANS, LA	Steel			. , , , , , , , , , , , , , , , , , , ,		
UNITED STATES	Oleci					
Place Built	Delivery Date	Keel Laid Date	Gross Tons	Net Tons	DWT	Length
GULFPORT, MS	12Sep2014	10Jul2014	R-1619	R-1619		R-297.5
UNITED STATES			l-	ŀ		1-0

Owner

ST TAMMANY PARISH DEVELOPMENT DISTRICT 21489 KOOP DRIVE SUITE 7 MANDEVILLE, LA 70471 UNITED STATES Operator

FLORIDA MARINE LLC 2360 FIFTH STREET MANDEVILLE, LA 70471 UNITED STATES

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters	0 Licensed Mates	0 Chief Engineers	0 Oilers
0 Chief Mates	0 First Class Pilots	0 First Assistant Engineers	
0 Second Mates	0 Radio Officers	0 Second Assistant Engineers	
0 Third Mates	0 Able Seamen	0 Third Assistant Engineers	
0 Master First Class Pilot	0 Ordinary Seamen	0 Licensed Engineers	
0 Mate First Class Pilots	0 Deckhands	0 Qualified Member Engineer	

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

---Lakes, Bays, and Sounds---

Also, in fair weather only, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.

This vessel has been granted a fresh water service examination interval in accordance with 46 CFR Table 31.10-21(b); if this vessel is operated in salt water more than six (6) months in any twelve (12) month period, the vessel must be inspected using salt water intervals and the cognizant OCMI notified in writing as soon as this change in status occurs.

This tank barge is participating in the Eighth-Ninth Coast Guard District's Tank Barge Streamlined Inspection

\*\*\*SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION\*\*\*

With this Inspection for Certification having been completed at New Orleans, LA, UNITED STATES, the Officer in Charge, Marine Inspection, Sector New Orleans certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

	Annual/Peri	odic/Re-Inspe	ction	This Amended certificate issued by:
Date	Zone	A/P/R	Signature	D. VELEZ COMMANDER By direction
				Officer in Charge, Marine Inspection
				Sector New Orleans
				Inspection Zone



## United States of America Department of Homeland Security United States Coast Guard

Certification Date: 12 Nov 2024 Expiration Date: 12 Nov 2029

### Certificate of Inspection

Vessel Name: FMT 6006

Program (TBSIP). Inspection activities aboard this barge shall be conducted in accordance with its Tank Barge Action Plan. Inspection issues concerning this barge should be directed to Sector New Orleans OCMI.

### ---Hull Exams---

Exam Type	Next Exam	Last Exam	Prior Exam
DryDock	30Sep2034	21Oct2024	12Sep2014
Internal Structure	30Sep2029	21Oct2024	25Sep2019

### --- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization: GRADE "A" AND LOWER AND SPECIFIED HAZARDOUS CARGOS

Total Capacity Units Highest Grade Type Part151 Regulated Part153 Regulated Part154 Regulated

30508 Barrels A Yes No No

### \*Hazardous Bulk Solids Authority\*

#### \*Loading Constraints - Structural\*

Tank Number	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1P	792	13.6
18	792	13.6
2P	887	13.6
28	887	13.6
3P	800	13.6
38	800	13.6

### \*Loading Constraints - Stability\*

Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
11	3880	9ft 10in	13.6	R, LBS
Ш	4722	11ft 6in	13.6	R, LBS

### \*Conditions Of Carriage\*

Only those specified hazardous cargoes named in the vessel's Cargo Authority Attachment (CAA), Serial C1-1401318, dated 07MAY14 and Grade "A" and lower cargoes may be carried, and then only in the tanks indicated.

Per 46 CFR 150.130, the Person in Charge of the vessel is responsible for ensuring that the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using figures, tables and appendices of 46 CFR 150 in conjunction with the compatibility group numbers from the "COMPAT GRP" column listed in the vessel's CAA.

When the vessel is carrying cargoes containing greater than 0.5% benzene, the Person In Charge is responsible for ensuring the provisions of 46 CFR 197, Subpart C are applied.

#### \*Stability and Trim\*

Cargo tanks must be loaded uniformly whenever a 46 CFR Subchapter "O" cargo is carried; for trim purposes, the weight of cargo in each tank may exceed the uniformly loaded tank cargo weight by at most 5 percent.

The maximum density of cargo which may be filled to the tank top is 8.7 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.



## United States of America Department of Homeland Security United States Coast Guard

Certification Date: 12 Nov 2024 Expiration Date: 12 Nov 2029

### Certificate of Inspection

Vessel Name: FMT 6006

\*Vapor Control Authorization\*

In accordance with 46 CFR 39, excluding 46 CFR 39.4000, this vessel's vapor control system has been inspected to the plans approved by Marine Safety Center letter Serial C1-#1401318 dated 07MAY14 and the list of authorized cargoes on the CAA, Serial C1-#1401318 dated 07MAY14 and found acceptable for collection of bulk liquid cargo vapors annotated with "Yes" in the CAA's VCS column.

THE VCS IS FITTED WITH 2 HIGH VELOCITY P/V VALVES. THE PRIMARY VALVE IS SET AT 5.5 PSIG PRESSURE AND 2.0 PSIG VACUUM. THE SECONDARY VALVE IS SET AT 3.5 PSIG PRESSURE AND 0.5 PSIG VACUUM AND IS SEPARATED FROM THE MAIN VAPOR HEADER BY MEANS OF AN ISOLATION VALVE. THE ISOLATION VALVE IS REQUIRED TO BE OPENED WHEN CARRYING SUBCHAPTER "O" CARGOES. THE CARGO TANK TOP IS SUITABLE FOR A MAXIMUM ALLOWABLE WORKING PRESSURE (MAWP) OF 6.0 PSI

In accordance with 46 CFR Part 39.1017 and 39.5001(e) this vessel's VCS has been evaluated and approved for multibreasted tandem loading with other vessels specifically approved to tandem load with this vessel.

### --- Inspection Status ---

### \*Cargo Tanks\*

	Internal Exam			External Exan	n	
Tank ld	Previous	Last	Next	Previous	Last	Next
1P	12Sep2014	21Oct2024	21Oct2034	<del>-</del>	:+:	(=)
1S	12Sep2014	21Oct2024	21Oct2034	ä	-	50
2P	12Sep2014	21Oct2024	21Oct2034			=:
2S	12Sep2014	21Oct2024	21Oct2034	=	(#:	<b>=</b> 0
3P	12Sep2014	21Oct2024	21Oct2034	=	-	<b>=</b> 27.
3S	12Sep2014	21Oct2024	21Oct2034		-	<del>-2</del> 9
			Hydro Test			
Tank Id	Safety Valves	;	Previous	Last	Next	
1P	12Sep2014		? <b>≥</b> 1	12Sep2014		
1S	12Sep2014		<b>E</b>	12Sep2014	<u> </u>	
2P	12Sep2014		æ	12Sep2014	X <del>2</del> 3	
28	12Sep2014		326 200	12Sep2014	) <del>=</del>	
3P	12Sep2014		(S)	12Sep2014	-	
3S	12Sep2014		9=	12Sep2014	-	

### ---Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

### --- Fire Fighting Equipment ---

#### \*Fire Extinguishers - Hand portable and semi-portable\*

Quantity

Class Type

2

40-B

### ---Certificate Amendments---

Amending Unit

Amendment Date

Amendment Remark

Sector New Orleans

11Mar2025

Changed Operator Name and Address

\*\*\*END\*\*\*



C1-1401318 Dated:

07-May-14

# Certificate of Inspection

Cargo Authority Attachment

Vessel Name: FMT 6006 Official #: 1254215

Shipyard: Gulf Coast Shipyard

Hull #: TO-96

46 CFR 151 Tank Tank Group Information	1	Chara dentificati		tics	Cargo		Tanks		Carg		Enviror Control	nmental	Fire	Special Require	ements		
Tnk Grp Tanks in Group	Density	Press.	Тетр.	Hull Typ	Sea	1 _	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction	Elec Haz	
A #1P/S, #2P/S, #3P/S	13.6	Atmos.	Amb.	II	1ii 2ii	Integral Gravity	PV	Closed	II	G-1	NR	NA	Portable	.50-5(d), .50-60, .50-70(a), .50- 70(b), .50-73, .50- 81(a), .50-81(b),	55-1(b), (c), (e), (f), (h), (j), 56-1(a), (b), (c), (d), (e), (f), (g),	NR	No

Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks,

### **List of Authorized Cargoes**

Cargo Identification		Conditions of Carriage								
							Vapor R			
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
Authorized Subchapter O Cargoes										
Acetonitrile	ATN	37	0	С	III	Α	Yes	3	No	G
Acrylonitrile	ACN	15 <sup>2</sup>	0	С	П	Α	No	N/A	.50-70(a), .55-1(e)	G
Adiponitrile	ADN	37	0	Е	II	Α	Yes	1	No	G
Alkyl(C7-C9) nitrates	AKN	34 <sup>2</sup>	0	NA	111	Α	No	N/A	.50-81, 50-86	G
Aminoethylethanolamine	AEE	8	0	Ε	III	Α	Yes	1	.55-1(b)	G
Ammonium bisulfite solution (70% or less)	ABX	43 <sup>2</sup>	0	NA	111	Α	No	N/A	.50-73, .56-1(a), (b), (c)	G
Ammonium hydroxide (28% or less NH3)	AMH	6	0	NA	III	Α	No	N/A	.56-1(a), (b), (c), (f), (g)	G
Anthracene oil (Coal tar fraction)	AHO	33	0	NA	П	Α	No	N/A	No	G
Benzene	BNZ	32	0	С	111	Α	Yes	1	.50-60	G
Benzene or hydrocarbon mixtures (having 10% Benzene or more)	внв	32 <sup>2</sup>	0	С	111	Α	Yes	1	50-60	G
Benzene or hydrocarbon mixtures (containing Acetylene and 10% Benzene or more)	ВНА	32 <sup>2</sup>	0	С	Ш	Α	Yes	1	50-60, 56-1(b), (d), (f), (g)	G
Benzene, Toluene, Xylene mixtures (10% Benzene or more)	BTX	32	0	B/C	III	Α	Yes	1	.50-60	G
Butyl acrylate (all isomers)	BAR	14	0	D	III	Α	No	N/A	.50-70(a), .50-81(a), (b)	G
Butyl methacrylate	вмн	14	0	D	III	Α	No	N/A	.50-70(a), .50-81(a), (b)	G
Butyraldehyde (all isomers)	BAE	19	0	С	111	Α	Yes	1	.55-1(h)	G
Camphor oil (light)	CPO	18	0	D	н	Α	No	N/A	No	G
Carbon tetrachloride	СВТ	36	0	NA	III	Α	No	N/A	No	G
Caustic potash solution	CPS	5 <sup>2</sup>	0	NA	III	Α	No	N/A	.50-73, .55-1()	G
Caustic soda solution	CSS	5 <sup>2</sup>	0	NA	III	Α	No	N/A	50-73, .55-1(j)	G
Chemical Oil (refined, containing phenolics)	COD	21	0	Ε	11	Α	No	N/A	.50-73	G
Chlorobenzene	CRB	36	0	D	Ш	Α	Yes	1	No	G
Chloroform	CRF	36	0	NA	III	Α	Yes	3	No	G
Coal tar naphtha solvent	NCT	33	0	D	III	Α	Yes	1	.50-73	G
Creosote	ccw	21 <sup>2</sup>	0	E	111	Α	Yes	1	No	G
Cresols (all isomers)	CRS	21	0	E	III	Α	Yes	1	No	G
Cresylate spent caustic	CSC	5	0	NA	III	Α	No	N/A	.50-73, .55-1(b)	G
Cresylic acid tar	CRX		0	Е	III	Α	Yes	1	.55-1(f)	G
Crotonaldehyde	СТА	19 <sup>2</sup>	0	С	ll.	Α	No	N/A	,55-1(h)	G
Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropyl acrolein)	CHG		0	С	III	A	Yes	1	No	G
Cyclohexanone	ССН	18	0	D	Ш	Α	Yes	1	.56-1(a), (b)	G
Cyclohexanone, Cyclohexanol mixture	CYX	18 <sup>2</sup>	0	E	111	Α	Yes	1	.56-1 (b)	G

<sup>2.</sup> Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.

<sup>3.</sup> Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.



C1-1401318

## Certificate of Inspection

### Cargo Authority Attachment

Vessel Name: FMT 6006

Shipyard: Gulf Coast Shipyard

Group

Hull #: TO-96

Official #: 1254215

Page 2 of 8

Cargo Identification	Conditions of Carriage									
	Chem	Compat	Sub		Huji	Tank	Vapor Fi	ecovery VCS	Special Requirements in 46 OFR	1.
Name Cyclohexylamine	Code CHA	Group No		Grade D	Type	Group A		Category 1	Special Requirements in 46 CFR 151 General and Mat'ls of .56-1(a), (b), (c), (g)	Insp. Period G
Cyclopentadiene, Styrene, Benzene mixture	CSB	30	0	D	Ш	Α	Yes	1	.50-60, .56-1(b)	G
iso-Decyl acrylate	IAI	14	0	Е	M	Α	No	N/A	.50-70(a), .50-81(a), (b), .55-1(c)	G
Dichlorobenzene (all isomers)	DBX	36	0	E	Ш	Α	Yes	3	56-1(a), (b)	G
1,1-Dichloroethane	DCH	36	0	С	111	Α	Yes	1	No	G
2,2'-Dichloroethyl ether	DEE	41	0	D	1)	Α	Yes	1	.55-1(f)	G
Dichloromethane	DCM	36	0	NA	Ш	Α	No	N/A	No	G
2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution	DDE	43	0	E	HI	Α	No	N/A	.56-1(a), (b), (c), (g)	G
2.4-Dichlorophenoxyacetic acid, dimethylamine salt solution	DAD	0 1,2	0	Α	III	Α	No	N/A	.56-1(a), (b), (c), (g)	G
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DTI	43 <sup>2</sup>	0	Е	III	A	No	N/A	.56-1(a), (b), (c), (g)	G
1,1-Dichloropropane	DPB	36	0	С	111	Α	Yes	3	No	G
1,2-Dichloropropane	DPP	36	0	С	III	Α	Yes	3	No	G
1,3-Dichloropropane	DPC	36	0	С	Ш	Α	Yes	3	No	G
1,3-Dichloropropene	DPU	15	ō	D	II	A	No	N/A	No	G
Dichloropropene, Dichloropropane mixtures	DMX	15	0	C	II.	A	Yes	1	No	G
Diethanolamine	DEA	8	0	E	111	A	Yes	1	.55-1(c)	G
Diethylamine	DEN	7	0	c		A	Yes	3	.55-1(c)	G
Diethylenetriamine	DET	7 2	0	Ę	111	A	Yes	1	.55-1(c)	G
Diisobutylamine	DBU	7	0	D		A	Yes	3	.55-1(c)	G
Diisopropanolamine	DIP	8	0	E	III	A	Yes	1	.55-1(c)	G
Diisopropylamine	DIA	7	0	c	II.	A	Yes	3	.55-1(c)	G
N,N-Dimethylacetamide	DAC	10	0	E	m m	A	Yes	3	.56-1(b)	G
Dimethylethanolamine	DMB	8	0		111	A			.56-1(b), (c)	G
Dimethylformamide	DMF	10	0	D	111	A	Yes	1	.55-1(e)	G
Di-n-propylamine	DNA	7	0	C			Yes	1	.55-1(c)	G
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	0	E	- 11	Α	Yes	3	.56-1(b)	
Dodecyl diphenyl ether disulfonate solution	DOS					Α .	No	N/A		G
EE Glycol Ether Mixture	EEG	43	0	#	II	A	No	N/A	No	G
Ethanolamine	_	40	0	D	ш	A	No	N/A	No	G
Ethyl acrylate	MEA	8	0	E	III	Α	Yes	1	.55-1(c)	G
	EAC	14	0	C	Ш	Α	No	N/A	.50-70(a), .50-81(a), (b)	G
Ethylamine solution (72% or less)	EAN	7	0	Α	11	Α	Yes	6	.55-1(b)	G
N-Ethylbutylamine	EBA	7	0	D	III	Α	Yes	3	.55-1(b)	G
N-Ethylcyclohexylamine	ECC	7	0	D	III	Α	Yes	1	,55-1(b)	G
Ethylene cyanohydrin	ETC	20	0	E	III	Α	Yes	1	No	G
Ethylenediamine	EDA	7 2	0	D	_III	Α	Yes	1	.55-1(c)	G
Ethylene dichloride	EDC	36 <sup>2</sup>	0	С	III	Α	Yes	1	No	G
Ethylene glycol hexyl ether	EGH	40	0	E	III	Α	No	N/A	No	G
Ethylene glycol monoalkyl ethers	EGC	40	0	D/E	111	Α	Yes	1	No	G
Ethylene glycol propyl ether	EGP	40	0	E	181	Α	Yes	1	No	G
2-Ethylhexyl acrylate	EAI	14	0	E	III	Α	No	N/A	.50-70(a), .50-81(a), (b)	G
Ethyl methacrylate	ETM	14	0	D/E	III	Α	No	N/A	.50-70(a)	G
2-Ethyl-3-propylacrolein	EPA	19 <sup>2</sup>	0	E	101	Α	Yes	1	No	G
Formaldehyde solution (37% to 50%)	FMS	19 <sup>2</sup>	0	D/E	111	Α	Yes	1	.55-1(h)	G
Furfural	FFA	19	0	D	100	Α	Yes	1	.55-1(h)	G
Glutaraldehyde solution (50% or less)	GTA	19	0	NA	111	Α	No	N/A	No	G
Hexamethylenediamine solution	HMC	7	0	E	Ш	Α	Yes	1	,55-1(c)	G
Hexamethyleneimine	НМІ	7	0	С	H	Α	Yes	1	56-1(b), (c)	G
Hydrocarbon 5-9	HFN		0	С	Ш	Α	Yes	1	.50-70(a), .50-81(a), (b)	G



Serial #: C1-1401318 Dated: 07-May-14

## Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: FMT 6006

Shipyard: Gulf Coast Shipyard

Group Hull #: TO-96

Official #: 1254215

Page 3 of 8

Cargo Identification	n						Conditions of Carriage							
Name Isoprene	Chem Code IPR	Compat Group No 30	Sub Chapter O	Grade A	Hull Type	Tank Group A	App'd (Y or N) No	Recovery VCS Category N/A	Special Requirements in 46 CFR 151 General and Mat'ls of .50-70(a), .50-81(a), (b)	Insp. Period G				
Isoprene, Pentadiene mixture	IPN		0	В	III	Α	No	N/A	.50-70(a), .55-1(c)	G				
Kraft pulping liquors (free alkali content 3% or more)(including: Black Green, or White liquor)	, KPL	5	0	NA	III	Α	No	N/A	.50-73, .56-1(a), (c), (g)	G				
Mesityl oxide	MSO	18 <sup>2</sup>	0	D	Ш	Α	Yes	1	No	G				
Methyl acrylate	MAM	14	0	С	111	Α	No	N/A	50-70(a), .50-81(a), (b)	G				
Methylcyclopentadiene dimer	MCK	30	0	С	m	Α	Yes	1	No	G				
Methyl diethanolamine	MDE	8	0	Е	Ш	Α	Yes	1	.56-1(b), (c)	G				
2-Methyl-5-ethylpyridine	MEP	9	0	Е	111	Α	Yes	1	.55-1(e)	G				
Methyl methacrylate	MMM	14	0	С	111	Α	No	N/A	.50-70(a), .50-81(a), (b)	G				
2-Methylpyridine	MPR	9	0	D	111	Α	Yes	3	.55-1(c)	G				
alpha-Methylstyrene	MSR	30	0	D	III	Α	No	N/A	.50-70(a), .50-81(a), (b)	G				
Morpholine	MPL	7 <sup>2</sup>	0	D	III	Α	Yes	1	.55-1(c)	G				
Nitroethane	NTE	42	0	D	11	A	No	N/A	.50-81, .56-1(b)	G				
1- or 2-Nitropropane	NPM	42	ō	D	386	A	Yes	1	.50-81	G				
1,3-Pentadiene	PDE	30	0	A	10	A	No	N/A	50-70(a), .50-81	G				
Perchloroethylene	PER	36	0	NA	111	A	No	N/A	No	G				
Polyethylene polyamines	PEB	7 <sup>2</sup>	o	E	101	A	Yes	1	55-1(e)	G				
iso-Propanolamine	MPA	8	0	E	111	A	Yes	1	.55-1(c)	G				
Propanolamine (iso-, n-)	PAX	8	0	E	111	A	Yes	1	_56-1(b), (c)	G				
iso-Propylamine	IPP	7	0	A	- !!	Ā			.55-1(c)	- G				
Pyridine	PRD	9	0	c	111	A	No	N/A	.55-1(e)	G				
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxide)	SAP		0		III	A	Yes No	1 N/A	.50-73, _55-1(j)	G				
Sodium aluminate solution (45% or less)	SAU	5	0	NA	III	Α	No	N/A	.50-73, .56-1(a), (b), (c)	G				
Sodium chlorate solution (50% or less)	SDD	0 1,2	0	NA		A	No	N/A	50-73	G				
Sodium hypochlorite solution (20% or less)	SHQ	5	0	NA		A	No	N/A	.50-73, .56-1(a), (b)					
Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 1,2	0	NA	111	A	Yes	1	.50-73, .55-1(b)	G				
Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm)	SSI	0 1,2	0	NA	III	A	No	N/A	.50-73, .55-1(b)	G				
Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm)	SSJ	0 1,2	0	NA	II	Α	No	N/A	.50-73, .55-1(b)	G				
Styrene (crude)	STX		0	D	ill	A	No	N/A	No	G				
Styrene monomer	STY	30	0	D	111	A	No	N/A	.50-70(a), .50-81(a), (b)	G				
1,1,2,2-Tetrachloroethane	TEC	36	0	NA.	111	A	No	N/A	No No	G				
Tetraethylenepentamine	TTP	7	0	E	III	A	Yes	1	.55-1(c)	G				
Tetrahydrofuran	THF	41	0	С	III				.50-70(b)	G				
Toluenediamine	TDA	9	0	E		A	Yes	11	.50-73, .56-1(a), (b), (c), (g)	G				
1,2,4-Trichlorobenzene	TCB	36	0	E	III		No	N/A	No					
1,1,2-Trichloroethane	TCM		0			Α	Yes	1						
Trichloroethylene		36		NA	III	A	Yes	1	,50-73, .56-1(a)	G				
•	TCL	36 <sup>2</sup>	0	NA -	111	A	Yes	1	No	G				
1,2,3-Trichloropropane	TCN	36	0	E	111	<u>A</u>	Yes	3	.50-73, .56-1(a)	G				
Triethanolamine	TEA	8 <sup>2</sup>	0	E	101	A	Yes	1	.55-1(b)	G				
Triethylamine	TEN	7	0	С	11	Α	Yes	3	.55-1(e)	G				
Triethylenetetramine	TET	7 2	0	E	III	Α	Yes	1	.55-1(b)	G				
Triphenylborane (10% or less), caustic soda solution	TPB	5	0	NA	III	Α	No	N/A	.56-1(a), (b), (c)	G				
Trisodium phosphate solution	TSP	5	0	NA		_ A	No	N/A	.50-73, .56-1(a), (c).	G				
Urea, Ammonium nitrate solution (containing more than 2% NH3)	UAS	6	0	NA	III	Α	No	N/A	.56-1(b)	G				
Vanillin black liquor (free alkali content, 3% or more).	VBL	5	0	NA	Ш	Α	No	N/A	.50-73, .56-1(a), (c), (g)	G				
Vinyl acetate	VAM	13	0	С	Ш	Α	No	N/A	.50-70(a), .50-81(a), (b)	G				



### Cargo Authority Attachment

Vessel Name: FMT 6006

Shipyard: Gulf Coast Shipyard

Group

Serial #: C1-1401318

Dated: 07-May-14

Official #: 1254215

Page 4 of 8

Hull #: TO-96

Cargo Identification		Conditions of Carriage								
							Vapor F	Recovery		T
Name	Chem	Compat Group No	Sub	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp.
Vinyl neodecanate	VND	13	0	Е	111	A	No	N/A	.50-70(a), .50-81(a), (b)	Perio G
Vinyltoluene	VNT	13	0	D	111	Α	No	N/A	.50-70(a), .50-81, .56-1(a), (b), (c), (	G
Subchapter D Cargoes Authorized for Vapor Cont	rol									
Acetone	ACT	18 <sup>2</sup>	D	С		Α	Yes	1		
Acetophenone	ACP	18	D	Ē		Α	Yes	1		
Alcohol(C12-C16) poly(1-6)ethoxylates	APU	20	D	E		A	Yes	1		
Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates	AEB	20		E		A	Yes	1		
Amyl acetate (all isomers)	AEC	34	D	D		A	Yes	1		
Amyl alcohol (iso-, n-, sec-, primary)	AAI	20	D	D		A	Yes	1		
Benzyl alcohol	BAL	21	D	E		A	Yes	1		
Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters)	BFX	20	D	E		Ā	Yes	1		
Butyl acetate (all isomers)	BAX	34	D	D		Α	Yes	1		
Butyl alcohol (iso-)	IAL	20 <sup>2</sup>	D	D		A	Yes	1		
Butyl alcohol (n-)	BAN	20 <sup>2</sup>	D	D		A	Yes	1		
Butyl alcohol (sec-)	BAS	20 <sup>2</sup>	D	C		Α	Yes	1		
Butyl alcohol (tert-)	BAT		D	C		Α	Yes	1		
Butyl benzyl phthalate	BPH	34	D	E		A	Yes	1		
Butyl toluene	BUE	32	D	D		A				
Caprolactam solutions	CLS	22	D	E		A	Yes	1		
Cyclohexane	CHX	31	D	С			Yes	1		
Cyclohexanol	CHN	20	D	E		Ā	Yes	1		
p-Cymene	CMP	32	D	D			Yes	1		
iso-Decaldehyde	IDA	19	D	E		A	Yes	1		
n-Decaldehyde	DAL	19	D				Yes	1		
Decene	DCE	30		E		Α	Yes	1		
Decyl alcohol (all isomers)			D	D		A	Yes	1		
n-Decylbenzene, see Alkyl(C9+)benzenes	DAX	20 <sup>2</sup>	D	<u>E</u>	_	A	Yes	1		_
Diacetone alcohol	DBZ	32	D	E		A	Yes	1		
ortho-Dibutyl phthalate	DAA	20 <sup>2</sup>	D	D	_	Α	Yes	1		
Diethylbenzene	DPA	34	D	E		Α	Yes	1		
	DEB	32	D	D		Α	Yes	1		
Diethylene glycol	DEG	40 <sup>2</sup>	D	E		Α	Yes	1		
Diisobutylene	DBL	30	D	С		Α	Yes	1		
Diisobutyl ketone	DIK	18	D	D		Α	Yes	1		
Diisopropylbenzene (all isomers)	DIX	32	D	E		Α	Yes	1		
Dimethyl phthalate	DTL	34	D	E		Α	Yes	_11		
Dioctyl phthalate	DOP	34	D	E		Α	Yes	1		
Dipentene	DPN	30	D	D		Α	Yes	1		
Diphenyl	DIL	32	D	D/E		Α	Yes	1		
Diphenyl, Diphenyl ether mixtures	DDO	33		E		Α	Yes	1		
Diphenyl ether	DPE	41	D	{E}		Α	Yes	1		
Dipropylene glycol	DPG	40		Е		Α	Yes	1		
Distillates: Flashed feed stocks	DFF	33	D	E		Α	Yes	1		
Distillates: Straight run	DSR	33	D	E		Α	Yes	1		
Dodecene (all isomers)	DOZ	30	D	D		Α	Yes	1		
Dodecylbenzene, see Alkyl(C9+)benzenes	DDB	32	D	E		Α	Yes	1		
2-Ethoxyethyl acetate	EEA	34	D	D		Α	Yes	1		



### Cargo Authority Attachment

Vessel Name: FMT 6006

Shipyard: Gulf Coast Shipyard

Serial #: C1-1401318

07-May-14

Group Hull #: TO-96

Official #: 1254215

Page 5 of 8

Cargo Identification							Conditions of Carriage					
Name Ethoxy triglycol (crude)	Chem Code ETG	Compat Group No 40	Sub Chapter D	Grade	Hull Type	Tank Group A	App'd (Y or N) Yes	Recovery VCS Category 1	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period		
Ethyl acetate	ETA	34	D	c		A	Yes	1				
Ethyl acetoacetate	EAA	34	D	E		A	Yes	1				
Ethyl alcohol	EAL	20 <sup>2</sup>	D	C		A	Yes	1				
Ethylbenzene	ETB	32	D	c		Ā	Yes	3				
Ethyl butanol	EBT	20	D	D		A		1				
Ethyl tert-butyl ether	EBE	41	D	С		A	Yes Yes	1				
Ethyl butyrate	EBR	34	D	D								
Ethyl cyclohexane	ECY	31	D	D	_	Α	Yes	1				
Ethylene glycol	EGL	20 2	D	E		A	Yes	1				
Ethylene glycol butyl ether acetate	EMA					A	Yes	1				
Ethylene glycol diacetate	EGY	34	D	E		Α	Yes	1				
			D	E	_	A	Yes	1 1				
Ethylene glycol phenyl ether	EPE	40	D	E		A	Yes	1				
Ethyl-3-ethoxypropionate	EEP	34	D	D		Α .	Yes	1		_		
2-Ethylhexanol	EHX	20	D	E		A	Yes	1				
Ethyl propionate	EPR	34	D	С		Α	Yes	1				
Ethyl toluene	ETE	32	D	D		Α	Yes	1_				
Formamide	FAM	10	D	E		Α	Yes	11				
Furfuryl alcohol	FAL	20 <sup>2</sup>	D	E		Α	Yes	1				
Gasoline blending stocks: Alkylates	GAK	33	D	A/C		Α	Yes	1				
Gasoline blending stocks: Reformates	GRF	33	D	A/C		Α	Yes	1				
Gasolines: Automotive (containing not over 4.23 grams lead per gallon)	GAT	33	D	С		Α	Yes	1				
Gasolines: Aviation (containing not over 4.86 grams of lead per gallon)	GAV	33	D	С		Α	Yes	1				
Gasolines: Casinghead (natural)	GCS	33	D	A/C		Α	Yes	1				
Gasolines: Polymer	GPL	33	D	A/C		Α	Yes	1				
Gasolines: Straight run	GSR	33	D	A/C		Α	Yes	1				
Glycerine	GCR	20 <sup>2</sup>	D	Е		Α	Yes	1				
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	HMX	31	D	С		Α	Yes	1				
Heptanoic acid	HEP	4	D	E		Α	Yes	1				
Heptanol (all isomers)	HTX	20	D	D/E		Α	Yes	1				
Heptyl acetate	HPE	34	D	E		Α	Yes	1				
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 <sup>2</sup>	D	B/C		Α	Yes	1				
Hexanoic acid	HXO	4	D	Е		Α	Yes	1				
Hexanol	HXN	20	D	D		Α	Yes	1				
Hexylene glycol	HXG	20	D	Е		Α	Yes	1				
Isophorone	IPH	18 <sup>2</sup>	D	E		Α	Yes	1				
Jet fuel: JP-4	JPF	33	D	Е		Α	Yes	1				
Jet fuel: JP-5 (kerosene, heavy)	JPV	33	D	D		Α	Yes	1				
Kerosene	KRS	33	D	D		Α	Yes	1				
Methyl acetate	МТТ	34	D	D		Α	Yes	1				
Methyl alcohol	MAL	20 <sup>2</sup>	D	С		A	Yes	1				
Methylamyl acetate	MAC	34	D	D		A	Yes	1				
Methylamyl alcohol	MAA	20	D	D		A	Yes	1				
Methyl amyl ketone	MAK	18	D	D		A	Yes	1				
Methyl tert-butyl ether	MBE	41 2	D	c	_	A	Yes	1				
Methyl butyl ketone	MBK	18	D	С		A	Yes	1				
Methyl butyrate	MBU	34	D	С		A	Yes	1				



## Cargo Authority Attachment

Vessel Name: FMT 6006

Shipyard: Gulf Coast Shipyard

Serial #: C1-1401318

07-May-14

Group

Official #: 1254215

Page 6 of 8

Hull #: TO-96

Cargo Identification							Conditions of Carriage					
	Ch	0	2.4					Recovery				
Name Methyl ethyl ketone	Chem Code MEK	Group No 18 <sup>2</sup>	Sub Chapter D	Grade C	Hull Type	Tank Group A	App'd (Y or N) Yes	VCS Category 1	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period		
Methyl heptyl ketone	MHK	18	D	D		Α	Yes	1				
Methyl isobutyl ketone	MIK	18 <sup>2</sup>	D	С		Α	Yes	1				
Methyl naphthalene (molten)	MNA	32	D	E		Α	Yes	1				
Mineral spirits	MNS	33	D	D		Α	Yes	1				
Myrcene	MRE	30	D	D		Α	Yes	1				
Naphtha: Heavy	NAG	33	D	#		Α	Yes	1				
Naphtha: Petroleum	PTN	33	D	#		Α	Yes	1				
Naphtha: Solvent	NSV	33	D	D		Α	Yes	1				
Naphtha: Stoddard solvent	NSS	33	D	D		Α	Yes	1				
Naphtha: Varnish makers and painters (75%)	N∨M	33	D	С		Α	Yes	1				
Nonane (all isomers), see Alkanes (C6-C9)	NAX	31	D	D		Α	Yes	1				
Nonyl alcohol (all isomers)	NNS	20 <sup>2</sup>	D	E		Α	Yes	1				
Nonyl phenol	NNP	21	D	E		Α	Yes	1				
Nonyl phenol poly(4+)ethoxylates	NPE	40	D	E		Α	Yes	1				
Octane (all isomers), see Alkanes (C6-C9)	OAX	31	D	С		A	Yes	1				
Octanoic acid (all isomers)	OAY	4	D	E		A	Yes	1				
Octanol (all isomers)	OCX	20 <sup>2</sup>	D	E		A	Yes	1				
Oil, fuel: No. 2	OTW	33	D	D/E		A	Yes	1				
Oil, fuel: No. 2-D	OTD	33	D	D		A	Yes	1				
Oil, fuel: No. 4	OFR	33	D	D/E		A	Yes	1				
Oil, fuel: No. 5	OFV	33	D	D/E		A	Yes	1				
Oil, fuel: No. 6	OSX	33	D	E		A	Yes	1				
Oil, misc: Crude	OIL	33	D	C/D		Ā	Yes	1				
Oil, misc: Diesel	ODS	33	D	D/E		A	Yes	1				
Oil, misc: Gas, high pour	OGP	33	D	E		A	Yes	1				
Oil, misc: Lubricating	OLB	33	D	E		A	Yes	1				
Oil, misc: Residual	ORL	33	D	E		A	Yes	1				
Oil, misc: Turbine	ОТВ	33	D	E		A		1				
n-Pentyl propionate	PPE	34	D	D		A	Yes	1				
alpha-Pinene	PIO	30	D	D		Ā	Yes					
beta-Pinene	PIP	30	D	D		A						
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether	PAG	40	D	E		A	Yes	1				
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate	PAF	34	D	E		A						
Polybutene	PLB						Yes	1				
Polypropylene glycol		30	D	E		A	Yes	1				
	PGC	40	D	E		Α .	Yes	1				
iso-Propyl acetate	IAC	34	D	C	_	Α	Yes	1				
n-Propyl acetate	PAT	34	D	C		Α	Yes	1				
iso-Propyl alcohol n-Propyl alcohol	IPA	20 2		С	_	A	Yes	1				
	PAL	20 <sup>2</sup>		C	_	Α	Yes	1				
Propylbenzene (all isomers)	PBY	32	D	D		A	Yes	1				
iso-Propylcyclohexane	IPX	31		D _		A	Yes	1				
Propylene glycol	PPG	20 <sup>2</sup>		E		Α	Yes	1				
Propylene glycol methyl ether acetate	PGN	34		D		Α	Yes	1				
Propylene tetramer	PTT	30		D		Α	Yes	1				
Sulfolane	SFL	39		E		Α	Yes	1				
Tetraethylene glycol	TTG	40		E		Α	Yes	1				
Tetrahydronaphthalene	THN	32	D	E		Α	Yes	_ 1				



## Cargo Authority Attachment

Vessel Name: FMT 6006

Official #: 1254215

Shipyard: Gulf Coast Shipyard

Serial #: C1-1401318

Dated: 07-May-14

Group

Hull #: TO-96

Page 7 of 8

Cargo Identification						Conditions of Carriage					
Name Toluene	Chem Code TOL	Compat Group No 32	Sub Chapter D	Grade C	Hull Type	Tank Group A	App'd (Y or N) Yes	Recovery VCS Category 1	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period	
Tricresyl phosphate (less than 1% of the ortho isomer)	TCP	34	D	E		Α	Yes	1			
Triethylbenzene	TEB	32	D	Е		Α	Yes	1			
Triethylene glycol	TEG	40	D	E		Α	Yes	1			
Triethyl phosphate	TPS	34	D	E		Α	Yes	1			
Trimethylbenzene (all isomers)	TRE	32	D	{D}		Α	Yes	1			
Trixylenyl phosphate	TRP	34	D	Е		Α	Yes	1			
Undecene	UDC	30	D	D/E		Α	Yes	1			
1-Undecyl alcohol	UND	20	D	Ε		Α	Yes	1			
Xylenes (ortho-, meta-, para-)	XLX	32	D	D		Α	Yes	1			



### Department of Homeland Security United States Coast Guard

Serial #: C1-1401318 Dated:

07-May-14

# Certificate of Inspection

Cargo Authority Attachment

Vessel Name: FMT 6006

Official #: 1254215

Page 8 of 8

Shipyard: Gulf Coast Shi

Hull #: TO-96

#### Explanation of terms & symbols used in the Table:

Cargo Identification

Name

Chem Code

The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2. The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual

Certain mixtures of cargoes may not have a CHRIS Code assigned.

Compatability Group No.

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chair. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone

Note 1

Subchapter D

Subchanter O Note 3

Note 2

See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart. The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified.

Those flammable and combustible liquids listed in 46 CFR Table 30.25-1.

Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2.

Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.

Grade

Subchanter

A, B, C

Note 4

NΑ

Hull Type NA

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of

Flammable liquid cargoes, as defined in 46 CFR 30-10.22. Combustible liquid cargoes, as defined in 46 CFR 30-10.15.

The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo Those subchapter O cargoes which are not classified as a flammable or combustible liquid.

No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available.

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1).

Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3).

Designed to carry products of sufficeint hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4). Not applicable to barges certificated under Subchapter D.

#### Conditions of Carriage

Tank Group Vapor Recover Approved (Y or N)

The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo,

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

#### Conditions of Carriage

Tank Group Vapor Recovery Approved (Y or N)

The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo.

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo

VCS Category: Category 1

The specified cargo's provisional classification for vapor control systems

(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates.

Category 2

(Polymerizas) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester.

Category 3

(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39 20-9. This requirement is in addition to the requirements of Category 1.

Category 4

(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3.

Category 5

(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.

Category 6 Category 7

(High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5. (High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5,

none

The cargo has not been evaluated/classified for use in vapor control systems.