



# BARGE "FMT-3009"

## FLORIDA MARINE

HULL NO. 2080-2

CORRECTION TABLE FOR TRIM AFT.

### FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	(-) 0' - 0 1/8"	NIL
1'-0"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"
1'-6"	(-) 0' - 0 1/8"	(-) 0' - 0 1/4"	(-) 0' - 0 1/8"
2'-0"	(-) 0' - 0 1/8"	(-) 0' - 0 1/4"	(-) 0' - 0 1/4"
2'-6"	(-) 0' - 0 1/8"	(-) 0' - 0 3/8"	(-) 0' - 0 1/4"
3'-0"	(-) 0' - 0 1/4"	(-) 0' - 0 3/8"	(-) 0' - 0 3/8"
3'-6"	(-) 0' - 0 1/4"	(-) 0' - 0 1/2"	(-) 0' - 0 3/8"
4'-0"	(-) 0' - 0 1/4"	(-) 0' - 0 5/8"	(-) 0' - 0 1/2"
4'-6"	(-) 0' - 0 1/4"	(-) 0' - 0 5/8"	(-) 0' - 0 1/2"
5'-0"	(-) 0' - 0 3/8"	(-) 0' - 0 3/4"	(-) 0' - 0 5/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED, TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 4/18/00

BY:

INSPECTORATE AMERICA CORPORATION









BARGE "FMT-3009" FLORIDA MARINE

INNAGE TABLE

2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2080-2

Table with columns for height in feet (0 to 14) and corresponding capacity in barrels. Includes rows for various gauge heights and a final row for capacities at 42 U.S. gallons.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 4/18/00

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK.)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature

INSPECTORATE AMERICA CORPORATION







BARGE "FMT-3009"
FLORIDA MARINE

OUTAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2080-2

Table with columns for height (0 FT. to 15 FT.) and multiple rows for each height (0, 1/4, 1/2, 3/4). Contains numerical data for various measurements across the barge.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 4/18/00

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of the inspector.

INSPECTORATE AMERICA CORPORATION

BARGE "FMT-3009"  
FLORIDA MARINE

OUTAGE TABLE

1 STAR.



BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2080-2

Table with columns for height (0 FT. to 15 FT.) and corresponding capacity values for each gauge. Includes sub-columns for gauge types (1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 4/18/00

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and text: INSPECTORATE AMERICA CORPORATION









BARGE "FMT-3009" FLORIDA MARINE

OUTAGE TABLE

3 PORT OR STAR.

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2080-2

Table with columns for gauge height (0 FT. to 15 FT.) and rows for barge levels (0 to 11). Each cell contains capacity values for different gauge heights.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 4/18/00

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name