



BARGE "FMT-3011"

FLORIDA MARINE

HULL NO. 2080-3

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	(-) 0' - 0 1/8"	NIL
1'-0"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"
1'-6"	(-) 0' - 0 1/8"	(-) 0' - 0 1/4"	(-) 0' - 0 1/8"
2'-0"	(-) 0' - 0 1/8"	(-) 0' - 0 1/4"	(-) 0' - 0 1/4"
2'-6"	(-) 0' - 0 1/8"	(-) 0' - 0 3/8"	(-) 0' - 0 1/4"
3'-0"	(-) 0' - 0 1/4"	(-) 0' - 0 3/8"	(-) 0' - 0 3/8"
3'-6"	(-) 0' - 0 1/4"	(-) 0' - 0 1/2"	(-) 0' - 0 3/8"
4'-0"	(-) 0' - 0 1/4"	(-) 0' - 0 5/8"	(-) 0' - 0 1/2"
4'-6"	(-) 0' - 0 1/4"	(-) 0' - 0 5/8"	(-) 0' - 0 1/2"
5'-0"	(-) 0' - 0 3/8"	(-) 0' - 0 3/4"	(-) 0' - 0 5/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED, TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 5/16/00

BY:

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3011" FLORIDA MARINE

OUTAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2080-3

Table with columns for depth (0 FT. to 15 FT.) and corresponding capacity values in barrels of 42 U.S. gallons. Each depth has three rows of data (IN, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK.)

STRAPPED: 5/16/00

* CAPACITY BELOW STRIKE POINT

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of the inspector

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3011" FLORIDA MARINE

OUTAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2080-3

Table with columns for 0 FT. through 15 FT. and multiple rows for each depth, containing capacity values in gallons.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 5/16/00

REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK.)

* CAPACITY BELOW STRIKE POINT

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3011" FLORIDA MARINE

OUTAGE TABLE

2 PORT OR STAR

HULL NO. 2080-3

Table with columns for height (IN) and capacity (FT. 0 to 15) and rows for each inch measurement from 0 to 15 feet.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

REFERENCE GAUGE HEIGHT : 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK.)

STRAPPED: 5/16/00

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

[Handwritten signature]

INSPECTORATE AMERICA CORPORATION

* CAPACITY BELOW STRIKE POINT

BARGE "FMT-3011"
FLORIDA MARINE
OUTAGE TABLE

3 PORT



BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2080-3

Table with columns for gauge heights from 0 to 15 FT. and rows for depth increments (0, 1/4, 1/2, 3/4). Each cell contains numerical capacity data. Includes a handwritten asterisk in row 4, column 15.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

REFERENCE GAUGE HEIGHT : 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK.)

STRAPPED: 5/16/00

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.



INSPECTORATE AMERICA CORPORATION

* CAPACITY BELOW STRIKE POINT



BARGE "FMT-3011" FLORIDA MARINE

OUTAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2080-3

Table with 20 columns (IN 2 FT. to IN 16 FT.) and 20 rows (0 to 11). Each cell contains capacity values for different gauging points (1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 5/16/00

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11 1/2" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3011" FLORIDA MARINE

OUTAGE TABLE

3 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2080-3

Table with columns for gauge height (IN) and capacity (FT.) for gauges 0 through 16. Each gauge has four rows of data for different measurement points (1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 5/16/00

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-10 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of an inspector

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3011" FLORIDA MARINE

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2080-3

Table with 20 columns (IN, 2 FT., IN, 3 FT., IN, 4 FT., IN, 5 FT., IN, 6 FT., IN, 7 FT., IN, 8 FT., IN, 9 FT., IN, 10 FT., IN, 11 FT., IN, 12 FT., IN, 13 FT., IN, 14 FT., IN, 15 FT., IN, 16 FT.) and multiple rows of data.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 5/16/00

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-10 1/2" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of the inspector.

INSPECTORATE AMERICA CORPORATION