



BARGE "FMT-3016" FLORIDA MARINE

INNAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4337

Table with 19 columns (0 FT. to 14 FT.) and 19 rows (0 to 14). Each cell contains capacity values for different gauge heights (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/12/99

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-5 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR GEOMETRICAL CENTER OF TANK.)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and signature



BARGE "FMT-3016" FLORIDA MARINE

INNAGE TABLE

1 STAR

HULL NO. 4337

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

Table with columns for depth (0 FT. to 14 FT.) and capacity (0 to 324.22 barrels). Rows represent different gauge heights and depths.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/12/99

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-5 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR GEOMETRICAL CENTER OF TANK.)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3016" FLORIDA MARINE

INNAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4337

Table with columns for height (0 FT. to 14 FT.) and corresponding capacity values for various gauge heights (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/12/99

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-5 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR GEOMETRICAL CENTER OF TANK.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION







### BARGE "FMT-3016" FLORIDA MARINE

#### OUTAGE TABLE

# 1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4337

0 FT.		1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.		7 FT.		8 FT.		9 FT.		10 FT.		11 FT.		12 FT.		13 FT.		14 FT.		15 FT.	
0	0	5,177.50	0	4,881.27	0	4,516.28	0	4,151.29	0	3,786.30	0	3,421.30	0	3,056.31	0	2,691.32	0	2,326.33	0	1,961.34	0	1,596.34	0	1,231.35	0	866.36	0	501.49	0	155.89	
1/4	1/4	5,176.10	1/4	4,873.67	1/4	4,508.68	1/4	4,143.68	1/4	3,778.69	1/4	3,413.70	1/4	3,048.71	1/4	2,683.72	1/4	2,318.72	1/4	1,953.73	1/4	1,588.74	1/4	1,223.75	1/4	858.76	1/4	493.95	1/4	149.09	
3/4	3/4	5,172.16	3/4	4,858.46	3/4	4,493.47	3/4	4,128.48	3/4	3,763.48	3/4	3,398.49	3/4	3,033.50	3/4	2,668.51	3/4	2,303.52	3/4	1,938.52	3/4	1,573.53	3/4	1,208.54	3/4	843.55	3/4	478.87	3/4	135.50	
1	1	5,169.63	1	4,850.86	1	4,485.86	1	4,120.87	1	3,755.88	1	3,390.89	1	3,025.90	1	2,660.90	1	2,295.91	1	1,930.92	1	1,565.93	1	1,200.94	1	835.94	1	471.32	1	128.70	
11	11	4,911.69	11	4,546.70	11	4,181.70	11	3,816.71	11	3,451.72	11	3,086.73	11	2,721.74	11	2,356.74	11	1,991.75	11	1,626.76	11	1,261.77	11	866.78	11	531.79	11	183.32	11		

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-5 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR GEOMETRICAL CENTER OF TANK.)

STRAPPED: 10/12/99

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.



BARGE "FMT-3016" FLORIDA MARINE

OUTAGE TABLE

1 STAR

HULL NO. 4337

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

Table with columns for depth (0 FT. to 15 FT.) and rows for gauge heights (0, 1/4, 1/2, 3/4). Each cell contains capacity values in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/12/99

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-5 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR GEOMETRICAL CENTER OF TANK.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and signature











**BARGE "FMT-3016"**

**FLORIDA MARINE**

HULL NO. 4337

CORRECTION TABLE FOR TRIM AFT.

**FOR INNAGE GAUGES ONLY**

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	NIL	NIL
1'-0"	NIL	(-) 0' - 0 1/8"	NIL
1'-6"	NIL	(-) 0' - 0 1/8"	NIL
2'-0"	NIL	(-) 0' - 0 1/8"	NIL
2'-6"	NIL	(-) 0' - 0 1/8"	NIL
3'-0"	NIL	(-) 0' - 0 1/4"	NIL
3'-6"	NIL	(-) 0' - 0 1/4"	(-) 0' - 0 1/8"
4'-0"	NIL	(-) 0' - 0 1/4"	(-) 0' - 0 1/8"
4'-6"	NIL	(-) 0' - 0 1/4"	(-) 0' - 0 1/8"
5'-0"	NIL	(-) 0' - 0 1/4"	(-) 0' - 0 1/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,  
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 10/12/99

BY:

INSPECTORATE AMERICA CORPORATION