



BARGE "FMT-3023"

FLORIDA MARINE

HULL NO. 2091-2

CORRECTION TABLE FOR TRIM AFT.

FOR INNGAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	(-) 0'- 0 1/8"	(-) 0'- 0 1/8"
1'-0"	(-) 0'- 0 1/8"	(-) 0'- 0 1/8"	(-) 0'- 0 1/8"
1'-6"	(-) 0'- 0 1/8"	(-) 0' - 0 1/4"	(-) 0' - 0 1/4"
2'-0"	(-) 0'- 0 1/8"	(-) 0' - 0 1/4"	(-) 0' - 0 1/4"
2'-6"	(-) 0' - 0 1/4"	(-) 0' - 0 3/8"	(-) 0' - 0 3/8"
3'-0"	(-) 0' - 0 1/4"	(-) 0' - 0 3/8"	(-) 0' - 0 3/8"
3'-6"	(-) 0' - 0 3/8"	(-) 0' - 0 1/2"	(-) 0' - 0 1/2"
4'-0"	(-) 0' - 0 3/8"	(-) 0' - 0 1/2"	(-) 0' - 0 1/2"
4'-6"	(-) 0' - 0 3/8"	(-) 0' - 0 5/8"	(-) 0' - 0 5/8"
5'-0"	(-) 0' - 0 1/2"	(-) 0' - 0 3/4"	(-) 0' - 0 3/4"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 4/16/01

BY:

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3023" FLORIDA MARINE OUTAGE TABLE

1 PORT

HULL NO. 2091-2

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

Table with columns for depth (0 FT. to 15 FT.) and rows for measurement intervals (0, 1/4, 1/2, 3/4) at each depth. Contains numerical capacity data.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 4/16/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature: Bauer

INSPECTORATE AMERICA CORPORATION

BARGE "FMT-3023" FLORIDA MARINE

OUTAGE TABLE

3 PORT



INSPECTORATE ISO 9002 ACCREDITED

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2091-2

Table with columns for gauge heights (0 FT. to 15 FT.) and rows for depth measurements (0 to 15 FT.). Each cell contains capacity values for different gauge types (1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 4/16/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature: Amer

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3023" FLORIDA MARINE

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2091-2

Table with 20 columns (0 FT. to 15 FT.) and multiple rows for each depth (0, 1/4, 1/2, 3/4). Each cell contains numerical values representing measurements at specific depths.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 4/16/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION text.



BARGE "FMT-3023" FLORIDA MARINE

OUTAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2091-2

Table with columns for height (2 FT. to 16 FT.) and rows for gauge readings (0, 1/4, 1/2, 3/4) at each height.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 4/16/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3023" FLORIDA MARINE

OUTAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2091-2

Table with columns for gauge height (0 to 16 FT.) and rows for capacity measurements at various depths (0, 1/4, 1/2, 3/4). Each cell contains numerical capacity values in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 4/16/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-10 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector and text: INSPECTORATE AMERICA CORPORATION

