



BARGE "FMT-3024"

FLORIDA MARINE

HULL NO. 4354

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	NIL	NIL
1'-0"	NIL	(-) 0' - 0 1/8"	NIL
1'-6"	NIL	(-) 0' - 0 1/8"	NIL
2'-0"	NIL	(-) 0' - 0 1/8"	NIL
2'-6"	NIL	(-) 0' - 0 1/8"	NIL
3'-0"	NIL	(-) 0' - 0 1/4"	NIL
3'-6"	NIL	(-) 0' - 0 1/4"	(-) 0' - 0 1/8"
4'-0"	NIL	(-) 0' - 0 1/4"	(-) 0' - 0 1/8"
4'-6"	NIL	(-) 0' - 0 1/4"	(-) 0' - 0 1/8"
5'-0"	NIL	(-) 0' - 0 1/4"	(-) 0' - 0 1/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 3/30/00

BY:

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3024" FLORIDA MARINE

INNAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4354

Table with 18 columns (0 FT. to 14 FT.) and multiple rows of capacity data for each depth. Includes a note 'CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS' at the bottom left of the table area.

STRAPPED: 3/30/00

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-5 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR GEOMETRICAL CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

STAR REFERENCE GAUGE HEIGHT : 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR GEOMETRICAL CENTER OF TANK)



INSPECTORATE

ISO 9002 ACCREDITED

BARGE "FMT-3024" FLORIDA MARINE

INNAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4354

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.	IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.
0	14.33	0	364.96	0	729.49	0	1,093.04	0	1,458.28	0	1,823.51	0	2,188.74	0	2,553.97	0	2,919.20	0	3,284.43	0	3,624.77	0	3,878.40	0	4,131.65	0	4,384.90	0	4,638.15
1	33.86	1	395.35	1	759.76	1	1,123.48	1	1,488.71	1	1,853.94	1	2,219.17	1	2,584.41	1	2,949.64	1	3,314.87	1	3,646.26	1	3,899.51	1	4,152.75	1	4,406.00	1	4,658.07
2	61.00	2	425.75	2	790.04	2	1,153.92	2	1,519.15	2	1,884.38	2	2,249.61	2	2,614.84	2	2,980.07	2	3,345.31	2	3,667.36	2	3,920.61	2	4,173.86	2	4,427.11	2	4,675.26
3	91.39	3	456.15	3	820.31	3	1,184.35	3	1,549.58	3	1,914.81	3	2,280.05	3	2,645.28	3	3,010.51	3	3,375.74	3	3,688.47	3	3,941.71	3	4,194.96	3	4,448.21	3	4,689.33
4	121.79	4	486.54	4	850.58	4	1,214.79	4	1,580.02	4	1,945.25	4	2,310.48	4	2,675.71	4	3,040.95	4	3,406.18	4	3,709.57	4	3,962.82	4	4,216.07	4	4,469.31	4	4,706.26
5	152.19	5	516.94	5	880.85	5	1,245.22	5	1,610.45	5	1,975.69	5	2,340.92	5	2,706.15	5	3,071.38	5	3,436.61	5	3,730.67	5	3,983.92	5	4,237.17	5	4,490.42	5	4,708.07
6	182.58	6	547.33	6	911.12	6	1,275.66	6	1,640.89	6	2,006.12	6	2,371.35	6	2,736.59	6	3,101.82	6	3,467.05	6	3,751.78	6	4,005.03	6	4,258.27	6	4,511.52	6	4,712.74
7	212.98	7	577.73	7	941.40	7	1,306.10	7	1,671.33	7	2,036.56	7	2,401.79	7	2,767.02	7	3,132.25	7	3,496.79	7	3,772.88	7	4,026.13	7	4,279.38	7	4,532.63	7	4,714.58
8	243.37	8	608.13	8	971.67	8	1,336.53	8	1,701.76	8	2,066.99	8	2,432.23	8	2,797.46	8	3,162.69	8	3,525.15	8	3,793.99	8	4,047.23	8	4,300.48	8	4,553.73	8	
9	273.77	9	638.52	9	1,001.94	9	1,366.97	9	1,732.20	9	2,097.43	9	2,462.66	9	2,827.89	9	3,193.13	9	3,552.13	9	3,815.09	9	4,068.34	9	4,321.59	9	4,574.83	9	
10	304.17	10	668.92	10	1,032.21	10	1,397.40	10	1,762.63	10	2,127.87	10	2,493.10	10	2,858.33	10	3,223.56	10	3,577.73	10	3,836.19	10	4,089.44	10	4,342.69	10	4,595.94	10	
11	334.56	11	699.22	11	1,062.61	11	1,427.84	11	1,793.07	11	2,158.30	11	2,523.53	11	2,888.77	11	3,254.00	11	3,601.94	11	3,857.30	11	4,110.55	11	4,363.79	11	4,611.77	11	
12	364.96	12	732.56	12	1,093.04	12	1,458.28	12	1,823.51	12	2,188.74	12	2,553.97	12	2,919.20	12	3,284.43	12	3,624.77	12	3,878.40	12	4,131.65	12	4,384.90	12	4,638.15	12	
13	395.35	13	759.76	13	1,123.48	13	1,488.71	13	1,853.94	13	2,219.17	13	2,584.41	13	2,949.64	13	3,314.87	13	3,646.26	13	3,899.51	13	4,152.75	13	4,406.00	13	4,658.07	13	
14	425.75	14	790.04	14	1,153.92	14	1,519.15	14	1,884.38	14	2,249.61	14	2,614.84	14	2,980.07	14	3,345.31	14	3,667.36	14	3,920.61	14	4,173.86	14	4,427.11	14	4,675.26	14	
15	456.15	15	820.31	15	1,184.35	15	1,549.58	15	1,914.81	15	2,280.05	15	2,645.28	15	3,010.51	15	3,375.74	15	3,688.47	15	3,941.71	15	4,194.96	15	4,448.21	15	4,689.33	15	
16	486.54	16	850.58	16	1,214.79	16	1,580.02	16	1,945.25	16	2,310.48	16	2,675.71	16	3,040.95	16	3,406.18	16	3,709.57	16	3,962.82	16	4,216.07	16	4,469.31	16	4,706.26	16	

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 3/30/00

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR GEOMETRICAL CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR GEOMETRICAL CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3024" FLORIDA MARINE

OUTAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4354

Table with columns for 0 FT. to 15 FT. and rows for tank levels 0, 1/4, 1/2, 3/4. Each cell contains two numerical values representing capacity at different gauge heights.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 3/30/00

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-5 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR GEOMETRICAL CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of an inspector

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3024" FLORIDA MARINE

OUTAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4354

Table with 30 columns (0 FT. to 15 FT.) and 30 rows (0 to 15). Each cell contains capacity values for different gauges (IN, 1/4, 1/2, 3/4) at various heights.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 3/30/00

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-5 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR GEOMETRICAL CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature and Inspectorate America Corporation logo



BARGE "FMT-3024" FLORIDA MARINE

OUTAGE TABLE

3 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4354

Table with columns for gauge height (0 FT. to 15 FT.) and multiple rows for each height. Each row contains 20 numerical values representing capacity measurements. The table is organized in a grid format with 16 main columns and multiple rows per column.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 3/30/00

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR GEOMETRICAL CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector

INSPECTORATE AMERICA CORPORATION

