



BARGE "FMT-3029"

FLORIDA MARINE

HULL NO. 2094-2

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	(-) 0' - 0 1/8"	NIL
1'-0"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"
1'-6"	(-) 0' - 0 1/8"	(-) 0' - 0 1/4"	(-) 0' - 0 1/8"
2'-0"	(-) 0' - 0 1/8"	(-) 0' - 0 1/4"	(-) 0' - 0 1/4"
2'-6"	(-) 0' - 0 1/8"	(-) 0' - 0 3/8"	(-) 0' - 0 1/4"
3'-0"	(-) 0' - 0 1/4"	(-) 0' - 0 3/8"	(-) 0' - 0 3/8"
3'-6"	(-) 0' - 0 1/4"	(-) 0' - 0 1/2"	(-) 0' - 0 3/8"
4'-0"	(-) 0' - 0 1/4"	(-) 0' - 0 5/8"	(-) 0' - 0 1/2"
4'-6"	(-) 0' - 0 1/4"	(-) 0' - 0 5/8"	(-) 0' - 0 1/2"
5'-0"	(-) 0' - 0 3/8"	(-) 0' - 0 3/4"	(-) 0' - 0 5/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED, TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 6/20/01

BY:

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3029"
FLORIDA MARINE

INNAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2094-2

Table with 15 columns (0 FT. to 14 FT.) and multiple rows representing different gauge heights (0, 1/4, 1/2, 3/4) and barge numbers (0-11).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/20/01

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name



BARGE "FMT-3029" FLORIDA MARINE

INNAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2094-2

Table with columns for 0 FT. to 14 FT. and rows for 0 to 14. Each cell contains capacity values in barrels at different depths.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/20/01

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT: 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)
STAR REFERENCE GAUGE HEIGHT: 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3029" FLORIDA MARINE INNAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2094-2

Main innage table with columns for depth (0 FT. to 14 FT.) and multiple rows of capacity data.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/20/01

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of the inspector.

INSPECTORATE AMERICA CORPORATION



**BARGE "FMT-3029"
FLORIDA MARINE**

OUTAGE TABLE

1 PORT

HULL NO. 2094-2

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

Table with 15 columns representing heights from 0 FT. to 15 FT. and multiple rows for each height, providing capacity and gauge readings.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/20/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector
INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3029" FLORIDA MARINE

OUTAGE TABLE

3 PORT

HULL NO. 2094-2

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

Table with columns for depth (0 FT. to 15 FT.) and rows for gauge readings. Each cell contains a numerical value representing capacity or measurement at a specific depth and gauge location.

STRAPPED: 6/20/01

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

* CAPACITY BELOW STRIKE POINT

INSPECTORATE AMERICA CORPORATION logo and name



BARGE "FMT-3029"
FLORIDA MARINE

OUTAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2094-2

Table with columns for depth (2 FT. to 16 FT.) and rows for measurement points (0, 1/4, 1/2, 3/4). Each cell contains a numerical value representing capacity in barrels.


CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/20/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-10 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.



INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3029" FLORIDA MARINE OUTAGE TABLE

2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2094-2

Table with columns for gauge height (2 FT to 16 FT) and capacity. Each gauge height has four rows representing different measurement points (0, 1/4, 1/2, 3/4). The table contains numerical data for each measurement.

STRAPPED: 6/20/01

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11 1/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of inspector and INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3029" FLORIDA MARINE

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2094-2

IN		2 FT.		IN		3 FT.		IN		4 FT.		IN		5 FT.		IN		6 FT.		IN		7 FT.		IN		8 FT.		IN		9 FT.		IN		10 FT.		IN		11 FT.		IN		12 FT.		IN		13 FT.		IN		14 FT.		IN		15 FT.		IN		16 FT.	
0		0	4,990.08	0	4,709.81	0	4,429.54	0	4,149.27	0	3,867.69	0	3,493.18	0	3,100.88	0	2,708.57	0	2,316.27	0	1,923.96	0	1,531.66	0	1,139.36	0	751.67	0	359.79																														
1/4		1/4	4,984.24	1/4	4,703.97	1/4	4,423.70	1/4	4,143.43	1/4	3,861.27	1/4	3,485.01	1/4	3,092.70	1/4	2,700.40	1/4	2,308.10	1/4	1,915.79	1/4	1,523.49	1/4	1,131.18	1/4	743.60	1/4	351.62																														
1/2		1/2	4,978.40	1/2	4,698.13	1/2	4,417.86	1/2	4,137.59	1/2	3,854.86	1/2	3,476.83	1/2	3,084.53	1/2	2,692.23	1/2	2,299.92	1/2	1,907.62	1/2	1,515.31	1/2	1,123.01	1/2	735.54	1/2	343.44																														
3/4		3/4	4,972.57	3/4	4,692.29	3/4	4,412.02	3/4	4,131.75	3/4	3,848.45	3/4	3,468.66	3/4	3,076.36	3/4	2,684.05	3/4	2,291.75	3/4	1,899.45	3/4	1,507.14	3/4	1,114.84	3/4	727.47	3/4	335.27																														

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/20/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

[Signature]
INSPECTORATE AMERICA CORPORATION