



BARGE "FMT-3037"

FLORIDA MARINE

HULL NO. 4378

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

| TRIM | TANKS NO. 1 PORT OR STAR. | TANKS NO. 2 PORT OR STAR. |
|-------|------------------------------|------------------------------|
| 0'-6" | (-) 0'- 0 1/8" | (+) 0'- 0 1/8" |
| 1'-0" | (-) 0'- 0 1/8" | (+) 0'- 0 1/4" |
| 1'-6" | (-) 0'- 0 1/8" | (+) 0'- 0 3/8" |
| 2'-0" | (-) 0'- 0 1/4" | (+) 0'- 0 1/2" |
| 2'-6" | (-) 0'- 0 1/4" | (+) 0'- 0 3/4" |
| 3'-0" | (-) 0'- 0 1/4" | (+) 0'- 0 7/8" |
| 3'-6" | (-) 0'- 0 3/8" | (+) 0'- 1" |
| 4'-0" | (-) 0'- 0 3/8" | (+) 0'- 1 1/8" |
| 4'-6" | (-) 0'- 0 1/2" | (+) 0'- 1 1/4" |
| 5'-0" | (-) 0'- 0 1/2" | (+) 0'- 1 3/8" |
| 5'-6" | (-) 0'- 0 5/8" | (+) 0'- 1 1/2" |
| 6'-0" | (-) 0'- 0 5/8" | (+) 0'- 1 5/8" |
| 6'-6" | (-) 0'- 0 3/4" | (+) 0'- 1 3/4" |
| 7'-0" | (-) 0'- 0 3/4" | (+) 0'- 1 7/8" |
| 7'-6" | (-) 0'- 0 3/4" | (+) 0'- 2" |
| 8'-0" | (-) 0'- 0 7/8" | (+) 0'- 2 1/8" |

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 4/11/01

BY: 

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3037" FLORIDA MARINE

INNAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4378

Table with columns for depth (0 FT. to 14 FT.) and corresponding capacity values in barrels. Includes sub-columns for 1/4, 1/2, and 3/4 increments for each depth.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 4/11/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-5 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3037" FLORIDA MARINE

OUTAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4378

Table with columns for height (0 FT. to 15 FT.) and corresponding capacity values for each foot increment.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 4/1/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of the inspector

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3037" FLORIDA MARINE

OUTAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4378

Table with columns for gauge height (IN) and capacity (42 U.S. GALLONS) for gauges 0 through 16 FT. Each gauge has four capacity readings for different gauge heights (1/4, 1/2, 3/4, and full).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 4/11/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of the inspector

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3037" FLORIDA MARINE

OUTAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4378

Table with 20 columns (IN, 2 FT., IN, 3 FT., IN, 4 FT., IN, 5 FT., IN, 6 FT., IN, 7 FT., IN, 8 FT., IN, 9 FT., IN, 10 FT., IN, 11 FT., IN, 12 FT., IN, 13 FT., IN, 14 FT., IN, 15 FT., IN, 16 FT.) and 48 rows of capacity data.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 4/11/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11 1/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name

