



BARGE "FMT-3039"

FLORIDA MARINE


HULL NO. 2101-1

CORRECTION TABLE FOR TRIM AFT.			
FOR INNAGE GAUGES ONLY			
TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	(-) 0' - 0 1/8"	NIL
1'-0"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"
1'-6"	(-) 0' - 0 1/8"	(-) 0' - 0 1/4"	(-) 0' - 0 1/8"
2'-0"	(-) 0' - 0 1/8"	(-) 0' - 0 1/4"	(-) 0' - 0 1/4"
2'-6"	(-) 0' - 0 1/8"	(-) 0' - 0 3/8"	(-) 0' - 0 1/4"
3'-0"	(-) 0' - 0 1/4"	(-) 0' - 0 3/8"	(-) 0' - 0 3/8"
3'-6"	(-) 0' - 0 1/4"	(-) 0' - 0 1/2"	(-) 0' - 0 3/8"
4'-0"	(-) 0' - 0 1/4"	(-) 0' - 0 5/8"	(-) 0' - 0 1/2"
4'-6"	(-) 0' - 0 1/4"	(-) 0' - 0 5/8"	(-) 0' - 0 1/2"
5'-0"	(-) 0' - 0 3/8"	(-) 0' - 0 3/4"	(-) 0' - 0 5/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED, TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 12/4/01 BY: 
INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3039" FLORIDA MARINE

INNAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2101-1

Table with 20 columns for height (0 FT. to 14 FT.) and 20 rows for depth (0 to 3/4). Each cell contains capacity values for different measurement points.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/4/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate signature and text: INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3039" FLORIDA MARINE

INNAGE TABLE

3 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2101-1

Table with columns for height (0 FT. to 14 FT.) and corresponding capacity values. Includes a note: CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 12/4/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and name



BARGE "FMT-3039" FLORIDA MARINE

INNAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2101-1

Table with columns for depth (0 FT. to 14 FT.) and corresponding capacity values in barrels. Includes a note: CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS.

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 12/4/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name.



BARGE "FMT-3039"
FLORIDA MARINE

OUTAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2101-1

Table with 15 columns representing height in feet (0 FT. to 15 FT.) and 15 rows representing gauge height in feet (0 to 15 FT.). Each cell contains capacity values in barrels for different gauge heights (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/4/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name.



BARGE "FMT-3039" FLORIDA MARINE

OUTAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2101-1

Table with columns for depth (0 FT. to 15 FT.) and rows for gauge readings (0 to 3/4). Each cell contains numerical values representing measurements at specific depths and gauge heights.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/4/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of an inspector

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3039" FLORIDA MARINE

OUTAGE TABLE

2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2101-1

Table with columns for gauge height (0 FT. to 15 FT.) and rows for depth (0 to 3 3/4). Each cell contains a numerical value representing the measurement at that depth and gauge height.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/4/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION text.



BARGE "FMT-3039" FLORIDA MARINE

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2101-1

Table with columns for gauge height (0 FT. to 15 FT.) and rows for capacity measurements (0 to 11). Each cell contains a numerical value representing capacity in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/4/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3039" FLORIDA MARINE OUTAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2101-1

2 FT.		3 FT.		4 FT.		5 FT.		6 FT.		7 FT.		8 FT.		9 FT.		10 FT.		11 FT.		12 FT.		13 FT.		14 FT.		15 FT.		16 FT.					
IN	0	1/4	1/2	3/4	1	1/4	1/2	3/4	1	1/4	1/2	3/4	1	1/4	1/2	3/4	1	1/4	1/2	3/4	1	1/4	1/2	3/4	1	1/4	1/2	3/4	1	1/4	1/2	3/4	
0																																	
1/4																																	
1/2																																	
3/4																																	
1																																	
1/4																																	
1/2																																	
3/4																																	
2																																	
1/4																																	
1/2																																	
3/4																																	
3																																	
1/4																																	
1/2																																	
3/4																																	
4																																	
1/4																																	
1/2																																	
3/4																																	
5																																	
1/4																																	
1/2																																	
3/4																																	
6																																	
1/4																																	
1/2																																	
3/4																																	
7																																	
1/4																																	
1/2																																	
3/4																																	
8																																	
1/4																																	
1/2																																	
3/4																																	
9																																	
1/4																																	
1/2																																	
3/4																																	
10																																	
1/4																																	
1/2																																	
3/4																																	
11																																	
1/4																																	
1/2																																	
3/4																																	
12																																	

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/4/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-10 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.


 INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3039" FLORIDA MARINE

OUTAGE TABLE

2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2101-1

Table with 19 columns (IN, 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT., 15 FT., 16 FT.) and 50 rows of gauge readings. Includes a large handwritten 'X' on the left side of the table.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 10'-11 1/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

STRAPPED: 12/4/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of an inspector

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3039" FLORIDA MARINE

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2101-1

Table with 17 columns (2 FT. to 16 FT.) and 20 rows (0 to 11). Each cell contains a numerical value and a fraction (e.g., 4,985.58 0/4). Includes a diagonal line in the first 5 columns.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 16'-11" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

STRAPPED: 12/4/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION

