



BARGE "FMT-3048"
FLORIDA MARINE

INNAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2090-4

Main innage table with columns for height (0 FT. to 14 FT.) and corresponding capacity values in barrels of 42 U.S. gallons.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/19/12 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT).

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-5 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and logo



BARGE "FMT-3048" FLORIDA MARINE

INNAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2090-4

Table with 17 columns (0 FT. to 14 FT.) and 17 rows (0 to 14). Each cell contains capacity values for different gauge heights (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/19/12 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT).

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and name.



BARGE "FMT-3048"
FLORIDA MARINE

OUTAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2090-4

Table with 17 columns (0 FT. to 15 FT.) and multiple rows of capacity data for various gauge heights (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/19/12 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT).

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION logo



BARGE "FMT-3048"
FLORIDA MARINE

OUTAGE TABLE

2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2090-4

Table with 16 columns for gauge heights from 0 FT. to 15 FT. and multiple rows of capacity data. Includes a large diagonal line on the left side of the table.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-5 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 6/19/12 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT).

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3048"
FLORIDA MARINE

OUTAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2090-4

Table with 18 columns for gauge heights (0 FT. to 15 FT.) and multiple rows for liquid levels. Each cell contains a numerical value representing capacity in barrels. The table is organized into 18 columns corresponding to gauge heights from 0 FT. to 15 FT. Each column contains multiple rows representing different liquid levels at that gauge height.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 6/19/12 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT).

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

