



BARGE "FMT-3054"
FLORIDA MARINE

HULL NO. 2090-7

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1	TANKS NO. 2	TANKS NO. 3
	PORT OR STAR.	PORT OR STAR.	PORT OR STAR.
0'-6"	NIL	NIL	NIL
1'-0"	NIL	NIL	NIL
1'-6"	NIL	NIL	NIL
2'-0"	NIL	NIL	NIL
2'-6"	NIL	NIL	NIL
3'-0"	NIL	NIL	NIL
3'-6"	NIL	NIL	NIL
4'-0"	(-) 0'-0 1/8"	NIL	NIL
4'-6"	(-) 0'-0 1/8"	(+) 0'-0 1/8"	NIL
5'-0"	(-) 0'-0 1/8"	(+) 0'-0 1/8"	NIL

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 3/7/01 BY: 
INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3054" FLORIDA MARINE

INNAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2090-7

Table with columns for depth (0 FT. to 14 FT.) and corresponding innage values for various gauge heights (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 3/7/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3054" FLORIDA MARINE

INNAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2090-7

Table with 18 columns (0 FT. to 14 FT.) and multiple rows of depth measurements and corresponding capacity values.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 3/7/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature



BARGE "FMT-3054" FLORIDA MARINE

INNAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2090-7

Table with 14 columns (0 FT. to 14 FT.) and multiple rows of depth measurements (0, 1/4, 1/2, 3/4) and corresponding capacity values in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 3/7/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name



BARGE "FMT-3054" FLORIDA MARINE

OUTAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2090-7

Table with 17 columns (0 FT. to 15 FT.) and 17 rows (0 to 11). Each cell contains a gauge reading (e.g., 5,194.96) and a fractional gauge height indicator (e.g., 1/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

REFERENCE GAUGE HEIGHT : 15'-3 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 3/7/01

* CAPACITY BELOW STRIKE POINT

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of an inspector

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3054" FLORIDA MARINE

OUTAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2090-7

Table with columns for height (0 FT. to 15 FT.) and corresponding capacity values in barrels. Includes sub-columns for 1/4, 1/2, and 3/4 increments for each height.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 3/7/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector and text: INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3054" FLORIDA MARINE

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2090-7

Table with columns for depth (0 FT. to 15 FT.) and rows for gauge readings (0 to 3/4) at each depth. Each cell contains a numerical value representing the gauge reading.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 3/7/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector and text: INSPECTORATE AMERICA CORPORATION