



BARGE "FMT- 3058"

FLORIDA MARINE


HULL NO. 2093-1

CORRECTION TABLE FOR TRIM AFT.			
FOR INNAGE GAUGES ONLY			
TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	NIL	NIL
1'-0"	NIL	NIL	NIL
1'-6"	NIL	NIL	(-) 0'- 0 1/8"
2'-0"	NIL	(+) 0'- 0 1/8"	(-) 0'- 0 1/8"
2'-6"	(+) 0'- 0 1/8"	(+) 0'- 0 1/8"	(-) 0'- 0 1/8"
3'-0"	(+) 0'- 0 1/8"	(+) 0'- 0 1/8"	(-) 0'- 0 1/8"
3'-6"	(+) 0'- 0 1/8"	(+) 0'- 0 1/8"	(-) 0'- 0 1/8"
4'-0"	(+) 0'- 0 1/8"	(+) 0'- 0 1/8"	(-) 0'- 0 1/8"
4'-6"	(+) 0'- 0 1/8"	(+) 0'- 0 1/4"	(-) 0'- 0 1/4"
5'-0"	(+) 0'- 0 1/8"	(+) 0'- 0 1/4"	(-) 0'- 0 1/4"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 5/11/01 BY: 
INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3058" FLORIDA MARINE INNAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2093-1

Table with columns for gauge height (0 FT. to 14 FT.) and corresponding capacity values. Includes a note at the bottom: 'CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS'.

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 5/1/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of an inspector.

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3058"
FLORIDA MARINE
INNAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2093-1

Table with columns for height (0 FT. to 14 FT.) and capacity (IN). Rows represent different gauge heights and capacities.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 5/11/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION text.



BARGE "FMT-3058" FLORIDA MARINE INNAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2093-1

Table with 15 columns (0 FT. to 14 FT.) and 3 rows per column (0, 1/2, 3/4). Each cell contains numerical values representing measurements.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 5/11/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION logo



BARGE "FMT-3058" FLORIDA MARINE

OUTAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2093-1

Table with columns for height (0 FT. to 15 FT.) and corresponding capacity values in whole barrels of 42 U.S. gallons.

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 5/11/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3058" FLORIDA MARINE

OUTAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2093-1

Table with columns for depth (0 FT. to 15 FT.) and corresponding capacity values in barrels of 42 U.S. gallons. Includes a 'CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS' header and a 'STRAPPED: 5/11/01' note.

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and signature



BARGE "FMT-3058" FLORIDA MARINE

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2093-1

Table with columns for gauge height (0 FT. to 15 FT.) and rows for tank capacity (0 to 34). Each cell contains a numerical value representing capacity in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 5/11/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and company name.



BARGE "FMT-3058" FLORIDA MARINE

OUTAGE TABLE

3 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2093-1

Table with 15 columns (0 FT. to 15 FT.) and multiple rows showing capacity data for various gauge heights (0, 1/4, 1/2, 3/4, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 14, 15). Includes a note: CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 5/11/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspectorate America Corporation



BARGE "FMT-3058" FLORIDA MARINE OUTAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2093-1

Table with columns for gauge height (2 FT. to 16 FT.) and rows for measurement points (0 to 11). Each cell contains a numerical value representing capacity in barrels of 42 U.S. gallons.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

STRAPPED: 5/11/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION text.



**BARGE "FMT-3058"
FLORIDA MARINE**

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2093-1

Table with 19 columns (2 FT. to 16 FT.) and multiple rows of capacity data. Includes fractional gauge readings (0, 1/4, 1/2, 3/4) and capacity values in barrels of 42 U.S. gallons. Values range from approximately 341.35 to 17.54 barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 5/11/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

(Signature)
INSPECTORATE AMERICA CORPORATION

