



BARGE "FMT-3070"

FLORIDA MARINE


HULL NO. 2098-2

CORRECTION TABLE FOR TRIM AFT.			
FOR INNAGE GAUGES ONLY			
TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	(-) 0' - 0 1/8"	NIL
1'-0"	NIL	(-) 0' - 0 1/8"	NIL
1'-6"	NIL	(-) 0' - 0 1/4"	NIL
2'-0"	NIL	(-) 0' - 0 3/8"	NIL
2'-6"	NIL	(-) 0' - 0 3/8"	NIL
3'-0"	NIL	(-) 0' - 0 1/2"	NIL
3'-6"	NIL	(-) 0' - 0 5/8"	NIL
4'-0"	NIL	(-) 0' - 0 3/4"	NIL
4'-6"	NIL	(-) 0' - 0 3/4"	NIL
5'-0"	NIL	(-) 0' - 0 7/8"	NIL

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 10/2/01 BY: 
INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3070"
FLORIDA MARINE
INNAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2098-2

Table with columns for height in feet (0 to 14) and corresponding capacity in barrels. Each row represents a height interval with three measurement points (IN, 1/2, 3/4). The table includes 15 columns for each foot height and their corresponding capacity values.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 10/2/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3070"
FLORIDA MARINE
INNAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2098-2

Table with columns for height (0 FT. to 14 FT.) and corresponding capacity values in barrels. Includes a note: CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 10/2/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name



BARGE "FMT-3070"
FLORIDA MARINE
INNAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2098-2

Table with columns for height (0 FT. to 14 FT.) and corresponding capacity values in barrels. Includes sub-rows for 1/4, 1/2, and 3/4 increments.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/2/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION logo



BARGE "FMT-3070" FLORIDA MARINE

OUTAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2098-2

Table with 16 columns (0 FT. to 15 FT.) and 32 rows of capacity data. Each row shows capacity in barrels for different gauge heights at various lengths.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/2/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3070" FLORIDA MARINE

OUTAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2098-2

Table with 20 columns (2 FT. to 16 FT.) and multiple rows of capacity data. Includes a diagonal line in the first column.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/20/1

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-10 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and name



BARGE "FMT-3070" FLORIDA MARINE

OUTAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2098-2

Large data table with 20 columns (IN, 2 FT., IN, 3 FT., IN, 4 FT., IN, 5 FT., IN, 6 FT., IN, 7 FT., IN, 8 FT., IN, 9 FT., IN, 10 FT., IN, 11 FT., IN, 12 FT., IN, 13 FT., IN, 14 FT., IN, 15 FT., IN, 16 FT.) and multiple rows of numerical data.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/2/01

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-10 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and name.

