



BARGE "FMT-3072"

FLORIDA MARINE

HULL NO. 2099-1

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	(-) 0' - 0 1/8"	NIL
1'-0"	NIL	(-) 0' - 0 1/8"	NIL
1'-6"	NIL	(-) 0' - 0 1/4"	NIL
2'-0"	NIL	(-) 0' - 0 3/8"	NIL
2'-6"	NIL	(-) 0' - 0 3/8"	NIL
3'-0"	NIL	(-) 0' - 0 1/2"	NIL
3'-6"	NIL	(-) 0' - 0 5/8"	NIL
4'-0"	NIL	(-) 0' - 0 3/4"	NIL
4'-6"	NIL	(-) 0' - 0 3/4"	NIL
5'-0"	NIL	(-) 0' - 0 7/8"	NIL

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED, TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 10/11/01

BY:

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3072" FLORIDA MARINE INNAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2099-1

Table with columns for height (0 FT. to 14 FT.) and corresponding capacity values in barrels of 42 U.S. gallons. Includes a note: CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

\* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-3 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-3 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 10/10/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name



BARGE "FMT-3072" FLORIDA MARINE INNAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2099-1

Table with columns for depth (0 to 14 FT) and corresponding capacity in barrels for each inch measurement.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 10/10/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION logo





BARGE "FMT-3072" FLORIDA MARINE

OUTAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2099-1

Table with 16 columns (0 FT. to 15 FT.) and 34 rows of capacity data. Includes sub-columns for 1/4, 1/2, and 3/4 increments. Values represent capacity in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/10/01

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-3 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION text.



BARGE "FMT-3072"
FLORIDA MARINE

OUTAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2099-1

Main data table with columns for height in feet (0 to 15) and corresponding capacity in barrels. Includes sub-headers for IN and OUT measurements.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-3 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 10/10/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name.



BARGE "FMT-3072" FLORIDA MARINE

OUTAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2099-1

Table with columns for 0 FT. through 15 FT. and rows for 0, 1/4, 1/2, 3/4, and full tank capacity. Includes a note: CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/10/01

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3072" FLORIDA MARINE

OUTAGE TABLE

3 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2099-1

Table with columns for gauge height (0 FT. to 15 FT.) and rows for capacity measurements. Includes a diagonal line through the first 10 rows.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/10/01

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION text











BARGE "FMT-3072" FLORIDA MARINE

OUTAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2099-1

Table with columns for gauge height (IN) and capacity (0 to 16 FT) for 2 FT, 3 FT, 4 FT, 5 FT, 6 FT, 7 FT, 8 FT, 9 FT, 10 FT, 11 FT, 12 FT, 13 FT, 14 FT, 15 FT, and 16 FT. Includes a note: CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-10 1/2" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

STRAPPED: 10/11/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3072" FLORIDA MARINE

OUTAGE TABLE

3 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2099-1

Table with columns for height (IN), 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT., 15 FT., 16 FT. and rows for tank levels from 0 to 11.5 ft.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-10 1/2" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

STRAPPED: 10/11/01

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

