



BARGE "FMT-3076" FLORIDA MARINE INNAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2100-1

Table with columns for gauge height (0 FT. to 14 FT.) and corresponding capacity values in barrels. Includes a row for capacities given in barrels of 42 U.S. gallons.

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 6/19/12 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT).

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of Inspectorate America Corporation.

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3076" FLORIDA MARINE

OUTAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2100-1

Table with columns for height (0 FT. to 15 FT.) and rows for gauge numbers (0 to 11), showing capacity in barrels for various gauge heights.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 6/19/12 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT).

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of Inspectorate America Corporation

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3076" FLORIDA MARINE

OUTAGE TABLE

3 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2100-1

Table with 17 columns representing gauge heights (0 FT. to 15 FT.) and multiple rows representing different barge configurations and capacities.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/19/12 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT).

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and name

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3076" FLORIDA MARINE

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2100-1

Table with 18 columns (0 FT. to 15 FT.) and 20 rows (0 to 11 FT. depth), listing capacity values in barrels for each depth and distance.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/19/12 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT).

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION