



BARGE "FMT-3114"

FLORIDA MARINE

HULL NO. 2114-1

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	(-) 0' - 0 1/8"	NIL
1'-0"	NIL	(-) 0' - 0 1/8"	NIL
1'-6"	NIL	(-) 0' - 0 1/4"	NIL
2'-0"	NIL	(-) 0' - 0 3/8"	NIL
2'-6"	NIL	(-) 0' - 0 3/8"	NIL
3'-0"	NIL	(-) 0' - 0 1/2"	NIL
3'-6"	NIL	(-) 0' - 0 5/8"	NIL
4'-0"	NIL	(-) 0' - 0 3/4"	NIL
4'-6"	NIL	(-) 0' - 0 3/4"	NIL
5'-0"	NIL	(-) 0' - 0 7/8"	NIL


NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 12/6/02

BY:


INSPECTORATE AMERICA CORPORATION



**BARGE "FMT-3114"
FLORIDA MARINE
INNAGE TABLE**

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

0 FT.		1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.		7 FT.		8 FT.		9 FT.		10 FT.		11 FT.		12 FT.		13 FT.		14 FT.	
0	15.58	0	367.71	0	734.94	0	1,101.30	0	1,468.74	0	1,836.18	0	2,203.62	0	2,571.06	0	2,938.50	0	3,305.94	0	3,673.38	0	4,040.82	0	4,408.26	0	4,775.70	0	5,143.14
1/4	20.37	1/4	375.37	1/4	742.56	1/4	1,108.95	1/4	1,476.39	1/4	1,843.83	1/4	2,211.27	1/4	2,578.71	1/4	2,946.15	1/4	3,313.59	1/4	3,681.03	1/4	4,048.47	1/4	4,415.91	1/4	4,783.35	1/4	5,150.79
1/2	25.15	1/2	383.02	1/2	750.19	1/2	1,116.61	1/2	1,484.05	1/2	1,851.49	1/2	2,218.93	1/2	2,586.37	1/2	2,953.81	1/2	3,321.25	1/2	3,688.69	1/2	4,056.13	1/2	4,423.57	1/2	4,791.01	1/2	5,157.31
3/4	29.94	3/4	390.68	3/4	757.82	3/4	1,124.26	3/4	1,491.70	3/4	1,859.14	3/4	2,226.58	3/4	2,594.02	3/4	2,961.46	3/4	3,328.90	3/4	3,696.34	3/4	4,063.78	3/4	4,431.22	3/4	4,798.66	3/4	5,164.39
1	34.72	1	398.33	1	765.45	1	1,131.92	1	1,499.36	1	1,866.80	1	2,234.24	1	2,601.68	1	2,969.12	1	3,336.56	1	3,704.00	1	4,071.44	1	4,438.88	1	4,806.32	1	5,173.76
1/4	41.42	1/4	405.99	1/4	773.08	1/4	1,139.57	1/4	1,507.01	1/4	1,874.45	1/4	2,241.89	1/4	2,609.33	1/4	2,976.77	1/4	3,344.21	1/4	3,711.65	1/4	4,079.09	1/4	4,446.53	1/4	4,813.97	1/4	5,181.41
1/2	48.12	1/2	413.64	1/2	780.70	1/2	1,147.23	1/2	1,514.67	1/2	1,882.11	1/2	2,249.55	1/2	2,616.99	1/2	2,984.43	1/2	3,351.87	1/2	3,719.31	1/2	4,086.75	1/2	4,454.19	1/2	4,821.63	1/2	5,188.39
3/4	54.81	3/4	421.30	3/4	788.33	3/4	1,154.88	3/4	1,522.32	3/4	1,889.76	3/4	2,257.20	3/4	2,624.64	3/4	2,992.08	3/4	3,359.52	3/4	3,726.96	3/4	4,094.40	3/4	4,461.84	3/4	4,829.28	3/4	5,195.34
2	61.51	2	428.95	2	795.96	2	1,162.54	2	1,529.98	2	1,897.42	2	2,264.86	2	2,632.30	2	2,999.74	2	3,367.18	2	3,734.62	2	4,102.06	2	4,469.50	2	4,836.94	2	5,195.30
1/4	69.17	1/4	436.61	1/4	803.59	1/4	1,170.19	1/4	1,537.63	1/4	1,905.07	1/4	2,272.51	1/4	2,639.95	1/4	3,007.39	1/4	3,374.83	1/4	3,742.27	1/4	4,109.71	1/4	4,477.15	1/4	4,844.59	1/4	5,200.12
1/2	76.82	1/2	444.26	1/2	811.22	1/2	1,177.85	1/2	1,545.29	1/2	1,912.73	1/2	2,280.17	1/2	2,647.61	1/2	3,015.05	1/2	3,382.49	1/2	3,749.93	1/2	4,117.37	1/2	4,484.81	1/2	4,852.25	1/2	5,204.94
3/4	84.48	3/4	451.92	3/4	818.84	3/4	1,185.50	3/4	1,552.94	3/4	1,920.38	3/4	2,287.82	3/4	2,655.26	3/4	3,022.70	3/4	3,390.14	3/4	3,757.58	3/4	4,125.02	3/4	4,492.46	3/4	4,859.90	3/4	5,209.76
3	92.13	3	459.57	3	826.47	3	1,193.16	3	1,560.60	3	1,928.04	3	2,295.48	3	2,662.92	3	3,030.36	3	3,397.80	3	3,765.24	3	4,132.68	3	4,500.12	3	4,867.56	3	5,214.58
1/4	99.79	1/4	467.23	1/4	834.10	1/4	1,200.81	1/4	1,568.25	1/4	1,935.69	1/4	2,303.13	1/4	2,670.57	1/4	3,038.01	1/4	3,405.45	1/4	3,772.89	1/4	4,140.33	1/4	4,507.77	1/4	4,875.21	1/4	5,218.26
1/2	107.44	1/2	474.88	1/2	841.73	1/2	1,208.47	1/2	1,575.91	1/2	1,943.35	1/2	2,310.79	1/2	2,678.23	1/2	3,045.67	1/2	3,413.11	1/2	3,780.55	1/2	4,147.99	1/2	4,515.43	1/2	4,882.87	1/2	5,221.94
3/4	115.10	3/4	482.54	3/4	849.36	3/4	1,216.12	3/4	1,583.56	3/4	1,951.00	3/4	2,318.44	3/4	2,685.88	3/4	3,053.32	3/4	3,420.76	3/4	3,788.20	3/4	4,155.64	3/4	4,523.08	3/4	4,890.52	3/4	5,225.63
4	122.75	4	490.19	4	856.98	4	1,223.78	4	1,591.22	4	1,958.66	4	2,326.10	4	2,693.54	4	3,060.98	4	3,428.42	4	3,795.86	4	4,163.30	4	4,530.74	4	4,898.18	4	5,229.31
1/4	130.41	1/4	497.85	1/4	864.61	1/4	1,231.43	1/4	1,598.87	1/4	1,966.31	1/4	2,333.75	1/4	2,701.19	1/4	3,068.63	1/4	3,436.07	1/4	3,803.51	1/4	4,170.95	1/4	4,538.39	1/4	4,905.83	1/4	5,231.86
1/2	138.06	1/2	505.50	1/2	872.24	1/2	1,239.09	1/2	1,606.53	1/2	1,973.97	1/2	2,341.41	1/2	2,708.85	1/2	3,076.29	1/2	3,443.73	1/2	3,811.17	1/2	4,178.61	1/2	4,546.05	1/2	4,913.49	1/2	5,234.41
3/4	145.72	3/4	513.16	3/4	879.87	3/4	1,246.74	3/4	1,614.18	3/4	1,981.62	3/4	2,349.06	3/4	2,716.50	3/4	3,083.94	3/4	3,451.38	3/4	3,818.82	3/4	4,186.26	3/4	4,553.70	3/4	4,921.14	3/4	5,236.97
5	153.37	5	520.81	5	887.50	5	1,254.40	5	1,621.84	5	1,989.28	5	2,356.72	5	2,724.16	5	3,091.60	5	3,459.04	5	3,826.48	5	4,193.92	5	4,561.36	5	4,928.80	5	5,239.52
1/4	161.03	1/4	528.47	1/4	895.12	1/4	1,262.05	1/4	1,629.49	1/4	1,996.93	1/4	2,364.37	1/4	2,731.81	1/4	3,099.25	1/4	3,466.69	1/4	3,834.13	1/4	4,201.57	1/4	4,569.01	1/4	4,936.45	1/4	5,240.93
1/2	168.68	1/2	536.12	1/2	902.75	1/2	1,269.71	1/2	1,637.15	1/2	2,004.59	1/2	2,372.03	1/2	2,739.47	1/2	3,106.91	1/2	3,474.35	1/2	3,841.79	1/2	4,209.23	1/2	4,576.67	1/2	4,944.11	1/2	5,242.35
3/4	176.34	3/4	543.78	3/4	910.38	3/4	1,277.36	3/4	1,644.80	3/4	2,012.24	3/4	2,379.68	3/4	2,747.12	3/4	3,114.56	3/4	3,482.00	3/4	3,849.44	3/4	4,216.88	3/4	4,584.32	3/4	4,951.76	3/4	5,243.76
6	183.99	6	551.43	6	918.01	6	1,285.02	6	1,652.46	6	2,019.90	6	2,387.34	6	2,754.78	6	3,122.22	6	3,489.66	6	3,857.10	6	4,224.54	6	4,591.98	6	4,959.42	6	5,245.18
1/4	191.65	1/4	559.09	1/4	925.64	1/4	1,292.67	1/4	1,660.11	1/4	2,027.55	1/4	2,394.99	1/4	2,762.43	1/4	3,129.87	1/4	3,497.31	1/4	3,864.75	1/4	4,232.19	1/4	4,599.63	1/4	4,967.07	1/4	5,245.60
1/2	199.30	1/2	566.74	1/2	933.26	1/2	1,300.33	1/2	1,667.77	1/2	2,035.21	1/2	2,402.65	1/2	2,770.09	1/2	3,137.53	1/2	3,504.97	1/2	3,872.41	1/2	4,239.85	1/2	4,607.29	1/2	4,974.73	1/2	5,246.02
3/4	206.96	3/4	574.40	3/4	940.89	3/4	1,307.98	3/4	1,675.42	3/4	2,042.86	3/4	2,410.30	3/4	2,777.74	3/4	3,145.18	3/4	3,512.62	3/4	3,880.06	3/4	4,247.50	3/4	4,614.94	3/4	4,982.38	3/4	5,246.45
7	214.61	7	582.05	7	948.52	7	1,315.64	7	1,683.08	7	2,050.52	7	2,417.96	7	2,785.40	7	3,152.84	7	3,520.28	7	3,887.72	7	4,255.16	7	4,622.60	7	4,990.04	7	5,246.87
1/4	222.27	1/4	589.71	1/4	956.15	1/4	1,323.29	1/4	1,690.73	1/4	2,058.17	1/4	2,425.61	1/4	2,793.05	1/4	3,160.49	1/4	3,527.93	1/4	3,895.37	1/4	4,262.81	1/4	4,630.25	1/4	4,997.69	1/4	5,247.29
1/2	229.92	1/2	597.36	1/2	963.78	1/2	1,330.95	1/2	1,698.39	1/2	2,065.83	1/2	2,433.27	1/2	2,800.71	1/2	3,168.15	1/2	3,535.59	1/2	3,903.03	1/2	4,270.47	1/2	4,637.91	1/2	5,005.35	1/2	5,247.71
3/4	237.58	3/4	605.02	3/4	971.40	3/4	1,338.60	3/4	1,706.04	3/4	2,073.48	3/4	2,440.92	3/4	2,808.36	3/4	3,175.80	3/4	3,543.24	3/4	3,910.68	3/4	4,278.12	3/4	4,645.56	3/4	5,013.00	3/4	5,248.13
8	245.23	8	612.67	8	979.03	8	1,346.26	8	1,713.70	8	2,081.14	8	2,448.58	8	2,816.02	8	3,183.46	8	3,550.90	8	3,918.34	8	4,285.78	8	4,653.22	8	5,020.66	8	5,248.55
1/4	252.89	1/4	620.33	1/4	986.66	1/4	1,353.91	1/4	1,721.35	1/4	2,088.79	1/4	2,456.23	1/4	2,823.67	1/4	3,191.11	1/4	3,558.55	1/4	3,925.99	1/4	4,293.43	1/4	4,660.87	1/4	5,028.31	1/4	5,249.01
1/2	260.54	1/2	627.98	1/2	994.29	1/2	1,361.57	1/2	1,729.01	1/2	2,096.45	1/2	2,463.89	1/2	2,831.33	1/2	3,198.77	1/2	3,566.21	1/2	3,933.65	1/2	4,301.09	1/2	4,668.53	1/2	5,035.97	1/2	5,249.47
3/4	268.20	3/4	635.64	3/4	1,001.92	3/4	1,369.22	3/4	1,736.66	3/4	2,104.10	3/4	2,471.54	3/4	2,838.98	3/4	3,206.42	3/4	3,573.86	3/4	3,941.30	3/4	4,308.74	3/4	4,676.18	3/4	5,043.62	3/4	5,249.93
9	275.85	9	643.29	9	1,009.54	9	1,376.88	9	1,744.32	9	2,111.76	9	2,479.20	9	2,846.64	9	3,214.08	9	3,581.52	9	3,948.96	9	4,316.40	9	4,683.84	9	5,051.28	9	5,250.39
1/4	283.51	1/4	650.95	1/4	1,017.17	1/4	1,384.53	1/4	1,751.97	1/4	2,119.41	1/4	2,486.85	1/4	2,854.29	1/4	3,221.73	1/4	3,589.17	1/4	3,956.61	1/4	4,324.05	1/4	4,691.49	1/4	5,058.93	1/4	5,250.85
1/2	291.16	1/2	658.60	1/2	1,024.80	1/2	1,392.19	1/2	1,759.63																				



BARGE "FMT-3114" FLORIDA MARINE INNAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

Table with columns for depth (0 FT. to 14 FT.) and corresponding capacity values for a barge. The table is organized into 15 columns representing depth intervals. Each cell contains a depth value and a capacity value in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/6/02

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT: 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT: 15'-5 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and name: INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3114" FLORIDA MARINE INNAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

Large table with columns for height (0 FT. to 14 FT.), capacity (IN), and weight (LBS). Each height row has four capacity columns (IN, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/6/02

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature 'Amur' above the text 'INSPECTORATE AMERICA CORPORATION'.



BARGE "FMT-3114" FLORIDA MARINE

OUTAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

Table with 16 columns (0 FT. to 15 FT.) and 34 rows. Each cell contains a numerical value representing capacity. A diagonal line is drawn across the table from the top-left to the bottom-right.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-4 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 12/6/02

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3114" FLORIDA MARINE

OUTGAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

Table with columns for gauge heights (0 FT. to 15 FT.) and rows for depth increments (0, 1/4, 1/2, 3/4). Includes capacity values and a '15.58' note in the 15 FT. column.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 12/6/02

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3114" FLORIDA MARINE

OUTAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

Main data table with columns for height (0 FT. to 15 FT.) and multiple rows of capacity values.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/6/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name



BARGE "FMT-3114" FLORIDA MARINE

OUTAGE TABLE

2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

Table with columns for gauge height (0 FT. to 15 FT.) and rows for capacity measurements (0 to 11). Includes sub-columns for 1/4, 1/2, and 3/4 gauge readings.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-5 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 12/6/02

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION logo



BARGE "FMT-3114" FLORIDA MARINE

OUTAGE TABLE

3 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

Table with columns for gauge height (0 FT. to 15 FT.) and rows for capacity measurements (0 to 15 FT. in 1/4, 1/2, 3/4 increments). Includes a note: CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

• CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-5" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 12/6/02

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3114" FLORIDA MARINE

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

Table with columns for gauge height (0 FT. to 15 FT.) and rows for capacity (0 to 11). Each cell contains a numerical value representing capacity in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-4 1/2" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 12/6/02

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and name



BARGE "FMT-3114" FLORIDA MARINE

OUTAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

Table with columns for height (2 FT. to 16 FT.) and rows for gauge readings (0, 1/4, 1/2, 3/4) at each height. Includes capacity values in barrels at the bottom.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11 1/2" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

STRAPPED: 12/6/02

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector

INSPECTORATE AMERICA CORPORATION



**BARGE "FMT-3114"
FLORIDA MARINE**

OUTAGE TABLE

1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

2 FT.		3 FT.		4 FT.		5 FT.		6 FT.		7 FT.		8 FT.		9 FT.		10 FT.		11 FT.		12 FT.		13 FT.		14 FT.		15 FT.		16 FT.			
0		0	5,120.17	0	4,752.73	0	4,385.29	0	4,017.85	0	3,650.41	0	3,282.97	0	2,915.53	0	2,548.09	0	2,180.65	0	1,813.21	0	1,445.77	0	1,078.33	0	712.05	0	344.75		
1/4		1/4	5,112.52	1/4	4,745.08	1/4	4,377.64	1/4	4,010.20	1/4	3,642.76	1/4	3,275.32	1/4	2,907.88	1/4	2,540.44	1/4	2,173.00	1/4	1,805.56	1/4	1,438.12	1/4	1,070.68	1/4	704.42	1/4	337.09	1/4	329.44
1/2		1/2	5,104.86	1/2	4,737.42	1/2	4,369.98	1/2	4,002.54	1/2	3,635.10	1/2	3,267.66	1/2	2,900.22	1/2	2,532.78	1/2	2,202.22	1/2	1,835.34	1/2	1,469.90	1/2	1,104.46	1/2	739.02	1/2	372.17	1/2	329.44
3/4		3/4	5,097.21	3/4	4,729.77	3/4	4,362.54	3/4	3,994.89	3/4	3,627.45	3/4	3,260.01	3/4	2,892.57	3/4	2,525.13	3/4	2,157.69	3/4	1,792.25	3/4	1,426.81	3/4	1,061.97	3/4	697.09	3/4	329.44	3/4	321.78
1		1	5,089.55	1	4,722.11	1	4,354.67	1	3,987.23	1	3,619.79	1	3,252.35	1	2,884.91	1	2,517.47	1	2,150.03	1	1,782.59	1	1,415.15	1	1,047.71	1	681.54	1	314.13	1	314.13
1/4		1/4	5,081.90	1/4	4,714.46	1/4	4,347.02	1/4	3,979.58	1/4	3,612.14	1/4	3,244.70	1/4	2,877.26	1/4	2,509.82	1/4	2,142.38	1/4	1,774.94	1/4	1,407.50	1/4	1,040.06	1/4	673.91	1/4	306.47	1/4	306.47
1/2		1/2	5,074.24	1/2	4,706.80	1/2	4,339.36	1/2	3,971.92	1/2	3,604.48	1/2	3,237.04	1/2	2,869.60	1/2	2,502.16	1/2	2,134.72	1/2	1,767.28	1/2	1,399.84	1/2	1,032.43	1/2	666.26	1/2	298.82	1/2	298.82
3/4		3/4	5,066.59	3/4	4,699.15	3/4	4,331.71	3/4	3,964.27	3/4	3,596.83	3/4	3,229.39	3/4	2,861.95	3/4	2,494.51	3/4	2,127.07	3/4	1,759.63	3/4	1,392.19	3/4	1,024.80	3/4	658.60	3/4	291.16	3/4	291.16
2		2	5,058.93	2	4,691.49	2	4,324.05	2	3,956.61	2	3,589.17	2	3,221.73	2	2,854.29	2	2,486.85	2	2,119.41	2	1,751.97	2	1,384.53	2	1,017.17	2	650.95	2	283.51	2	283.51
1/4		1/4	5,051.28	1/4	4,683.84	1/4	4,316.40	1/4	3,948.96	1/4	3,581.52	1/4	3,214.08	1/4	2,846.64	1/4	2,479.20	1/4	2,111.76	1/4	1,744.32	1/4	1,376.88	1/4	1,009.54	1/4	643.29	1/4	275.85	1/4	275.85
1/2		1/2	5,043.62	1/2	4,676.18	1/2	4,308.74	1/2	3,941.30	1/2	3,573.86	1/2	3,206.42	1/2	2,838.98	1/2	2,471.54	1/2	2,104.10	1/2	1,736.66	1/2	1,369.22	1/2	1,001.92	1/2	635.64	1/2	268.20	1/2	268.20
3/4		3/4	5,035.97	3/4	4,668.53	3/4	4,301.09	3/4	3,933.65	3/4	3,566.21	3/4	3,198.77	3/4	2,831.33	3/4	2,463.89	3/4	2,096.45	3/4	1,729.01	3/4	1,361.57	3/4	994.29	3/4	627.98	3/4	260.54	3/4	260.54
3		3	5,028.31	3	4,660.87	3	4,293.43	3	3,925.99	3	3,558.55	3	3,191.11	3	2,823.67	3	2,456.23	3	2,088.79	3	1,721.35	3	1,353.91	3	986.66	3	620.33	3	252.89	3	252.89
1/4		1/4	5,020.66	1/4	4,653.22	1/4	4,285.78	1/4	3,918.34	1/4	3,550.90	1/4	3,183.46	1/4	2,816.02	1/4	2,448.58	1/4	2,081.14	1/4	1,713.70	1/4	1,346.26	1/4	979.03	1/4	612.67	1/4	245.23	1/4	245.23
1/2		1/2	5,013.00	1/2	4,645.56	1/2	4,278.12	1/2	3,910.68	1/2	3,543.24	1/2	3,175.80	1/2	2,808.36	1/2	2,440.92	1/2	2,073.48	1/2	1,706.04	1/2	1,338.60	1/2	971.40	1/2	605.02	1/2	237.58	1/2	237.58
3/4		3/4	5,005.35	3/4	4,637.91	3/4	4,270.47	3/4	3,903.03	3/4	3,535.59	3/4	3,168.15	3/4	2,800.71	3/4	2,433.27	3/4	2,065.83	3/4	1,698.39	3/4	1,330.95	3/4	963.78	3/4	597.36	3/4	229.92	3/4	229.92
4		4	4,997.69	4	4,630.25	4	4,262.81	4	3,895.37	4	3,527.93	4	3,160.49	4	2,793.05	4	2,425.61	4	2,058.17	4	1,690.73	4	1,323.29	4	956.15	4	589.71	4	222.27	4	222.27
1/4		1/4	4,990.04	1/4	4,622.60	1/4	4,255.16	1/4	3,887.72	1/4	3,520.28	1/4	3,152.84	1/4	2,785.40	1/4	2,417.96	1/4	2,050.52	1/4	1,683.08	1/4	1,315.64	1/4	948.52	1/4	582.05	1/4	214.61	1/4	214.61
1/2	5,246.45	1/2	4,982.38	1/2	4,614.94	1/2	4,247.50	1/2	3,880.06	1/2	3,512.62	1/2	3,145.18	1/2	2,777.74	1/2	2,410.30	1/2	2,042.86	1/2	1,675.42	1/2	1,307.98	1/2	940.89	1/2	574.40	1/2	206.96	1/2	206.96
3/4	5,246.02	3/4	4,974.73	3/4	4,607.29	3/4	4,239.85	3/4	3,872.41	3/4	3,504.97	3/4	3,137.53	3/4	2,770.09	3/4	2,402.65	3/4	2,035.21	3/4	1,667.77	3/4	1,300.33	3/4	933.26	3/4	566.74	3/4	199.30	3/4	199.30
5		5	4,967.07	5	4,599.63	5	4,232.19	5	3,864.75	5	3,497.31	5	3,129.87	5	2,762.43	5	2,394.99	5	2,027.55	5	1,660.11	5	1,292.67	5	925.64	5	559.09	5	191.65	5	191.65
1/4		1/4	4,959.42	1/4	4,591.98	1/4	4,224.54	1/4	3,857.10	1/4	3,489.66	1/4	3,122.22	1/4	2,754.78	1/4	2,387.34	1/4	2,019.90	1/4	1,652.46	1/4	1,285.02	1/4	918.01	1/4	551.43	1/4	183.99	1/4	183.99
1/2		1/2	4,951.76	1/2	4,584.32	1/2	4,216.88	1/2	3,849.44	1/2	3,482.00	1/2	3,114.56	1/2	2,747.12	1/2	2,379.68	1/2	2,012.24	1/2	1,644.80	1/2	1,277.36	1/2	910.38	1/2	543.78	1/2	176.34	1/2	176.34
3/4		3/4	4,944.11	3/4	4,576.67	3/4	4,209.23	3/4	3,841.79	3/4	3,474.35	3/4	3,106.91	3/4	2,739.47	3/4	2,372.03	3/4	2,004.59	3/4	1,637.15	3/4	1,269.71	3/4	902.75	3/4	536.12	3/4	168.68	3/4	168.68
6		6	4,936.45	6	4,569.01	6	4,201.57	6	3,834.13	6	3,466.69	6	3,099.25	6	2,731.81	6	2,364.37	6	1,996.93	6	1,629.49	6	1,262.05	6	895.12	6	528.47	6	161.03	6	161.03
1/4		1/4	4,928.80	1/4	4,561.36	1/4	4,193.92	1/4	3,826.48	1/4	3,459.04	1/4	3,091.60	1/4	2,724.16	1/4	2,356.72	1/4	1,992.28	1/4	1,621.84	1/4	1,254.40	1/4	887.50	1/4	520.81	1/4	153.37	1/4	153.37
1/2		1/2	4,921.14	1/2	4,553.70	1/2	4,186.26	1/2	3,818.82	1/2	3,451.38	1/2	3,083.94	1/2	2,716.50	1/2	2,349.06	1/2	1,981.62	1/2	1,614.18	1/2	1,246.74	1/2	879.87	1/2	513.16	1/2	145.72	1/2	145.72
3/4		3/4	4,913.49	3/4	4,546.05	3/4	4,178.61	3/4	3,811.17	3/4	3,443.73	3/4	3,076.29	3/4	2,708.85	3/4	2,341.41	3/4	1,973.97	3/4	1,606.53	3/4	1,239.09	3/4	872.24	3/4	505.50	3/4	138.06	3/4	138.06
7		7	4,905.83	7	4,538.39	7	4,170.95	7	3,803.51	7	3,436.07	7	3,068.63	7	2,701.19	7	2,333.75	7	1,966.31	7	1,598.87	7	1,231.43	7	864.61	7	497.85	7	130.41	7	130.41
1/4		1/4	4,898.18	1/4	4,530.74	1/4	4,163.30	1/4	3,795.86	1/4	3,428.42	1/4	3,060.98	1/4	2,693.54	1/4	2,326.10	1/4	1,958.66	1/4	1,591.22	1/4	1,223.78	1/4	856.98	1/4	490.19	1/4	122.75	1/4	122.75
1/2		1/2	4,890.52	1/2	4,523.08	1/2	4,155.64	1/2	3,788.20	1/2	3,420.76	1/2	3,053.32	1/2	2,685.88	1/2	2,318.44	1/2	1,951.00	1/2	1,583.56	1/2	1,216.12	1/2	849.36	1/2	482.54	1/2	115.10	1/2	115.10
3/4		3/4	4,882.87	3/4	4,515.43	3/4	4,147.99	3/4	3,780.55	3/4	3,413.11	3/4	3,045.67	3/4	2,678.23	3/4	2,310.79	3/4	1,943.35	3/4	1,575.91	3/4	1,208.47	3/4	841.73	3/4	474.88	3/4	107.44	3/4	107.44
8		8	4,875.21	8	4,507.77	8	4,140.33	8	3,772.89	8	3,405.45	8	3,038.01	8	2,670.57	8	2,303.13	8	1,935.69	8	1,568.25	8	1,200.81	8	834.10	8	467.23	8	99.79	8	99.79
1/4		1/4	4,867.56	1/4	4,500.12	1/4	4,132.68	1/4	3,765.24	1/4	3,397.80	1/4	3,030.36	1/4	2,662.92	1/4	2,295.48	1/4	1,928.04	1/4	1,560.60	1/4	1,193.16	1/4	826.47	1/4	459.57	1/4	92.13	1/4	92.13
1/2		1/2	4,859.90	1/2	4,492.46	1/2	4,125.02	1/2	3,757.58	1/2	3,390.14	1/2	3,022.70	1/2	2,655.26	1/2	2,287.82	1/2	1,920.38	1/2	1,552.94	1/2	1,185.50	1/2	818.84	1/2	451.92	1/2	84.48	1/2	84.48
3/4		3/4	4,852.25	3/4	4,484.81	3/4	4,117.37	3/4	3,749.93	3/4																					



BARGE "FMT-3114" FLORIDA MARINE

OUTAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

Main data table with columns for gauge height (IN, 1/4, 1/2, 3/4) and discharge capacity (2 FT. to 16 FT.) for various levels (0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/6/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 16'-11 1/2" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate signature and text 'INSPECTORATE AMERICA CORPORATION'.



BARGE "FMT-3114" FLORIDA MARINE

OUTAGE TABLE

2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

Table with columns for gauge height (2 FT. to 16 FT.) and rows for capacity measurements. Includes a diagonal line on the left side of the table.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/6/02

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-3114" FLORIDA MARINE

OUTAGE TABLE

3 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

2 FT.		3 FT.		4 FT.		5 FT.		6 FT.		7 FT.		8 FT.		9 FT.		10 FT.		11 FT.		12 FT.		13 FT.		14 FT.		15 FT.		16 FT.	
0		0	4,602.65	0	4,350.93	0	4,099.22	0	3,847.51	0	3,595.25	0	3,253.24	0	2,889.55	0	2,525.85	0	2,162.15	0	1,798.46	0	1,434.76	0	1,071.07	0	711.78	0	348.71
1/4		1/4	4,597.40	1/4	4,345.69	1/4	4,093.98	1/4	3,842.27	1/4	3,589.82	1/4	3,245.67	1/4	2,881.97	1/4	2,518.27	1/4	2,154.58	1/4	1,790.88	1/4	1,427.18	1/4	1,063.49	1/4	704.31	1/4	341.14
1/2		1/2	4,592.16	1/2	4,340.45	1/2	4,088.73	1/2	3,837.02	1/2	3,584.00	1/2	3,238.09	1/2	2,874.39	1/2	2,510.70	1/2	2,147.00	1/2	1,783.30	1/2	1,419.61	1/2	1,055.91	1/2	696.84	1/2	333.56
3/4		3/4	4,586.91	3/4	4,335.20	3/4	4,083.49	3/4	3,831.78	3/4	3,578.18	3/4	3,230.51	3/4	2,866.82	3/4	2,503.12	3/4	2,139.42	3/4	1,775.73	3/4	1,412.03	3/4	1,048.33	3/4	689.36	3/4	325.98
1		1	4,581.67	1	4,329.96	1	4,078.25	1	3,826.53	1	3,572.36	1	3,222.93	1	2,859.24	1	2,495.54	1	2,131.85	1	1,768.15	1	1,404.45	1	1,040.76	1	681.89	1	318.41
1/4		1/4	4,576.43	1/4	4,324.71	1/4	4,073.00	1/4	3,821.29	1/4	3,566.55	1/4	3,215.36	1/4	2,851.66	1/4	2,487.96	1/4	2,124.27	1/4	1,760.57	1/4	1,396.88	1/4	1,033.18	1/4	674.42	1/4	310.83
1/2		1/2	4,571.18	1/2	4,319.47	1/2	4,067.76	1/2	3,816.05	1/2	3,560.34	1/2	3,207.78	1/2	2,844.08	1/2	2,480.39	1/2	2,116.69	1/2	1,753.00	1/2	1,389.30	1/2	1,025.60	1/2	666.95	1/2	303.25
3/4		3/4	4,565.94	3/4	4,314.23	3/4	4,062.51	3/4	3,810.80	3/4	3,554.13	3/4	3,200.20	3/4	2,836.51	3/4	2,472.81	3/4	2,109.11	3/4	1,745.42	3/4	1,381.72	3/4	1,018.13	3/4	659.37	3/4	295.67
2		2	4,560.69	2	4,308.98	2	4,057.27	2	3,805.56	2	3,547.92	2	3,192.63	2	2,828.93	2	2,465.23	2	2,101.54	2	1,737.84	2	1,374.15	2	1,010.66	2	651.79	2	288.10
1/4		1/4	4,555.45	1/4	4,303.74	1/4	4,052.03	1/4	3,800.31	1/4	3,541.71	1/4	3,185.05	1/4	2,821.35	1/4	2,457.66	1/4	2,093.96	1/4	1,730.26	1/4	1,366.57	1/4	1,003.19	1/4	644.22	1/4	280.52
1/2		1/2	4,550.21	1/2	4,298.49	1/2	4,046.78	1/2	3,795.07	1/2	3,535.11	1/2	3,177.47	1/2	2,813.78	1/2	2,450.08	1/2	2,086.38	1/2	1,722.69	1/2	1,358.99	1/2	995.72	1/2	636.64	1/2	272.94
3/4		3/4	4,544.96	3/4	4,293.25	3/4	4,041.54	3/4	3,789.83	3/4	3,528.51	3/4	3,169.90	3/4	2,806.20	3/4	2,442.50	3/4	2,078.81	3/4	1,715.11	3/4	1,351.41	3/4	988.24	3/4	629.06	3/4	265.37
3		3	4,539.72	3	4,288.01	3	4,036.29	3	3,784.58	3	3,521.91	3	3,162.32	3	2,798.62	3	2,434.93	3	2,071.23	3	1,707.53	3	1,343.84	3	980.77	3	621.49	3	257.79
1/4		1/4	4,534.47	1/4	4,282.76	1/4	4,031.05	1/4	3,779.34	1/4	3,515.31	1/4	3,154.74	1/4	2,791.05	1/4	2,427.35	1/4	2,063.65	1/4	1,699.96	1/4	1,336.26	1/4	973.30	1/4	613.91	1/4	250.21
1/2		1/2	4,529.23	1/2	4,277.52	1/2	4,025.81	1/2	3,774.09	1/2	3,508.32	1/2	3,147.16	1/2	2,783.47	1/2	2,419.77	1/2	2,056.08	1/2	1,692.38	1/2	1,328.68	1/2	965.83	1/2	606.33	1/2	242.64
3/4		3/4	4,523.99	3/4	4,272.27	3/4	4,020.56	3/4	3,768.85	3/4	3,501.33	3/4	3,139.59	3/4	2,775.89	3/4	2,412.19	3/4	2,048.50	3/4	1,684.80	3/4	1,321.11	3/4	958.36	3/4	598.75	3/4	235.06
4		4	4,518.74	4	4,267.03	4	4,015.32	4	3,763.61	4	3,494.34	4	3,132.01	4	2,768.31	4	2,404.62	4	2,040.92	4	1,677.23	4	1,313.53	4	950.88	4	591.18	4	227.48
1/4		1/4	4,513.50	1/4	4,261.79	1/4	4,010.07	1/4	3,758.36	1/4	3,487.35	1/4	3,124.43	1/4	2,760.74	1/4	2,397.04	1/4	2,033.34	1/4	1,669.65	1/4	1,305.95	1/4	943.41	1/4	583.60	1/4	219.90
1/2		1/2	4,508.25	1/2	4,256.54	1/2	4,004.83	1/2	3,753.12	1/2	3,479.97	1/2	3,116.86	1/2	2,753.16	1/2	2,389.46	1/2	2,025.77	1/2	1,662.07	1/2	1,298.38	1/2	935.94	1/2	576.02	1/2	212.33
3/4	4,683.90	3/4	4,503.01	3/4	4,251.30	3/4	3,999.59	3/4	3,747.87	3/4	3,472.59	3/4	3,109.28	3/4	2,745.58	3/4	2,381.89	3/4	2,018.19	3/4	1,654.49	3/4	1,290.80	3/4	928.47	3/4	568.45	3/4	204.75
5		5	4,497.77	5	4,246.05	5	3,994.34	5	3,742.63	5	3,465.20	5	3,101.70	5	2,738.01	5	2,374.31	5	2,010.61	5	1,646.92	5	1,283.22	5	921.00	5	560.87	5	197.17
1/4		1/4	4,492.52	1/4	4,240.81	1/4	3,989.10	1/4	3,737.39	1/4	3,457.82	1/4	3,094.13	1/4	2,730.43	1/4	2,366.73	1/4	2,003.04	1/4	1,639.34	1/4	1,275.64	1/4	913.52	1/4	553.29	1/4	189.60
1/2		1/2	4,487.28	1/2	4,235.57	1/2	3,983.85	1/2	3,732.14	1/2	3,450.24	1/2	3,086.55	1/2	2,722.85	1/2	2,359.16	1/2	1,995.46	1/2	1,631.76	1/2	1,268.07	1/2	906.05	1/2	545.72	1/2	182.02
3/4		3/4	4,482.03	3/4	4,230.32	3/4	3,978.61	3/4	3,728.90	3/4	3,442.67	3/4	3,078.97	3/4	2,715.27	3/4	2,351.58	3/4	1,987.88	3/4	1,624.19	3/4	1,260.49	3/4	898.58	3/4	538.14	3/4	174.44
6		6	4,476.79	6	4,225.08	6	3,973.37	6	3,721.65	6	3,435.09	6	3,071.39	6	2,707.70	6	2,344.00	6	1,980.31	6	1,616.61	6	1,252.91	6	891.11	6	530.56	6	166.87
1/4		1/4	4,471.55	1/4	4,219.83	1/4	3,968.12	1/4	3,716.41	1/4	3,427.51	1/4	3,063.82	1/4	2,700.12	1/4	2,336.42	1/4	1,972.73	1/4	1,609.03	1/4	1,245.34	1/4	883.64	1/4	522.98	1/4	159.29
1/2		1/2	4,466.30	1/2	4,214.59	1/2	3,962.88	1/2	3,711.17	1/2	3,419.94	1/2	3,056.24	1/2	2,692.54	1/2	2,328.85	1/2	1,965.15	1/2	1,601.46	1/2	1,237.76	1/2	876.16	1/2	515.41	1/2	151.71
3/4		3/4	4,461.06	3/4	4,209.35	3/4	3,957.63	3/4	3,705.92	3/4	3,412.36	3/4	3,048.66	3/4	2,684.97	3/4	2,321.27	3/4	1,957.57	3/4	1,593.88	3/4	1,230.18	3/4	868.69	3/4	507.83	3/4	144.13
7		7	4,455.81	7	4,204.10	7	3,952.39	7	3,700.68	7	3,404.78	7	3,040.78	7	2,677.39	7	2,313.69	7	1,950.00	7	1,586.30	7	1,222.61	7	861.22	7	500.25	7	136.56
1/4		1/4	4,450.57	1/4	4,198.86	1/4	3,947.15	1/4	3,695.43	1/4	3,397.21	1/4	3,033.51	1/4	2,669.81	1/4	2,306.12	1/4	1,942.42	1/4	1,578.72	1/4	1,215.03	1/4	853.75	1/4	492.68	1/4	128.98
1/2		1/2	4,445.33	1/2	4,193.61	1/2	3,941.90	1/2	3,690.19	1/2	3,389.63	1/2	3,025.93	1/2	2,662.24	1/2	2,298.54	1/2	1,934.84	1/2	1,571.15	1/2	1,207.45	1/2	846.28	1/2	485.10	1/2	121.40
3/4		3/4	4,440.08	3/4	4,188.37	3/4	3,936.66	3/4	3,684.95	3/4	3,382.05	3/4	3,018.36	3/4	2,654.66	3/4	2,290.96	3/4	1,927.27	3/4	1,563.57	3/4	1,199.87	3/4	838.80	3/4	477.52	3/4	113.83
8		8	4,434.84	8	4,183.13	8	3,931.41	8	3,679.70	8	3,374.47	8	3,010.78	8	2,647.08	8	2,283.39	8	1,919.69	8	1,555.99	8	1,192.30	8	831.33	8	469.95	8	106.25
1/4		1/4	4,429.59	1/4	4,177.88	1/4	3,926.17	1/4	3,674.46	1/4	3,366.90	1/4	3,003.20	1/4	2,639.50	1/4	2,275.81	1/4	1,912.11	1/4	1,548.42	1/4	1,184.72	1/4	823.86	1/4	462.37	1/4	98.67
1/2		1/2	4,424.35	1/2	4,172.64	1/2	3,920.93	1/2	3,669.21	1/2	3,359.32	1/2	2,995.62	1/2	2,631.93	1/2	2,268.23	1/2	1,904.54	1/2	1,540.84	1/2	1,177.14	1/2	816.39	1/2	454.79	1/2	91.10
3/4		3/4	4,419.11	3/4	4,167.39	3/4	3,915.68	3/4	3,663.97	3/4	3,351.74	3/4	2,988.05	3/4	2,624.35	3/4	2,260.65	3/4	1,896.96	3/4	1,533.26	3/4	1,169.57	3/4	808.92	3/4	447.21	3/4	83.52
9		9	4,413.86	9	4,162.15	9	3,910.44	9	3,658.73	9	3,344.17	9	2,980.47	9	2,616.77	9	2,253.08	9	1,889.38	9	1,525.69	9	1,161.99	9	801.44	9	439.64	9	75.94
1/4		1/4	4,408.62	1/4	4,156.91	1/4	3,905.19	1/4	3,653.48	1/4	3,336.59	1/4	2,972.89	1/4	2,609.20	1/4	2,245.50	1/4	1,881.80	1/4	1,518.11	1/4	1,154.41	1/4	793.97	1/4	432.06	1/4	68.36
1/2		1/2	4,403.37	1/2	4,151.66	1/2	3,899.95	1/2	3,648.24	1/2	3,329.01	1/2	2,965.32	1/2	2,601.62	1/2	2,237.92	1/2	1,874.23	1/2	1,510.53	1/2	1,146.84	1/2	786.50	1/2	424.48	1/2	60.79
3/4		3/4	4,398.13	3/4	4,146.42	3/4	3,894.71	3/4																					



BARGE "FMT-3114" FLORIDA MARINE

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2114-1

Table with columns for gauge height (2 FT. to 16 FT.) and rows for gauge readings (0 to 3/4) at each height. The table contains capacity values in barrels of 42 U.S. gallons.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/6/02

• CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-11" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and logo