

T.T. 183 LLC

Phone # 225-473-8222

Pipeline Test Letter


Date: 8/14/2024

To Whom it may concern:

The cargo piping and relief valve as required by 3 CFR156.170, on Tank Barge # HFL-212 was located at TT 183, LLC, was tested on 8/14/24 at 188 psi.

- Pressure gauge was found to be operating.
- The relief valve functioned as required.
- The steam piping system as tested at 125 psi.
- The steam relief valve functioned as required.




Signature of Tester :



T.T. Barge Cleaning
Mile 183, Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB – NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS
FROM BENZENE TRANSFER OPERATIONS SECTION 61.300-61.306

1. Test Method Conducted: Dry air/soap
2. Marine Vessel Owner: HFL
Address: 2302 9th Street Mandeville La 70001
3. Marine Vessel Identification Number: HFL 212
4. Testing Location: TT Barge Mile 183
5. Date: 8-14-2024
6. Tester Name: Sherman H. Carter
Company: TT 183 LLC
7. Signature of Tester: 
8. Witnessing Inspector: 
9. Witnessing Inspector Signature: 

TEST RESULTS:

Test cargo tanks and related vapor system to 16 oz.

Beginning pressure 16 oz. at 0930 time. Barge pass OK

Ending pressure 16 oz. at 0930 time.

Pressure cargo tanks and pipelines to 1.0 psig dry air record pressure allow vessel to remain pressurized for thirty minutes and use soap test to inspect for leaks.

At the end of thirty minutes record pressure reading.

Maximum Pressure Change Limits:

10,000 bbl - .20 psi

3.20 ounces per square inch

5.54 inches of water

30,000 bbl - .10 psig

1.6 ounces per square inch

2.70 inches of water

If pressure change is greater than the above limit, vessel cannot be certified. The source of the leak must be identified and repaired and the vessel retested.