T.T. 183 LLC

Pipeline Test Letter

Date: 8.142024

To Whom it may concern:

The cargo piping and relief valve as required by 3 CFR156.170, on Tank Barge # HFL 214 was located at TT 183, LLC, was tested on 8 74-202 fat 188 psi.

- Pressure gauge was found to be operating.
- The relief valve functioned as required.
 The steam piping system as tested at 125
 The steam relief valve functioned as required.

T.T. Barge Cleaning Mile 183, Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB – NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS , FROM BENZENE TRANSFER OPERATIONS SECTION 61.300-61.306

1.	Test Method Conducted: Dry air/soap
2.	Marine Vessel Owner: HFL Address: WO15 H:114Boro RIKY STE 202 Nashvill TN 37213
3.	Marine Vessel Identification Number: HFL 2/4
4,	Testing Location: TT Barge Mile 183
	Date: 8-14-2 4 Tester Name: Translation Company: Translation Tran
7.	Signature of Tester: Sherman Henderson
8.	Witnessing Inspector: Men Dugass
9.	Witnessing Inspector Signature: New Mayer
TEST RESULTS: Test cargo tanks and related vapor system to 16 oz. Beginning pressure 6 oz. at 10.33 time. Barge pass OK Ending pressure 5 oz. at 16.30 time.	
Pressure cargo tanks and pipelines to 1.0 psig dry air record pressure allow vessel to remain pressurized for thirty minutes and use soap test to inspect for leaks. At the end of thirty minutes record pressure reading.	
	aximum Pressure Change Limits: ,000 bbl20 psi 3.20 ounces per square inch 5.54 inches of water 30,000 bbl10 psig 1.6 ounces per square inch 2.70 inches of water

If pressure change is greater than the above limit, vessel cannot be certified. The source of the leak must be identified and repaired and the vessel retested.