FMT

Florida Marine Transporters, Inc.

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629- 2110 Fax

HOSE AND PIPELINE TESTS

VESSEL: HFL 3282	
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 4 CFR 35.35-70 AND 33 CFR 156.170 ON3/26/25	6
PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY. EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE	
TRANSFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I	
CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 D.C.	
CHECKED AND IS CLEAR OF POLMERIZING CARGO.	
THE ABOVE ITEMS CHECKED, TESTED, AND VERIFIED BY:	



Florida Marine Transporters, Inc.

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00 -61.306

VESSEL: HFL 3282 OFFICIAL NUMBER: 1258063
TESTING LOCATION: FITT Shippard MAXIMUM LOADING RATE (BPH) 5,000
TANK(S) TESTED: ALL PRESSURE INDICATOR:
VESSEL OWNER AND ADDRESS: Hines Furlong Line INC 4015 Hillsboro Pike StE 40
TEST RESULTS TEST RESULTS
BEGINNING PRESSURE: 28" OF H20 BEGINNING TIME: 0800
ENDING PRESSURE: 28" OF 470 ENDING TIME: 0900
TOTAL PRESSURE LOSS: 2.2" of H20
NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT. TESTER: (PRINT) WITNESS: Adam Brayd (PRINT) TESTER: (SIGN) WITNESS: (SIGN)
CALCULATION OF ALLOWABLE PRESSURE LOSS: 0.861 × 15.7 × $(5.000/30706)$ = 2.2
(TP) (L) (V) (APL)
TP= 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1 psi = 16 ounces) L= MAXIMUM LOADING RATE IN BARRELS PER HOUR V= VOLUME OF TANK(S) IN BARRELS APL= ALLOWABLE PRESSURE LOSS IN INCHES OF WATER
14.70psi = 406.8 inches of H20 1psi = 27.67 inches of H2O 1 inch = 25.40 mm 1inch = 2.54 cm 1oz = 1.729 inches OF H2O