

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL:	M7X 428	
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46CFR 35.35-70 AND 33CFR 156.170 ON		
	PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.	
	EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.	
	TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.	
NLA	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.	
· Signatura - Caracteria - Cara	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.	
THE ABOVE ITEMS CHECKED, TESTED AND VERIFIED BY:		
8	Just My of	

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: MP & 428	OFFICIAL NUMBER: 1313708	
TESTING LOCATION: DEURLL FLT		
TANK(S) TESTED: A22	PRESSURE INDICATOR: MANOMETER	
VESSEL OWNER AND ADDRESS: PLOPIDA MA	RINE 236 FIFTH ST MANDEVILLE, LA	
TEST DATE: 2-25-25 TEST	RESULTS	
	BEGINNING TIME: 1330	
ending pressure:	ENDING TIME 1400	
	ALLOWABLE PRESSURE LOSS: 2-2" 1/120	
NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS" THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT.		
	WITNESS: MATT BRAZZEC (PRINT WITNESS: (SIGN)	
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AFFILIATION OF WITNESS	
0.861 x 15.7 x (5.000 / 30.17) (L) (V	$\frac{706}{(APL)} = \frac{Z. Z}{(APL)}$	
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1) L = MAXIMUM LOADING RATE IN BARRELS PER HO V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF W	DUR	
NOTES: 14.70psi = 406.8 inches of H2O 1psi = 27.67 inches of H2O 1 inch = 25.40 mm 1inch = 2.54 cm 1oz. = 1.729 inches OF H2O		