



BARGE "FMT-3284"
FLORIDA MARINE

OUTAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. G005

Table with 17 columns representing gauge heights from 0 FT. to 15 FT. and multiple rows for each height, showing capacity values in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 04/27/2015

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-8 3/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.



INSPECTORATE

BARGE "FMT-3284"
FLORIDA MARINE

OUTAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. G005

Table with columns for height (0 FT. to 15 FT.) and multiple rows of capacity values. Includes a diagonal line on the left side of the table grid.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 04/27/2015

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-8 3/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.



INSPECTORATE

BARGE "FMT-3284"
FLORIDA MARINE

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. G005

Table with columns for gauge heights (2 FT. to 17 FT.) and rows for liquid levels (0, 1/4, 1/2, 3/4). Each cell contains a numerical value representing capacity in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 04/27/2015

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 17'-3 1/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.