



BARGE "FMT-6006"
FLORIDA MARINE
INNAGE TABLE

SLOP TANK
STAR

INSPECTORATE

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. TO-96

	0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.
0	0.00	0	51.59	0	77.39	0	103.18								
1/4	0.54	1/4	26.33	1/4	52.13	1/4	77.92								
1/2	1.07	1/2	28.67	1/2	53.67	1/2	78.46								
3/4	1.61	3/4	27.41	3/4	53.20	3/4	79.00								
1	2.15	1	27.84	1	53.74	1	79.54	1	105.33						
1 1/4	2.69	1 1/4	28.48	1 1/4	54.28	1 1/4	80.07	1 1/4	105.87						
1 1/2	3.22	1 1/2	29.02	1 1/2	54.81	1 1/2	80.61	1 1/2	106.41						
3/4	3.76	3/4	29.56	3/4	55.35	3/4	81.15	3/4	106.94						
2	4.30	2	30.09	2	55.89	2	81.68	2	107.48						
2 1/4	4.84	2 1/4	30.63	2 1/4	56.43	2 1/4	82.22	2 1/4	108.02						
1/2	5.37	1/2	31.17	1/2	56.96	1/2	82.76	1/2	108.55						
3/4	5.91	3/4	31.71	3/4	57.50	3/4	83.30	3/4	109.09						
3	6.45	3	32.24	3	58.04	3	83.83	3	109.63						
3 1/4	6.99	3 1/4	32.78	3 1/4	58.58	3 1/4	84.37	3 1/4	110.17						
1/2	7.52	1/2	33.32	1/2	59.11	1/2	84.91	1/2	110.70						
3/4	8.06	3/4	33.86	3/4	59.65	3/4	85.45	3/4	111.24						
4	8.60	4	34.39	4	60.19	4	85.98	4	111.78						
4 1/4	9.14	4 1/4	34.93	4 1/4	60.73	4 1/4	86.52	4 1/4	112.32						
1/2	9.67	1/2	35.47	1/2	61.26	1/2	87.06	1/2	112.85						
3/4	10.21	3/4	36.01	3/4	61.80	3/4	87.60	3/4	113.39						
5	10.75	5	36.54	5	62.34	5	88.13	5	113.93						
5 1/4	11.29	5 1/4	37.08	5 1/4	62.88	5 1/4	88.67	5 1/4	114.47						
1/2	11.82	1/2	37.62	1/2	63.41	1/2	89.21	1/2	115.00						
3/4	12.36	3/4	38.16	3/4	63.95	3/4	89.75	3/4	115.54						
6	12.90	6	38.69	6	64.49	6	90.28	6	116.08						
6 1/4	13.44	6 1/4	39.23	6 1/4	65.03	6 1/4	90.82	6 1/4	116.62						
1/2	13.97	1/2	39.77	1/2	65.56	1/2	91.36	1/2	117.16						
3/4	14.51	3/4	40.31	3/4	66.10	3/4	91.90	3/4	117.69						
7	15.05	7	40.84	7	66.64	7	92.43	7	118.23						
7 1/4	15.59	7 1/4	41.38	7 1/4	67.18	7 1/4	92.97	7 1/4	118.77						
1/2	16.12	1/2	41.92	1/2	67.71	1/2	93.51	1/2	119.30						
3/4	16.66	3/4	42.45	3/4	68.25	3/4	94.05	3/4	119.84						
8	17.20	8	42.99	8	68.79	8	94.59	8	120.38						
8 1/4	17.73	8 1/4	43.53	8 1/4	69.32	8 1/4	95.12	8 1/4	120.92						
1/2	18.27	1/2	44.07	1/2	69.86	1/2	95.66	1/2	121.45						
3/4	18.81	3/4	44.60	3/4	70.40	3/4	96.19	3/4	121.99						
9	19.35	9	45.14	9	70.94	9	96.73	9	122.53						
9 1/4	19.89	9 1/4	45.68	9 1/4	71.47	9 1/4	97.27	9 1/4	123.07						
1/2	20.42	1/2	46.22	1/2	72.01	1/2	97.81	1/2	123.60						
3/4	20.96	3/4	46.75	3/4	72.55	3/4	98.34	3/4	124.14						
10	21.50	10	47.29	10	73.09	10	98.88	10	124.68						
10 1/4	22.03	10 1/4	47.83	10 1/4	73.62	10 1/4	99.42	10 1/4	125.21						
1/2	22.57	1/2	48.37	1/2	74.16	1/2	99.96	1/2	125.75						
3/4	23.11	3/4	48.90	3/4	74.70	3/4	100.49	3/4	126.29						
11	23.65	11	49.44	11	75.24	11	101.03	11	126.83						
11 1/4	24.18	11 1/4	49.98	11 1/4	75.77	11 1/4	101.57	11 1/4	127.37						
1/2	24.72	1/2	50.52	1/2	76.31	1/2	102.11	1/2	127.91						
3/4	25.26	3/4	51.05	3/4	76.85	3/4	102.64	3/4	128.45						

STRAPPED: 03/26/2014

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

[Signature]
 INSPECTORATE AMERICA CORPORATION



**BARGE "FMT-6006"
FLORIDA MARINE
INNAGE TABLE**

**SLOP TANK
PORT**

HULL NO. 30-96

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

INSPECTORATE

	0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.
0	0.00	26.77	53.55	80.32	107.10										
1/4	0.56	27.33	54.11	80.88	107.66										
1/2	1.12	27.89	54.66	81.44	108.21										
3/4	1.67	28.45	55.22	82.00	108.77										
1	2.23	29.01	55.78	82.55	109.33										
1/4	2.79	29.56	56.34	83.11	109.89										
1/2	3.35	30.12	56.90	83.67	110.44										
3/4	3.90	30.68	57.45	84.23	111.00										
2	4.46	31.24	58.01	84.79	111.55										
1/4	5.02	31.79	58.57	85.34	112.12										
1/2	5.58	32.35	59.13	85.90	112.68										
3/4	6.14	32.91	59.68	86.46	113.23										
3	6.69	33.47	60.24	87.02	113.79										
1/4	7.25	34.03	60.80	87.57	114.35										
1/2	7.81	34.58	61.36	88.13	114.91										
3/4	8.37	35.14	61.92	88.69	115.46										
4	8.92	35.70	62.47	89.25	116.02										
1/4	9.48	36.26	63.03	89.81	116.58										
1/2	10.04	36.81	63.59	90.35	117.14										
3/4	10.60	37.37	64.15	90.92	117.70										
5	11.16	37.93	64.70	91.48	118.25										
1/4	11.71	38.49	65.26	92.04	118.81										
1/2	12.27	39.05	65.82	92.59	119.37										
3/4	12.83	39.60	66.38	93.15	119.93										
6	13.39	40.16	66.94	93.71	120.48										
1/4	13.95	40.72	67.49	94.27	121.04										
1/2	14.50	41.28	68.05	94.83	121.60										
3/4	15.06	41.84	68.61	95.38	122.16										
7	15.62	42.39	69.17	95.94	122.72										
1/4	16.18	42.95	69.73	96.50	123.27										
1/2	16.73	43.51	70.28	97.06	123.83										
3/4	17.29	44.07	70.84	97.62	124.39										
8	17.85	44.62	71.40	98.17	124.95										
1/4	18.41	45.18	71.96	98.73	125.51										
1/2	18.97	45.74	72.51	99.29	126.06										
3/4	19.52	46.30	73.07	99.85	126.62										
9	20.08	46.86	73.63	100.40	127.18										
1/4	20.64	47.41	74.19	100.96	127.74										
1/2	21.20	47.97	74.75	101.52	128.29										
3/4	21.75	48.53	75.30	102.08	128.85										
10	22.31	49.09	75.86	102.64	129.41										
1/4	22.87	49.64	76.42	103.19	129.97										
1/2	23.43	50.20	76.98	103.75	130.53										
3/4	23.99	50.76	77.53	104.31	131.09										
11	24.54	51.32	78.09	104.87	131.65										
1/4	25.10	51.88	78.65	105.42	132.21										
1/2	25.66	52.43	79.21	105.98	132.77										
3/4	26.22	52.99	79.77	106.54	133.33										

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 08/26/2014

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

[Signature]
INSPECTORATE AMERICA CORPORATION



BARGE "FMT-6006"
FLORIDA MARINE

OUTAGE TABLE

2 STAR

INSPECTORATE

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. TD-98

Table with columns for gauge numbers (2 FT. to 53 FT.) and corresponding measurements. Includes a 'CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS' section at the bottom.

STRAPPED: 06282014

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector

INSPECTOR BUREAU VERITAS AMERICA CORPORATION

REFERENCE GAUGE HEIGHT: 17'-3 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY.

* CAPACITY BELOW STRIKE POINT



BARGE "FMT-6006" FLORIDA MARINE

2 PORT

OUTAGE TABLE

INSPECTORATE

BARGE SHOULD BE ON EVEN LEVEL. KEEL WHEN GAUGES ARE TAKEN.

HULL NO. 70-96

Table with columns for gauge heights (2 FT. to 17 FT.) and corresponding readings. Includes a note: CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS.

INSPECTORATE AMERICA CORPORATION

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

REFERENCE GAUGE HEIGHT: 17'-4" (GAUGE POINT LOCATED NEAR CENTER OF TANK) GAUGE WITH HERMETIC GAUGE TAPE ONLY.

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-6006"
FLORIDA MARINE

1 PORT OR STAR

OUTAGE TABLE

INSPECTORATE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. TD-86

Table with 17 columns representing gauge heights from 2 FT to 17 FT. Each column contains numerical data points corresponding to the gauge height. The table is organized into three main sections: 2 FT to 6 FT, 7 FT to 11 FT, and 12 FT to 17 FT.

CAPACITIES GIVEN IN BARRELS OF U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 17'-3 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION

STRAPPED: 06282014



**BARGE "FMT-6006"
FLORIDA MARINE**

OUTAGE TABLE

INSPECTORATE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. TO-90

0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.	15 FT.	17 FT.
0	4,351.62	4,360.98	4,361.44	4,362.68	4,363.97	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
1	4,360.98	4,361.44	4,362.68	4,363.97	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
2	4,361.44	4,362.68	4,363.97	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
3	4,362.68	4,363.97	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
4	4,363.97	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
5	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
6	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
7	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
8	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
9	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
10	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
11	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
12	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
13	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
14	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
15	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
16	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25
17	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25	4,375.25

STRAPPED: 00/28/2014

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

[Signature]
INSPECTORATE AMERICA CORPORATION

REFERENCE GAUGE HEIGHT: 15'-9" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

* CAPACITY BELOW STRIKE POINT



BARGE "FMT-6006"
FLORIDA MARINE

2 STAR

OUTAGE TABLE

INSPECTORATE

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. TD-88

Table with columns for gauge height (0 FT. to 15 FT.) and corresponding capacity values. The table is organized in 5-foot increments, with each gauge height having multiple capacity readings.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: '15-9 1/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED
NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION

STRAPPED: 03/26/2014



BARGE "FMT-6006"
FLORIDA MARINE

2 PORT

OUTAGE TABLE

INSPECTORATE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 10-86

Table with columns for gauge height (0 FT. to 54 FT.), capacity (0 to 300.98), and other measurements. The table is organized into 14 vertical sections, each representing a different gauge location along the barge's length.

CAPACITIES GIVEN IN BARRELS OF #2 U.S. GALLONS

STRAPPED: 08/28/2014

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

REFERENCE GAUGE HEIGHT: 15'-9" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

INSPECTORATE AMERICA CORPORATION



BARGE "FMT-6006" FLORIDA MARINE

1 PORT OR STAR

OUTRAGE TABLE

BARGE SHOULD BE ON EVEN LEVEL. KEEL WHEN GAUGES ARE TAKEN

INSPECTORATE

Table with 23 columns: 0 FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT., 15 FT. Each column contains numerical data and a letter code.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15.9 1/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION

STRAPPED: 08282014



3 PORT OR STAR
FLORIDA MARINE

INNAGE TABLE

INSPECTORATE

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 10-95

Table with columns for height (0 FT. to 15 FT.) and corresponding capacity values. The table is organized into sections for different gauge heights and includes a 'CAPACITIES GIVEN IN BARRELS OF U.S. GALLONS' section at the bottom.

CAPACITIES GIVEN IN BARRELS OF U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-8 1/2" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature

INSPECTORATE AMERICA CORPORATION

STRAPPED: 02/26/2014



BARGE "FMT-6006"
FLORIDA MARINE

INNAGE TABLE

2 PORT OR STAR

INSPECTORATE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 10-36

Table with 20 columns (0 FT. to 15 FT.) and 20 rows of data. Each cell contains a numerical value representing volume or measurement at a specific height and distance.

STRAPPED: 08282014

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

REFERENCE GAUGE HEIGHT: 15'-9 1/2" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

* CAPACITY BELOW STRIKE POINT

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS



BARGE "FMT-6006"
FLORIDA MARINE

INNAGE TABLE

1 PORT OR STAR

INSPECTORATE

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 70-96

Table with columns for gauge height (0 FT. to 15 FT.) and corresponding capacity values. Includes a 'CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS' note at the bottom.

INSPECTORATE

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-9 1/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 022620014

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature

INSPECTORATE AMERICA CORPORATION