FMT

Florida Marine Transporters, Inc.

2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

VESSEL: FMT 1418
THE FOLLOWING ITEMS HAVE BEEN CHECKED AND TESTED IN ACCORDANCE WITH 46 CFR 35.35-70 AND 33 CFR 156.170 ON 1/3/25
PRESSURE GAUGES HAVE BEEN CHECKED
TOTAL TOTAL OF ACCORACY.
EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
TRANSFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I
ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
VAPOR PIPELINE HAS BEEN VISUALLY CHECKED AND IS CLEAR OF POLMERIZING CARGO.
THE ABOVE ITEMS CHECKED, TESTED, AND VERIFIED BY:

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FAT 1418	OFFICIAL NUMBER: 1299469	
TESTING LOCATION: FMT Shipyard	MAXIMUM LOADING RATE (BPH) 4, 285	
TANK(S) TESTED: ALL	PRESSURE INDICATOR: MANOMETER	
VESSEL OWNER AND ADDRESS: FLORIDA MI	PRINE 2360 FIFTH ST- MANDEVILLE L	
TEST RESULTS		
TEST DATE: 1/3/25		
BEGINNING PRESSURE: 28" of 42 °	BEGINNING TIME: 0800	
ENDING PRESSURE: 28" of 420	ENDING TIME: 0900	
TOTAL PRESSURE LOSS:	ALLOWABLE PRESSURE LOSS: 4,90 ec/420	
NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TO	TAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"	
	CCORDANCE WITH SECTION 61.304F, AND IS RED VAPOR TIGHT.	
TESTER: (PRINT)	WITNESS: Adam brand (PRINT)	
TESTER: (SIGN)	WITNESS: (SIGN)	
	FMT	
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AFFILIATION OF WITNESS	
	4.90	
0.861 x 14.7 x (4,285 / 1/,	$V) = \frac{V}{(APL)}$	
, , , , , ,		
IP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (L = MAXIMUM LOADING RATE IN BARRELS PER H V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF V	OUR	
NOTES: 14.70psi = 406.8 inches of H20	TALER	
1psi = 27.67 inches of H2O		
1 inch = 25.40 mm		
linch = 2.54 cm loz. = 1.729 inches OF H2O		