2360 Fifth Street Mandeville, LA 70471 (985) 629-2082 Phone (985) 629-2110 Fax

HOSE AND PIPELINE TESTS

	VESSEL:	FMT 3184
		#1
THE FOLLOW 46CFR 35.	VING ITEMS HAVE BE 35-70 AND 33CFR 1	EN CHECKED AND TESTED IN ACCORDANCE WITH 56.170 ON/~/S25
		,
		PRESSURE GAUGES HAVE BEEN CHECKED WITHIN 10% OF ACCURACY.
2.8.5		EMERGENCY SHUTDOWN HAS BEEN CHECKED AND FOUND OPERABLE.
z		TRASFER SYSTEM RELIEF VALVE HAS BEEN TESTED AND CHECKED - 125 P.S.I.
	- Alexander	ALL TRANSFER PIPING SYSTEMS AND ASSOCIATED VALVES HAVE BEEN TESTED AND CHECKED AT 187.5 P.S.I.
_	W/A	CARGO HOSE VISUALLY AND HYDROSTATICALLY CHECKED TO 225 P.S.I.
	8	TOTAL MAINTENANT DAY OF
THE ABOVE	ITEMS CHECKED, T	STED AND VERIFIED BY:

Florida Marine Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FMT 3184	OFFICIAL NUMBER: 1186297
TESTING LOCATION: NAT MAIN KY	MAXIMUM LOADING RATE (BPH) 5,000
TANK(S) TESTED: ALL	PRESSURE INDICATOR: MANOMETER
VESSEL OWNER AND ADDRESS: FLORIDA MI	ARINE 2360 FIFTH ST. MANDEULLE
	RESULTS
TEST DATE:	N*11
TEST DATE:(~/5~25 BEGINNING PRESSURE:28" of 442 o	BEGINNING TIME: /300
ENDING PRESSURE: 28" OF 1420	ENDING TIME:
TOTAL PRESSURE LOSS:	ALLOWABLE PRESSURE LOSS: 2.2" H20
NOTE: VESSEL IS CONSIDERED YAPOR TIGHT IF "TOT	AL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
CONSIDER	CCORDANCE WITH SECTION 61.304F, AND IS ED VAPOR TIGHT.
TESTER: D.J. C.DID (PRINT) TESTER: (SIGN)	Ent
CALCULATION OF ALLOWABLE PRESSURE LOSS:	AFFILIATION OF WITNESS
0.861 x 15.7 x (5,000 / 30,	(APL) = (APL)
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (L = MAXIMUM LOADING RATE IN BARRELS PER H V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF TANK 14.70psi = 406.8 inches of H2O 1 psi = 27.67 inches of H2O 1 inch = 25.40 mm 1 inch = 2.54 cm 1 oz = 1.729 inches OF H2O	OUR